

Novell GroupWise®

7

August 15, 2005

TROUBLESHOOTING 1:
ERROR MESSAGES

www.novell.com

N

Novell®

Legal Notices

Novell, Inc. makes no representations or warranties with respect to the contents or use of this documentation, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc. reserves the right to revise this publication and to make changes to its content, at any time, without obligation to notify any person or entity of such revisions or changes.

Further, Novell, Inc. makes no representations or warranties with respect to any software, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc. reserves the right to make changes to any and all parts of Novell software, at any time, without any obligation to notify any person or entity of such changes.

Any products or technical information provided under this Agreement may be subject to U.S. export controls and the trade laws of other countries. You agree to comply with all export control regulations and to obtain any required licenses or classification to export, re-export, or import deliverables. You agree not to export or re-export to entities on the current U.S. export exclusion lists or to any embargoed or terrorist countries as specified in the U.S. export laws. You agree to not use deliverables for prohibited nuclear, missile, or chemical biological weaponry end uses. Please refer to www.novell.com/info/exports/ for more information on exporting Novell software. Novell assumes no responsibility for your failure to obtain any necessary export approvals.

Copyright © 1993-2005 Novell, Inc. All rights reserved. No part of this publication may be reproduced, photocopied, stored on a retrieval system, or transmitted without the express written consent of the publisher.

Novell, Inc. has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more of the U.S. patents listed at <http://www.novell.com/company/legal/patents/> and one or more additional patents or pending patent applications in the U.S. and in other countries.

Novell, Inc.
404 Wyman Street, Suite 500
Waltham, MA 02451
U.S.A.

www.novell.com

GroupWise 7 Troubleshooting 1: Error Messages

[August 15, 2005](#)

Online Documentation: To access the online documentation for this and other Novell products, and to get updates, see www.novell.com/documentation.

Novell Trademarks

ConsoleOne is a registered trademark of Novell, Inc. in the United States and other countries.

eDirectory is a trademark of Novell, Inc.

GroupWise is a registered trademark of Novell, Inc. in the United States and other countries.

IPX is a trademark of Novell, Inc.

NetWare is a registered trademark of Novell, Inc. in the United States and other countries.

NDS is a registered trademark of Novell, Inc. in the United States and other countries.

NLM is a trademark of Novell, Inc.

Novell is a registered trademark of Novell, Inc. in the United States and other countries.

QuickFinder is a trademark of Novell, Inc.

Third-Party Materials

All third-party trademarks are the property of their respective owners.

Contents

About This Guide	7
Part I GroupWise Engine Error Codes	
0xxx Engine Error Codes	11
8xxx Engine Error Codes	13
9xxx Engine Error Codes	39
Axxx Engine Error Codes	41
Bxxx Engine Error Codes	49
Cxxx Engine Error Codes	51
Dxxx Engine Error Codes	75
Exxx Engine Error Codes	129
Fxxx Engine Error Codes	147
Part II Agent Error Messages	
Post Office Agent Error Messages	169
Message Transfer Agent Error Messages	181
Internet Agent Error Messages	201
WebAccess Agent Error Messages	207
Monitor Agent and Application Error Messages	219
Part III Administration Error Messages	
GroupWise Administrator Snap-In to ConsoleOne Error Messages	225
GroupWise Check Error Codes	233
GroupWise Time Stamp Utility Error Messages	249
Part IV Client Error Messages	
Windows Client Error Messages	253
Remote Mode Windows Client Error Messages	255
Cross-Platform Client Error Messages	261

About This Guide

This Novell® *GroupWise*® 7 *Troubleshooting 1 Guide* guide covers error messages that appear in ConsoleOne®, GroupWise agents, and GroupWise clients, along with possible causes and suggested actions to resolve the problem. The guide is divided into the following sections:

- ◆ “GroupWise Engine Error Codes” on page 9
- ◆ “Agent Error Messages” on page 167
- ◆ “Administration Error Messages” on page 223
- ◆ “Client Error Messages” on page 251

Other sources of troubleshooting assistance include:

- ◆ Novell Support (<http://support.novell.com>)
- ◆ Novell Support Knowledgebase (http://support.novell.com/search/kb_index.jsp)
- ◆ GroupWise 7 Support Forums (<http://support.novell.com/forums/2gw.html>)
- ◆ Novell GroupWise Support Community (<http://support.novell.com/products/groupwise>)
- ◆ GroupWise Cool Solutions (<http://www.novell.com/cool solutions/gwmag/index.html>)

Additional Documentation

For additional GroupWise documentation, see the following guides at the [GroupWise 7 documentation Web site \(http://www.novell.com/documentation/lg/gw7\)](http://www.novell.com/documentation/lg/gw7):

- ◆ *Installation Guide*
- ◆ *Administration Guide*
- ◆ *Multi-System Administration Guide*
- ◆ *Interoperability Guide*
- ◆ *Troubleshooting 2: Solutions to Common Problems*
- ◆ *Troubleshooting 3: Message Flow and Directory Structure*
- ◆ *GroupWise Client User Guides*

Documentation Updates

For the most recent version of the *GroupWise 7 Troubleshooting 1 Guide*, visit the [Novell GroupWise 7 documentation Web site \(http://www.novell.com/documentation/lg/gw7\)](http://www.novell.com/documentation/lg/gw7).

Documentation Conventions

In Novell documentation, a greater-than symbol (>) is used to separate actions within a step and items in a cross-reference path.

A trademark symbol (™, ®, etc.) denotes a Novell trademark. An asterisk denotes a third-party trademark.

When a single pathname can be written with a backslash for some platforms or a forward slash for other platforms, the pathname is presented with a backslash. Users of platforms that require a forward slash, such as Linux*, should use forward slashes as required by your software.

When a startup switch can be written with a forward slash for some platforms or a double hyphen for other platforms, the startup switch is presented with a forward slash. Users of platforms that require a double hyphen, such as Linux, should use double hyphens as required by your software.

User Comments

We want to hear your comments and suggestions about this manual and the other documentation included with this product. Please use the User Comment feature at the bottom of each page of the online documentation, or go to www.novell.com/documentation/feedback.html and enter your comments there.



GroupWise Engine Error Codes

GroupWise engine code underlies all aspects of GroupWise[®], including the GroupWise client, the agents, and the GroupWise snap-ins to ConsoleOne[®]. An engine error code can be displayed from any GroupWise component.

This part of *Troubleshooting 1: Error Messages* helps you resolve engine error codes in any GroupWise component.

- ◆ “0xxx Engine Error Codes” on page 11
- ◆ “8xxx Engine Error Codes” on page 13
- ◆ “9xxx Engine Error Codes” on page 39
- ◆ “Axxx Engine Error Codes” on page 41
- ◆ “Bxxx Engine Error Codes” on page 49
- ◆ “Cxxx Engine Error Codes” on page 51
- ◆ “Dxxx Engine Error Codes” on page 75
- ◆ “Exxx Engine Error Codes” on page 129
- ◆ “Fxxx Engine Error Codes” on page 147

Other sources of assistance include:

- ◆ Novell[®] Support (<http://support.novell.com>)
- ◆ Novell Support Knowledgebase (http://support.novell.com/search/kb_index.jsp)
- ◆ GroupWise 7 Support Forums (<http://support.novell.com/forums/2gw.html>)
- ◆ Novell GroupWise Support Community (<http://support.novell.com/products/groupwise>)
- ◆ GroupWise Cool Solutions (<http://www.novell.com/coolsolutions/gwmag/index.html>)

0xxx Engine Error Codes

Range: 000x

“0002 Unexpected error” on page 11

“0003 Encryption password failed verification process” on page 11

“0004 Encryption password too long” on page 11

“0005 Unexpected error” on page 11

“0006 Unexpected error” on page 11

“0007 Unexpected error” on page 12

“0008 Unexpected error” on page 12

0002 Unexpected error

Source: GroupWise® engine; encryption.

Action: See “000x Unexpected error” on page 12.

0003 Encryption password failed verification process

Source: GroupWise engine; encryption.

Explanation: Wrong encryption password.

Action: Enter the correct password.

0004 Encryption password too long

Source: GroupWise engine; encryption.

Explanation: Password too long.

Action: Reduce the password length.

0005 Unexpected error

Source: GroupWise engine; encryption.

Action: See “000x Unexpected error” on page 12

0006 Unexpected error

Source: GroupWise engine; encryption.

Action: See “000x Unexpected error” on page 12

0007 Unexpected error

Source: GroupWise engine; encryption.

Action: See [“000x Unexpected error” on page 12](#)

0008 Unexpected error

Source: GroupWise engine; encryption.

Action: See [“000x Unexpected error” on page 12](#)

000x Unexpected error

Source: GroupWise engine; encryption.

Explanation: An engine error has occurred for which GroupWise does not have a specific error message.

Action: Exit and then restart the GroupWise client.

8xxx Engine Error Codes

Range:

- ◆ 81xx
- ◆ 82xx
- ◆ 85xx
- ◆ 88xx
- ◆ 89xx
- ◆ 8Bxx
- ◆ 8Cxx
- ◆ 8Fxx

Range: 81xx

“8101 Memory error” on page 15

Range: 82xx

- “8200 File I/O error” on page 16
- “8201 Access to file denied” on page 17
- “8202 Cannot access required file” on page 18
- “8203 Cannot copy file or directory” on page 18
- “8204 Disk full” on page 19
- “8205 End of file” on page 19
- “8206 Cannot open file” on page 20
- “8207 Cannot locate file” on page 20
- “8208 Cannot modify file” on page 20
- “8209 Path not found” on page 21
- “820B Path too long” on page 22
- “820E Cannot lock file” on page 23
- “8210 Cannot create path” on page 23
- “8211 Cannot rename file” on page 24
- “8212 Password incorrect” on page 24
- “8214 Unsupported encryption level” on page 24

“8215 Path root error” on page 25
“8219 Cannot connect to remote network resource” on page 25
“821A Access to a critical file denied” on page 25

Range: 85xx

“8502 Cannot initialize protocol” on page 25
“8503 Cannot connect to specified IP address” on page 25
“8509 Cannot access TCP/IP services” on page 26
“850F Connection no longer valid” on page 26
“8555 Port in use” on page 26
“8562 Client/server request packet contained invalid identifier” on page 27
“8563 Client/server request packet contained invalid identifier” on page 27
“8567 Data not in BCEF format” on page 27
“8568 HTTP port already in use” on page 27
“8569 SSL login required for this post office” on page 27
“8570 IMAP port already in use” on page 28
“8571 SOAP port already in use” on page 28
“8572 CAP port already in use” on page 28
“8573 LDAP port already in use” on page 28

Range: 88xx

“8809 Unexpected error” on page 28
“880B Unexpected error” on page 28
“880C Unexpected error” on page 29

Range: 89xx

“8901 Cannot use TCP/IP services” on page 29
“8902 Cannot load TCP/IP services” on page 29
“8903 Cannot use TCP/IP services” on page 29
“8906 Cannot use TCP/IP services” on page 29
“8907 Cannot use TCP/IP services” on page 29
“8908 Cannot connect to specified address” on page 29
“8909 Cannot use TCP/IP services” on page 30
“890A Cannot listen on specified port” on page 30
“890B Cannot accept incoming connection” on page 30
“890F Connection no longer valid” on page 30
“8910 Cannot read on connection” on page 31
“8911 Cannot write on connection” on page 31
“8912 Cannot read on connection; timed out” on page 31
“8913 Cannot write on connection; timed out” on page 32
“8916 Cannot use TCP/IP services” on page 32
“8917 TCP/IP name lookup failed” on page 32

“8918 UDP send failed” on page 32
“8919 Attempt to bind to a non-existent IP address” on page 32
“891A TCP/IP data is not ready for reading” on page 33
“891B No SSL certificate supplied” on page 33
“891C Bad SSL certificate” on page 33
“891D Bad SSL private key or password” on page 33
“891E Insufficient memory for SSL” on page 34
“891F Invalid SSL certificate” on page 34
“8920 SSL certificate and private key do not match” on page 34
“8921 SSL accept failure” on page 34
“8922 SSL connect failure” on page 35
“8923 Insufficient memory for SSL” on page 35
“8924 SSL handshake timeout failure” on page 35
“8925 Connection refused” on page 35
“8926 Unknown host” on page 36
“8927 Host not reachable” on page 36

Range: 8Bxx

“8B02 Unexpected error” on page 36

Range: 8Cxx

“8C04 Unexpected error” on page 36
“8C09 Unexpected error” on page 36
“8C0A Unexpected error” on page 36
“8C88 Unexpected error” on page 37

Range: 8Fxx

“8F03 Invalid configuration option” on page 37

8101 Memory error

Source: GroupWise® engine; memory management.

Explanation: Memory function failure. Invalid memory handle.

Possible Cause: If this error occurs in the NetWare® POA, there might be insufficient memory on the server for the POA to run. On the server where the POA runs, cache buffers should be around 60%. If cache buffers drop below 30%, there is not enough memory available.

Action: Unload some other NLM™ programs or add memory to the server. In some cases, the insufficient memory condition is temporary. GroupWise automatically resends unsuccessful messages, so no action might be required.

Possible Cause: If this error occurs in the NetWare POA, some current server parameters might be set too low.

Action: Increase the settings for the following NetWare server parameters:

- ◆ Minimum Packet Receive Buffers

- ◆ Maximum Directory Cache Buffers
- ◆ Maximum Services Processes

Many factors influence what the proper settings should be for a particular server. Make sure each parameter is set to at least 1000 and increase settings from there as needed. For more information, see “[Fine-Tuning Your NetWare POA Installation](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

- Possible Cause: If this error occurs in the NetWare agents after updating your GroupWise system, you might not have updated the agents properly.
- Action: After exiting all the agents, unload the agent engine (`gwenn5.nlm`), then perform the update. See “[Updating Your GroupWise 6.x System to Version 7](#)” in “[Update](#)” in the “*GroupWise 7 Installation Guide*”.
- Possible Cause: If this error occurs when starting the GroupWise client, the user might have exceeded the limit of viewable 65,000 items per folder. Remember that Trash is considered a folder.
- Action: Delete items or move them to a different folder. Empty the Trash.
- Possible Cause: If this error occurs when manually addressing a message to multiple external recipients, the user might have typed one or more addresses incorrectly in such a way that the client exceeded available memory trying to resolve the erroneous external addresses. For example, leaving out the at (@) sign can cause this problem.
- Action: Users should select recipients from the Address Book whenever possible. If users must type external addresses, care should be used to type the addresses correctly, especially in cases where the number of recipients is large.
- Possible Cause: If this error occurs in the GroupWise client in Remote mode, GroupWise might not be installed correctly on the remote computer.
- Action: Reinstall GroupWise on the remote computer. See the platform-specific setup instructions for using Remote mode in “[GroupWise Modes](#)” in “[Client](#)” in the *GroupWise 7 Administration Guide*.
- Possible Cause: This error can occasionally be caused by damaged databases.
- Action: Check, and, if necessary, repair databases accessed by the user who is receiving the error. See “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

8200 File I/O error

- Source: GroupWise engine; file input/output.
- Explanation: Generic file I/O error. Any file I/O error that cannot be mapped to a more specific file I/O error message.
- Possible Cause: A GroupWise database has been damaged so it is unrecognizable as a GroupWise database, for example, having a size of 0 KB or 2 GB.
- Action: For the locations of GroupWise databases in domains and post offices, see “[Domain Directory](#)” and “[Post Office Directory](#)” in “[Directory Structure Diagrams](#)” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. Restore the damaged databases from backup.
- Possible Cause: One or more of the GroupWise databases might have an invalid owner or no owner.
- Action: Check the ownership of the GroupWise databases. If necessary, change the ownership to a valid user such as the system administrator.

Possible Cause: If this error occurs when users are trying to log in to GroupWise through the GroupWise Internet Agent from a POP3 mail client, the post office link information needed by the GroupWise Internet Agent might be incorrect.

Action: Check the post office link set up for the GroupWise Internet Agent. In ConsoleOne[®], browse to and select the Domain object where the Internet Agent is installed. Right-click the GWIA object, then click Properties. Click Post Office Links, select the post office, then click Edit Link. Make sure the IP address and TCP port for the POA are specified correctly in the Client/Server Access box. See “Internet Agent” in the *GroupWise 7 Administration Guide*.

8201 Access to file denied

Source: GroupWise engine; file input/output.

Explanation: Access denied. The program tried to access or open a file that did not have or allow sharing. The program might also have tried to create a file that already exists.

Possible Cause: If this error occurs from the POA, the POA might not have access to a required file.

Action: Start the POA including the /rights switch to determine the specific problem the POA is encountering. See “Using POA Startup Switches” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs when creating a post office, you might not be connected to the domain in which you are trying to create the post office.

Action: Connect to the domain where you want the post office located. See “Connecting to a Domain” in “Domains” in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs when trying to access the account of a new user, some required files might be missing from the post office directory.

Action: See “Post Office Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. Make sure all required files are present in the post office directory, especially the *.dc files, which are required for creating new user and message databases. If *.dc files are missing, copy them from another post office or from the po subdirectory of the software distribution directory.

Possible Cause: If this error occurs for a user who has previously been able to access GroupWise successfully, the user’s Novell[®] eDirectory™ object might have become damaged.

Action: Delete the user object from eDirectory, then re-create it. Do not delete the user’s GroupWise account, because this would delete the user’s mailbox as well.

Possible Cause: If this error occurs when users exit the GroupWise client, the users might have the archive directory set to a location where they do not have sufficient rights.

Action: In the GroupWise client, check the users’ path to the archive directory. Look up “archive, directory” in GroupWise client Help. Make sure users have sufficient rights to create and modify files there. Or have users change their archive directory to a location where they already have sufficient rights.

Possible Cause: If this error occurs when users exit the GroupWise client, the user database (userxxx.db) might be damaged.

Action: Check and, if necessary, repair the user database. See “Maintaining User/Resource and Message Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck. See “Standalone Database Maintenance Programs” in “Databases” in the *GroupWise 7 Administration Guide*.

- Possible Cause: If this error occurs when a user is running in Caching mode or Remote mode, the user's local databases might be damaged.
- Action: Repair the user's Caching or Remote mailbox. See "Tools for Analyzing and Correcting GroupWise Client Problems" in "Client" in the *GroupWise 7 Administration Guide*.
- Possible Cause: The GroupWise databases might be owned by an invalid user.
- Action: For the locations of GroupWise databases in domains and post offices, see "Domain Directory" and "Post Office Directory" in "Directory Structure Diagrams" in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. Check the ownership of the GroupWise databases. If necessary, change the ownership to a valid user such as the system administrator.
- Possible Cause: Another program might already have the required file open with exclusive access.
- Action: Check the open/lock activity on GroupWise databases and other files. You might find that a backup program or virus scanner is holding the file open.
- Action: Use backup software that interacts properly with GroupWise file locking, as described in "Target Service Agents" in "Databases" in the *GroupWise 7 Administration Guide*.
- Possible Cause: The GroupWise client has been installed on the local drive, so the program can still run, but the network connection to the post office has been lost.
- Action: When the network connection to the post office is reestablished, the GroupWise client will function normally again. Reboot the server. If the post office still cannot be accessed, resolve those network problems.

8202 Cannot access required file

- Source: GroupWise engine; file input/output.
- Explanation: Bad file handle.
- Possible Cause: GroupWise is no longer able to access a required file.
- Action: Exit and then restart the GroupWise program that displayed the error.
- Possible Cause: An invalid or old (closed) file handle was passed to a file I/O function.
- Action: Perform the action again. If the same error occurs, exit and then restart the GroupWise program that displayed the error.

8203 Cannot copy file or directory

- Source: GroupWise engine; file input/output.
- Explanation: Copy error.
- Possible Cause: If this error occurs when trying to rebuild a post office database, the domain or the post office might not contain the correct files.
- Action: For the required contents of domains and post offices, see "Domain Directory" and "Post Office Directory" in "Directory Structure Diagrams" in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. Make sure the post office you are trying to rebuild and the domain it belongs to contain the correct files (especially *.dc files).
- Possible Cause: If this error occurs in the GroupWise client in Remote mode, there might be a problem with the structure or content of the Remote mailbox. For example, copying a GroupWise client installation from one laptop to another might introduce this problem.
- Action: Delete the **rofdata** directory on the remote computer, then request all information from the master mailbox again.

Action: Reinstall the GroupWise client on the remote computer. See the platform-specific setup instructions for using Remote mode in “GroupWise Modes” in “Client” in the *GroupWise 7 Administration Guide*.

8204 Disk full

Source: GroupWise engine; file input/output.

Explanation: Disk full.

Possible Cause: There is no space left on a disk when writing and/or creating a file.

Action: Create space on disk by deleting unwanted or unnecessary files.

Possible Cause: One or more of the GroupWise databases might have an invalid owner or no owner.

Action: For the locations of GroupWise databases in domains and post offices, see “Domain Directory” and “Post Office Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. Check the ownership of the GroupWise databases. If necessary, change the ownership to a valid user such as the system administrator.

Possible Cause: The owner of a GroupWise database has a space restriction on the volume where the database resides and that limit has been reached, so that the database cannot grow any larger.

Action: Check the ownership of these databases and make sure that owner does not have disk space restrictions.

Action: If disk space is available and database ownership is correct, the disk itself might need repair.

Possible Cause: If this error occurs from the POA, there might be a problem with its input queue.

Action: Stop the POA. Rename the **wpcout** directory in the post office. Restart the POA. This re-creates the wpcout directory structure for the post office. If the POA now runs without the error, copy message files from the subdirectories of the original wpcout structure into the corresponding subdirectories of the newly created wpcout directory so the POA can process them.

Possible Cause: If this error occurs on a server where the NetWare POA performs a substantial amount of indexing, temporary files that are created and deleted, but not purged, can build up on the server. Most of these temporary files are created and deleted in the index subdirectories of libraries and users’ mailboxes, but some are placed at the root of the sys: volume on NetWare servers.

Action: Purge deleted files from index subdirectories and the root of the sys: volume on the server where the problem is occurring.

8205 End of file

Source: GroupWise engine; file input/output.

Explanation: End of file was reached unexpectedly.

Possible Cause: The **ngwguard.db** file has been damaged.

Action: Check the size of the **ngwguard.rfl** file (roll forward log). If it is less than 24 KB, it is considered empty. Make backup copies of the **ngwguard.db**, **ngwguard.rfl**, and **ngwguard.fbk** files. Delete the **ngwguard.db** file, then copy **ngwguard.fbk** to **ngwguard.db**. Be sure to copy it; do not rename it. See also “Information Stored in the Post Office” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

Possible Cause: One or more of the GroupWise databases might have an invalid owner or no owner. For the locations of critical GroupWise databases in domains and post offices, see “Domain Directory” and “Post Office Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

Action: Check the ownership of the GroupWise databases. If necessary, change the ownership to a valid user such as the system administrator.

8206 Cannot open file

Source: GroupWise engine; file input/output.

Explanation: File open error.

Possible Cause: GroupWise cannot copy the specified file. During an explicit file copy function, failure to create the destination file generates this error. If the destination file exists and is read only, this error might occur.

Action: Check destination filename specified and ensure it is unique.

Possible Cause: If this error occurs the first time a user tries to archive messages, the user might not have sufficient rights to the archive location.

Action: Check the user's rights to the archive location. Grant the user the rights necessary to create the archive, or suggest a location where the user already has sufficient rights to create the archive.

Possible Cause: If this error occurs when updating the GroupWise client software, users might be running the client software.

Action: Perform the update when no one is using the GroupWise client, or send a broadcast message asking all users to exit so you can update the software. Check the open/lock activity on the GroupWise program files.

Possible Cause: If this error occurs from the POA, the POA might not have access to a required file.

Action: Start the POA including the `/rights` switch to determine the specific problem the POA is encountering. See "Using POA Startup Switches" in "Post Office Agent" in the *GroupWise 7 Administration Guide*.

8207 Cannot locate file

Source: GroupWise engine; file input/output.

Explanation: File seek error.

Possible Cause: A failure occurred when positioning file pointers during an explicit file copy function. Cannot open the specified file or directory.

Possible Cause: If this error occurs when a specific user starts the GroupWise client, that user database (`userxxx.db`) might be damaged.

Action: Check and, if necessary, repair the database. See "Maintaining User/Resource and Message Databases" in "Databases" in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck. See "Standalone Database Maintenance Programs" in "Databases" in the *GroupWise 7 Administration Guide*.

8208 Cannot modify file

Source: GroupWise engine; file input/output.

Explanation: File modify error.

Possible Cause: Cannot move or rename the file. An error occurred when renaming or moving a file to another location.

Action: Check to see if another file with the same name exists (the filename must be unique). If so, rename that file, or move or rename the current file.

8209 Path not found

Source: GroupWise engine; file input/output.

Explanation: Drive or path not found.

Possible Cause: GroupWise cannot find the specified drive or path.

Action: Use Browse to find the correct path.

Possible Cause: The file you are trying to perform an action on does not exist.

Action: Enter a valid filename.

Possible Cause: If this error occurs shortly after starting the GroupWise client, the path to the archive directory might not be correct.

Action: In the GroupWise client, verify that the path to the archive directory exists and that you have sufficient rights to create and modify files. Look up “archive, directory” in GroupWise client Help.

Action: If the path to the archive directory is valid and this is the first time the user has tried to archive items, make sure the **ngwguard.dc** file exists in the post office. If it is missing, the databases required for archiving cannot be created. To restore the ngwguard.dc file if it is missing, copy it from the **po** directory in the software distribution directory to the post office directory. For the locations of these files, see “Post Office Directory” and “Software Distribution Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

Possible Cause: If this error occurs from the POA, the POA might not have access to a required file.

Action: Start the POA including the **/rights** switch to determine the specific problem the POA is encountering. See “Using POA Startup Switches” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs from the MTA, the MTA might not have access to one or more of the post offices in the domain.

Action: Verify that the list of post offices belonging to the domain is correct. To view the list in ConsoleOne, browse to and right-click the Domain object, then click Properties. Click GroupWise > Post Offices. Check the properties of each Post office object to make sure that the post office directory for each post office exists. Make sure that the post office path is correctly defined in the Post Office object. In ConsoleOne, right-click the Post Office object to display the post office Identification page. Also make sure the MTA has access to the post office.

Possible Cause: If this error occurs when importing a document into GroupWise, there might be a problem with the library.

Action: Check and, if necessary, fix the library. See “Maintaining Library Databases and Documents” in “Databases” in the *GroupWise 7 Administration Guide*. Then synchronize the library. See “Synchronizing Database Information” in “Databases” in the *GroupWise 7 Administration Guide*.

Action: If documents are being stored at the post office, make sure the **docs** subdirectory exists for the library.

Action: If documents are being stored in a remote document storage area, make sure that the POA can access the location of the document storage area. In ConsoleOne, browse to and right-click the Library object, then click Properties. Click GroupWise > Storage Areas. Select a storage area, then

click Edit. Check the location to make sure the required library directory structure exists. The structure of a remote document storage area is the same as the **gwdms** directory in the post office.

- Possible Cause: If this error occurs when trying to access a document in a library, the BLOB file containing the document might no longer exist.
- Action: You can determine what BLOB file the document was in from the GroupWise client. Right-click the document reference, then click Properties > Activity Log. If filenames are not currently displayed, right-click the menu bar, then click Filename to display the filename in the activity log. If the document is needed, you can restore the BLOB file from backup. See “**Restoring Archived Documents**” in “**Libraries and Documents**” in the *GroupWise 7 Administration Guide*.
- If the document is not needed, you can delete it from the library to eliminate the error.
- Action: Have the original sender of the message resend the attachment.
- Possible Cause: Some applications, such as Corel* WordPerfect* 7, MS Word 95, and Excel 95, need a blank file stored in the c:/windows/shellnew directory. For example, Corel WordPerfect 7 needs a file named wordpfc.wpd to exist in the shellnew directory in order to create a new file when called from GroupWise. If this error occurs when creating a new document in the GroupWise client, the blank template file for the application might be missing.
- Action: Check the shellnew directory for the existence of a blank file for the application in use from GroupWise. If the blank file is missing, start the application independently, then save an empty file under the required name in the shellnew directory. You should then be able to create new documents using that application from GroupWise.
- Possible Cause: A directory required for the normal flow of GroupWise messages could be missing.
- Action: See “**Message Transfer/Storage Directories**” in “**Directory Structure Diagrams**” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. Verify the existence, ownership, and rights of the directories involved with message flow (domain, post office, and MTA local directory).
- Possible Cause: A required file or subdirectory could be missing from the directory structure of the user’s post office.
- Action: See “**Post Office Directory**” in “**Directory Structure Diagrams**” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. Verify the existence, ownership, and rights of the files and subdirectories in the user’s post office. See “**GroupWise User Rights**” in “**Security**” in the *GroupWise 7 Administration Guide*.
- Possible Cause: If this error occurs when trying to add users to a post office or when trying to rebuild a user database, a required file might be missing from the post office directory.
- Action: Make sure the **ngwguard.dc** file exists in the post office directory. If it does not, copy it from the **po** subdirectory of your software distribution directory. For the specific location of this file, see “**Post Office Directory**” and “**Software Distribution Directory**” in “**Directory Structure Diagrams**” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. New user databases (**userxxx.db** files) and message databases (**msgnnn.db** files) cannot be created for new users if this file is missing.

820B Path too long

- Source: GroupWise engine; file input/output.
- Explanation: Path too long.
- Possible Cause: The file system cannot build or modify a path because the specified path contains too many characters.

Action: Shorten the path name to a length that is valid for the operating system. If a filename will be appended to the path name, include the filename in the total length.

Possible Cause: If this error occurs when you are trying to create a new GroupWise system, you might have mapped the drive where you are creating the GroupWise system to an object in the eDirectory tree, instead of to the correct volume on the server. For example, if you used Windows* Explorer or Network Neighborhood to map the drive, you might have browsed under the tree icon, rather than under the server icon.

Action: Make sure you have mapped the drive where you are creating the GroupWise system to the correct volume on the server, not to an object in the eDirectory tree.

820E Cannot lock file

Source: GroupWise engine; file input/output.

Explanation: File lock error.

Possible Cause: An attempt to lock a file failed.

Action: Verify that the file is not currently locked by another process that has terminated.

Possible Cause: You cannot open the specified file because another user might have the file open.

Action: Ask the other user to close the file.

Action: Retry the action later.

Action: If no valid user or process has the file open, delete the connection to unlock the file.

Possible Cause: You cannot open the specified file because you might not have rights to open the file.

Action: Obtain rights to the file.

Possible Cause: If this error occurs from the POA when rebuilding a database, a user might still have the database open. The POA requires exclusive access to databases when rebuilding them.

Action: Make sure no users associated with the database to be rebuilt are currently running the GroupWise client. If none are and the database is still locked, break the connection to unlock the file.

Action: Exit, then restart the POA.

8210 Cannot create path

Source: GroupWise engine; file input/output.

Explanation: Path create failed. An attempt by the file system to create a unique file failed.

Possible Cause: If the error occurs as the user is exiting the GroupWise client, the client might be encountering a problem archiving messages. GroupWise might not be able to archive messages if the original sender's message database is damaged.

Action: Manually archive any items that are old enough to be archived. You can use a filter to display only items that are older than a specified number of days. Look up "archive, item" and "filters, creating" in GroupWise client Help.

Action: If errors occur during manual archiving, determine the user who sent the problem items. If that user is not experiencing any problems with GroupWise, you can delete the problem items. If the sending user is also having problems, check and, if necessary, repair the message database (*msgnnn.db*) of the user who sent the problem items. See "Maintaining User/Resource and Message Databases" in "Databases" in the *GroupWise 7 Administration Guide*.

Action: In the GroupWise client, open the archive, then use the Repair Mailbox feature to repair the archive. See “[Enabling GroupWise Check in the Windows Client](#)” in “[Client](#)” in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck on the archive. See “[Standalone Database Maintenance Programs](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*. GWCheck provides additional repair options compared to the Repair Mailbox feature in the GroupWise client.

Possible Cause: If this error occurs from the POA, the POA might not have access to a required location.

Action: Start the POA including the `/rights` switch to determine the specific problem the POA is encountering. See “[Using POA Startup Switches](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: On a NetWare server, deleted files must be purged to free up the disk space they occupy. If the purge is not done, the deleted file space is not reused, causing insufficient disk space to create the path.

Action: Purge deleted files to reclaim the disk space. Add more disk space to the volume. See “[Managing Database Disk Space](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

8211 Cannot rename file

Source: GroupWise engine; file input/output.

Explanation: File rename failed.

Possible Cause: Attempt by the file system to rename a file failed.

Action: Make sure the specified filename is unique.

Possible Cause: A directory required for the normal flow of GroupWise messages might be missing.

Action: See “[Message Transfer/Storage Directories](#)” in “[Directory Structure Diagrams](#)” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. Verify the existence, ownership, and rights of the directories involved with message flow (domain, post office, and MTA local directory).

8212 Password incorrect

Source: GroupWise engine; file input/output.

Explanation: Invalid file password.

Possible Cause: The password entered by the user does not match the one stored in the encrypted file.

Action: Reenter the password.

8214 Unsupported encryption level

Source: GroupWise engine; file input/output.

Explanation: Unsupported encryption level in file.

Possible Cause: Attempted to decrypt a file using an encryption level that is no longer supported.

Action: The file you are trying to open was created in a newer version of GroupWise and cannot be opened in an older version. Update to the latest version of GroupWise. To check the date of the GroupWise client you are using, click Help > About GroupWise. For technical services and file updates, see [Novell Support \(http://support.novell.com\)](http://support.novell.com).

Action: Make sure the archive directory is not locked to an unusable location. In ConsoleOne, browse to and select the post office the user belongs to, then click Tools > GroupWise Utilities > Client Options > Environment > File Location. Check the setting in the Archive Directory field and check whether or not it is locked.

8215 Path root error

Source: GroupWise engine; file input/output.

Explanation: At path root.

Possible Cause: If this error occurs as the GroupWise client starts, the user might have specified an archive path that does not exist.

Action: In the GroupWise client, verify the path to the archive directory exists and the user has sufficient rights to create and modify files there. Look up “archive, directory” in GroupWise client Help.

8219 Cannot connect to remote network resource

Source: GroupWise engine; file input/output.

Explanation: The POA cannot access a document storage area located on a remote server.

Possible Cause: If this error occurs when running the Windows agents, the user’s user name and password on the server where the POA is running are different from the user name and password on the server where the document storage area is located.

Action: Use the same user name and password on the server where the POA is running and the server where the document storage area is located.

Action: Use the `/user` and `/password` switches to provide the login information for the server where the document storage area is located. See “Using POA Startup Switches” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

Action: In ConsoleOne, specify the login information in the Remote File Server Settings box on the Post Office Settings page of the Post Office object.

821A Access to a critical file denied

Source: GroupWise engine; file input/output.

Explanation: The POA cannot access a required file.

Possible Cause: The required file is locked by another program, for example, a backup program.

Action: Implement a backup process that does not lock files in your live GroupWise system. See “Backing Up GroupWise Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

Action: If necessary, restart the server to reset all file locks.

8502 Cannot initialize protocol

Source: GroupWise engine; general communication.

Explanation: Cannot open protocol.

Action: See “8901 Cannot use TCP/IP services” on page 29.

8503 Cannot connect to specified IP address

Source: GroupWise engine; general communication.

Explanation: Cannot open connection to specified address.

Action: See “8908 Cannot connect to specified address” on page 29.

8509 Cannot access TCP/IP services

Source: GroupWise engine; general communication.

Explanation: TCP/IP bind failed.

Possible Cause: TCP/IP is not loaded on the server or is not loaded correctly. The TCP port is already in use by another process.

Action: Configure TCP/IP on the server correctly. If this error occurs on a NetWare server, make sure you have the latest version of the TCPIP NLM. For technical services and file updates, see [Novell Support \(http://support.novell.com\)](http://support.novell.com).

Action: Reboot the server.

850F Connection no longer valid

Source: GroupWise engine; general communication.

Explanation: Connection was broken while in use.

Possible Cause: A client or server machine has crashed, or the process was forced to close without shutting down. The machine might have been exited while connections were active.

Action: Exit and restart GroupWise when the machine is back up.

8555 Port in use

Source: GroupWise engine; general communication.

Explanation: Port in use.

Possible Cause: The POA defaults to TCP/IP communication, but the necessary TCP/IP information is not configured in ConsoleOne. The default TCP port used by the POA (1667) is in use by another program.

Action: To enable TCP/IP communication, configure the POA for ConsoleOne. See “Using Client/Server Access to the Post Office” in “Configuring the POA” in the *GroupWise 7 Administration Guide*.

Action: To disable TCP/IP communication, use the `/notcpip` switch when starting the POA. See “Using POA Startup Switches” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

Possible Cause: You are trying to run two POAs on the same server in client/server mode and you have not given them unique TCP port numbers.

Action: Check the TCP port for each POA object. See “Using Client/Server Access to the Post Office” in “Configuring the POA” in the *GroupWise 7 Administration Guide*. Change the TCP port for one of the POAs.

Possible Cause: You are trying to run two POAs on the same server in client/server mode and you haven’t created a second POA object in ConsoleOne.

Action: In ConsoleOne, create a second POA object in the post office. Make sure you give it a unique TCP port number, different from what the first POA is using. Use the `/name` switch when starting each POA. You might want to create a separate startup file for each POA. See “Creating a POA Object in eDirectory” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

8562 Client/server request packet contained invalid identifier

Source: GroupWise engine; general communication.

Explanation: Client/server request packet contained an invalid identifier.

Possible Cause: Someone is trying to forge packets to break into the system.

Action: Check your system security.

Possible Cause: The server was shut down and brought back up while GroupWise clients were attached.

Action: Exit and restart the GroupWise clients.

Possible Cause: A TCP/IP packet was damaged in transit.

Action: None.

8563 Client/server request packet contained invalid identifier

Source: GroupWise engine; general communication.

Action: See [“8562 Client/server request packet contained invalid identifier”](#) on page 27

8567 Data not in BCEF format

Source: GroupWise engine; general communication.

Explanation: A packet of information received by an agent was not in the expected format.

Possible Cause: The packet was damaged somewhere between the source and the destination of the data.

Action: Use packet trace software to identify the source of the problem. It could be something like a bad network card or a problem with dial-up software.

8568 HTTP port already in use

Source: GroupWise engine; general communication.

Explanation: The HTTP port used by the POA for its Web console is already in use by another program on the server.

Possible Cause: You are trying to run two POAs on the same server and you have not given them unique HTTP port numbers.

Action: Check the HTTP port for each POA object. See [“Setting Up the POA Web Console”](#) in [“Monitoring the POA”](#) in the *GroupWise 7 Administration Guide*. Change the HTTP port for one of the POAs.

8569 SSL login required for this post office

Source: GroupWise engine; general communication.

Explanation: Starting with GroupWise 6.5, the POA can be configured to require SSL connections with clients.

Possible Cause: Users of clients earlier than GroupWise 6.5 are trying to log in to the post office.

Action: Have users update their GroupWise client software. See [“Updating Users' GroupWise Clients”](#) in [“Update”](#) in the *“GroupWise 7 Installation Guide”*.

Action: Configure the POA so that SSL is enabled rather than required, so that the older GroupWise clients can connect to the post office. See [“Enhancing Post Office Security with SSL Connections to the POA”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

8570 IMAP port already in use

Source: GroupWise engine; general communication.

Explanation: The IMAP port used by the POA to communicate with IMAP e-mail clients is already in use by another program on the server.

Possible Cause: You are trying to run two POAs on the same server and you have not given them unique IMAP port numbers.

Action: Check the IMAP port for each POA object. See “[Supporting IMAP Clients](#)” in “[Configuring the POA](#)” in the *GroupWise 7 Administration Guide*. Change the IMAP port for one of the POAs.

8571 SOAP port already in use

Source: GroupWise engine; general communication.

Explanation: The SOAP port used by the POA to communicate with SOAP clients is already in use by another program on the server.

Possible Cause: You are trying to run two POAs on the same server and you have not given them unique SOAP port numbers.

Action: Check the SOAP port for each POA. See “[Supporting SOAP Clients](#)” in “[Configuring the POA](#)” in the *GroupWise 7 Administration Guide*. Change the SOAP port for one of the POAs.

8572 CAP port already in use

Source: GroupWise engine; general communication.

Explanation: The CAP port used by the POA to communicate with CAP clients is already in use by another program on the server.

Possible Cause: You are trying to run two POAs on the same server and you have not given them unique CAP port numbers.

Action: Check the CAP port for each POA object. See “[Supporting CAP Clients](#)” in “[Configuring the POA](#)” in the *GroupWise 7 Administration Guide*. Change the CAP port for one of the POAs.

8573 LDAP port already in use

Source: GroupWise engine; general communication.

Explanation: The LDAP port used by the POA is already in use by another program on the server.

Possible Cause: You are trying to run two POAs on the same server and you have not given them unique LDAP port numbers.

Action: Check the LDAP port for each POA object. See “[Providing LDAP Authentication for GroupWise Users](#)” in “[Configuring the POA](#)” in the *GroupWise 7 Administration Guide*. Change the LDAP port for one of the POAs.

8809 Unexpected error

Source: GroupWise engine; inter- or intra-process communication

Action: See “[8xxx Unexpected error](#)” on [page 37](#).

880B Unexpected error

Source: GroupWise engine; inter- or intra-process communication

Action: See **“8xxx Unexpected error” on page 37.**

880C Unexpected error

Source: GroupWise engine; inter- or intra-process communication

Action: See **“8xxx Unexpected error” on page 37.**

8901 Cannot use TCP/IP services

Source: GroupWise engine; TCP/IP communication.

Explanation: A fundamental TCP/IP call failed.

Possible Cause: TCP/IP services couldn't be used. It is possible that TCP/IP is loaded incorrectly on this server.

Possible Cause: Cannot load WINSOCK (Windows only), or the WINSOCK that did load is not supported. DNS is not loaded and you are trying to resolve DNS names.

Action: Correctly configure TCP/IP on the server.

8902 Cannot load TCP/IP services

Source: GroupWise engine; TCP/IP communication.

Explanation: TCP/IP load failed because a required file was missing.

Possible Cause: Unable to load TCP/IP services because one or more of the required files is missing: winsock.dll, wsoc32.dll, or tcpip.nlm.

Action: Make sure that you have the required files, and that they are in the search path.

Action: Correctly configure TCP/IP on the server.

8903 Cannot use TCP/IP services

Source: GroupWise engine; TCP/IP communication.

Action: See **“8901 Cannot use TCP/IP services” on page 29.**

8906 Cannot use TCP/IP services

Source: GroupWise engine; TCP/IP communication.

Action: See **“8901 Cannot use TCP/IP services” on page 29.**

8907 Cannot use TCP/IP services

Source: GroupWise engine; TCP/IP communication.

Action: See **“8901 Cannot use TCP/IP services” on page 29.**

8908 Cannot connect to specified address

Source: GroupWise engine; TCP/IP communication.

Explanation: Connection to the specified address failed.

Possible Cause: Unable to load TCP/IP services because one or more of the required files is missing: winsock.dll, wsoc32.dll, or tcpip.nlm.

Action: Make sure that you have the required files, and that they are in the search path.

Action: Correctly configure TCP/IP on the server. Make sure you are using a current IP stack. If you must use an older IP stack, try specifying the IP address in dotted numeric format (172.16.5.18), rather than as a host name that requires resolution, when setting the /ipa switch.

Action: When using direct mode rather than client/server, the GroupWise client still requires a valid winsock.dll to be available on the search path. Make sure a current, valid winsock.dll file is available on the workstation where the problem is occurring.

Possible Cause: The GroupWise client cannot establish a TCP/IP connection with the POA.

Action: Check the IP address for the POA. See “[Using Client/Server Access to the Post Office](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

Action: Check the status of the POA server and the load on the network.

Possible Cause: If this error appears in the Message Transfer Status box of the POA, the MTA to which it is transferring messages is not running.

Action: Check the status of the MTA for the domain. Restart the MTA if necessary.

Possible Cause: If this error occurs from the GroupWise Internet Agent, the Internet Agent might not be able to establish a TCP/IP connection to the POA.

Action: Check the post office link set up for the Internet Agent. In ConsoleOne, click the domain where the Internet Agent is installed. Right-click the Internet Agent object, then click Properties. Click Post Office Links, select the post office, then click Edit Link. Make sure the IP address and TCP port for the POA are specified correctly in the Client/Server box.

Action: Use a UNC or mapped link between the Internet Agent and the POA, rather than a TCP/IP link.

8909 Cannot use TCP/IP services

Source: GroupWise engine; TCP/IP communication.

Action: See “[8901 Cannot use TCP/IP services](#)” on page 29.

890A Cannot listen on specified port

Source: GroupWise engine; TCP/IP communication.

Explanation: Listen failed.

Possible Cause: Unable to listen on the specified port. It is possible the specified port is in use by another process. For example, two GroupWise agents might be running on the same server where both were configured for the same port.

Action: Verify that the IP address and port provided in ConsoleOne are correct. See “[Using Client/Server Access to the Post Office](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

890B Cannot accept incoming connection

Source: GroupWise engine; TCP/IP communication.

Explanation: Acceptance failed.

Possible Cause: Hardware is overloaded.

Action: Upgrade the hardware.

890F Connection no longer valid

Source: GroupWise engine; TCP/IP communication.

Explanation: Connection was broken while in use.

Possible Cause: A client or server machine has crashed, or the process was forced to close without shutting down. The machine might have been exited while connections were active.

Action: Make sure the POA is running. Check the IP address for the POA. See “Using Client/Server Access to the Post Office” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

Possible Cause: The GroupWise client is trying to use client/server mode to connect with the POA, but the POA is not set up for client/server processing.

Action: Configure the POA for client/server processing to match the needs of the client. See “Using Client/Server Access to the Post Office” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error appears in the Message Transfer Status box of the POA, the MTA to which it is transferring messages is not running.

Action: Check the status of the MTA for the domain. Restart the MTA if necessary.

8910 Cannot read on connection

Source: GroupWise engine; TCP/IP communication.

Explanation: Read failed.

Action: Retry the operation.

8911 Cannot write on connection

Source: GroupWise engine; TCP/IP communication.

Explanation: Cannot write on connection; the receiver isn't responding.

Possible Cause: A client or server machine has crashed, or the process was forced to close without shutting down. The machine might have been exited while connections were active.

Action: Restart the GroupWise client.

Possible Cause: If this error occurs from the POA, the server where the POA runs might not have the most current version of TCP/IP.

Action: Install the latest TCP/IP. For technical services and file updates, see [Novell Support \(http://support.novell.com\)](http://support.novell.com).

8912 Cannot read on connection; timed out

Source: GroupWise engine; TCP/IP communication.

Explanation: Cannot read on connection. The sender isn't writing the required information to GroupWise.

Possible Cause: A client or server machine has crashed, or the process was forced to close without shutting down. The machine might have been exited while connections were active.

Action: Restart the GroupWise client when the machine is back up.

Possible Cause: If this error appears in the Message Transfer Status box of the POA, the MTA to which it is transferring messages might be restarting.

Action: Check the status of the MTA for the domain. If the MTA is restarting, the message transfer status should change to Open after the restart is completed.

8913 Cannot write on connection; timed out

Source: GroupWise engine; TCP/IP communication.

Explanation: Cannot write on connection because it is no longer available.

Possible Cause: A client or server machine has crashed, or the process was forced to close without shutting down. The machine might have been exited while connections were active.

Action: Restart the GroupWise client to reestablish the connection.

8916 Cannot use TCP/IP services

Source: GroupWise engine; TCP/IP communication.

Explanation: No network error.

Possible Cause: TCP/IP services couldn't be used. It is possible that TCP/IP isn't loaded correctly on the server.

Possible Cause: GroupWise has encountered unusually long timeouts while trying to retrieve names from DNS. This probably occurred in Windows where the workstation is not connected to the network.

Action: Check the network connections for the workstation.

8917 TCP/IP name lookup failed

Source: GroupWise engine; TCP/IP communication.

Explanation: A GroupWise agent or client cannot ping the specified IP address.

Possible Cause: The agent or client was passed an invalid IP address.

Action: Ping the IP address manually to see if it responds. If it does not respond, correct the problem with the server associated with that IP address.

Action: Determine what the correct IP address should be.

8918 UDP send failed

Source: GroupWise engine; TCP/IP communication.

Explanation: The GroupWise agent cannot write to the specified UDP socket (port).

Possible Cause: The server that the agent is running on is not functioning normally.

Action: Restart the server.

8919 Attempt to bind to a non-existent IP address

Source: GroupWise engine; TCP/IP communication.

Explanation: The GroupWise agent cannot locate the specified IP address to set up an exclusive bind on it.

Possible Cause: The agent is configured to bind to an IP address but that IP address is not available on the server where the agent is running.

Action: Determine what IP addresses are available on the server where the agent is running, then configure the agent to use a valid IP address. See the following sections of the *GroupWise 7 Administration Guide*, depending on which agent is encountering the problem:

- ◆ “Binding the POA to a Specific IP Address”
- ◆ “Binding the MTA to a Specific IP Address”
- ◆ “Binding the Internet Agent to a Specific IP Address”

891A TCP/IP data is not ready for reading

- Source: GroupWise engine; TCP/IP communication.
- Explanation: The TCP/IP connection is blocked.
- Possible Cause: The data has been delayed by SSL encryption.
- Action: None. TCP/IP services will continue to try to read the data.
- Action: If the problem persists, check the line connection and the NIC card on the server.

891B No SSL certificate supplied

- Source: GroupWise engine; TCP/IP communication.
- Explanation: You have configured an agent for SSL, but the agent cannot locate the SSL certificate.
- Possible Cause: In ConsoleOne, you enabled SSL on the Agent object Network Address page but did not provide the certificate information on the SSL Settings page.
- Action: Finish configuring the agent for SSL. See the following sections of the *GroupWise 7 Administration Guide*, depending on which agent is encountering the problem:
- ◆ “Enhancing Post Office Security with SSL Connections to the POA” in “Post Office Agent”
 - ◆ “Enhancing Domain Security with SSL Connections to the MTA” in “Message Transfer Agent”
 - ◆ “Securing Internet Agent Connections Via SSL” in “Internet Agent”
 - ◆ “Securing WebAccess Agent Connections Via SSL” in “WebAccess”

891C Bad SSL certificate

- Source: GroupWise engine; TCP/IP communication.
- Explanation: You have configured an agent for SSL, but the agent cannot read the SSL certificate.
- Possible Cause: The SSL certificate is not in the required format.
- Action: Obtain an SSL certificate in the proper format. See “Encryption and Certificates” in “Security” in the *GroupWise 7 Administration Guide*.
- Possible Cause: The SSL certificate has been damaged.
- Action: Replace the bad SSL certificate with a valid SSL certificate.

891D Bad SSL private key or password

- Source: GroupWise engine; TCP/IP communication.
- Explanation: You have configured an agent for SSL, but the agent cannot read the private key file or the password.
- Possible Cause: The SSL certificate that accompanies the private key file is not in the required format.
- Action: Obtain an SSL certificate in the proper format. See “Encryption and Certificates” in “Security” in the *GroupWise 7 Administration Guide*.
- Possible Cause: The password you provided on the agent object SSL Settings page in ConsoleOne does not match the password in the private key file.
- Action: Correct the password information in ConsoleOne. See the following sections of the *GroupWise 7 Administration Guide*, depending on which agent is encountering the problem:

- ◆ “Enhancing Post Office Security with SSL Connections to the POA” in “Post Office Agent”
- ◆ “Enhancing Domain Security with SSL Connections to the MTA” in “Message Transfer Agent”
- ◆ “Securing Internet Agent Connections Via SSL” in “Internet Agent”
- ◆ “Securing WebAccess Agent Connections Via SSL” in “WebAccess”

891E Insufficient memory for SSL

Source: GroupWise engine; TCP/IP communication.

Explanation: A GroupWise agent failed to establish an SSL connection because insufficient memory is available for creating the connection.

Possible Cause: Another program was temporarily using a very large amount of memory on the server.

Action: Wait and try the operation again.

Possible Cause: Too many programs are currently running on the server.

Action: Stop some programs that are running on the server in order to free up some memory.

Possible Cause: The server where the agent is running has insufficient memory for proper functioning.

Action: Run the agent on a more powerful server.

891F Invalid SSL certificate

Source: GroupWise engine; TCP/IP communication.

Explanation: A GroupWise agent cannot establish an SSL connection because the SSL certificate file is not usable.

Possible Cause: The certificate file is damaged.

Action: Obtain a usable certificate file. See “[Server Certificates and SSL Encryption](#)” in “[Security](#)” in the *GroupWise 7 Administration Guide*.

8920 SSL certificate and private key do not match

Source: GroupWise engine; TCP/IP communication.

Explanation: A GroupWise agent cannot establish an SSL connection because the SSL certificate file and the public key file cannot be used together.

Possible Cause: One of the files is damaged.

Possible Cause: You are trying to use a certificate file and a public key file that were not generated for use together.

Action: Obtain usable files. See “[Server Certificates and SSL Encryption](#)” in “[Security](#)” in the *GroupWise 7 Administration Guide*.

8921 SSL accept failure

Source: GroupWise engine; TCP/IP communication.

Explanation: A GroupWise agent cannot establish an SSL connection because the handshake negotiation between the two servers failed.

Possible Cause: Both servers might have identical certificate files.

Action: Obtain a new certificate file for one of the servers. See “[Server Certificates and SSL Encryption](#)” in “[Security](#)” in the *GroupWise 7 Administration Guide*.

8922 SSL connect failure

Source: GroupWise engine; TCP/IP communication.

Explanation: A GroupWise agent cannot establish an SSL connection because the other server failed to connect.

Possible Cause: The other server is down.

Action: Restart the other server.

Possible Cause: The certificate file is damaged.

Action: Obtain a usable certificate file. See “[Server Certificates and SSL Encryption](#)” in “[Security](#)” in the *GroupWise 7 Administration Guide*.

8923 Insufficient memory for SSL

Source: GroupWise engine; TCP/IP communication.

Explanation: A GroupWise agent failed to establish an SSL connection because insufficient memory is available for creating the connection.

Possible Cause: Another program was temporarily using a very large amount of memory on the server.

Action: Wait and try the operation again.

Possible Cause: Too many programs are currently running on the server.

Action: Stop some programs that are running on the server in order to free up some memory.

Possible Cause: The server where the agent is running has insufficient memory for proper functioning.

Action: Run the agent on a more powerful server.

8924 SSL handshake timeout failure

Source: GroupWise engine; TCP/IP communication.

Explanation: You have configured an agent for SSL, but the agent failed to establish the SSL connection. The agent will try again on the next SSL connection request and might be successful.

Possible Cause: If the agent repeatedly fails to establish the SSL connection, the SSL certificate file or key file might be damaged.

Action: Obtain a new SSL certificate and key file. See “[Encryption and Certificates](#)” in “[Security](#)” in the *GroupWise 7 Administration Guide*.

8925 Connection refused

Source: GroupWise engine; TCP/IP communication.

Explanation: An agent that is configured for TCP/IP attempted to contact another agent and the connection was refused.

Possible Cause: The agent is not communicating on the right TCP port number.

Action: Determine the configuration of the target agent and make sure the initiating agent is using the correct port number. See the following sections of the *GroupWise 7 Administration Guide*, depending on which agent is refusing the connection:

- ◆ “Using Client/Server Access to the Post Office” in “Post Office Agent”
- ◆ “Using TCP/IP Links between a Domain and its Post Offices” in “Message Transfer Agent”
- ◆ “Changing the Link Protocol between the Internet Agent and the Message Transfer Agent” in “Internet Agent”
- ◆ “Changing the WebAccess Agent's Network Address or Port Numbers” in “WebAccess”

8926 Unknown host

Source: GroupWise engine; TCP/IP communication.

Explanation: The IP address or DNS hostname cannot be resolved to a host in the network.

Possible Cause: An incorrect IP address was specified.

Action: Verify the IP address.

Possible Cause: If a DNS hostname was specified, the DNS name server might not be running.

Action: Make sure that the DNS name server is running.

Action: Specify the IP address instead of the DNS hostname.

8927 Host not reachable

Source: GroupWise engine; TCP/IP communication.

Explanation: An agent that is configured for TCP/IP attempted to contact another agent and no route could be found on the network to contact the specified host.

Possible Cause: A firewall is interfering with the connection.

Action: Contact the administrator of the firewall to obtain the external IP address for use outside the firewall.

Possible Cause: A router is down.

Action: Make sure that all routers are running.

8B02 Unexpected error

Source: GroupWise engine; named memory.

Action: See “8xxx Unexpected error” on page 37.

8C04 Unexpected error

Source: GroupWise engine; process control.

Action: See “8xxx Unexpected error” on page 37.

8C09 Unexpected error

Source: GroupWise engine; process control.

Action: See “8xxx Unexpected error” on page 37.

8C0A Unexpected error

Source: GroupWise engine; process control.

Action: See “8xxx Unexpected error” on page 37.

8C88 Unexpected error

Source: GroupWise engine; process control.

Action: See “8xxx Unexpected error” on page 37.

8F03 Invalid configuration option

Source: GroupWise engine; server toolkit.

Explanation: Invalid startup switch specified when starting one of the agents.

Action: Check the startup switches in use for the agent reporting the error. For lists of startup switches, see “Using POA Startup Switches” in “Post Office Agent” and “Using MTA Startup Switches” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

8xxx Unexpected error

Source: GroupWise engine.

Explanation: An engine error has occurred for which GroupWise does not have a specific error message.

Action: Exit and then restart the GroupWise client.

9xxx Engine Error Codes

Range: 90xx

“9007 Client not set up for SSL” on page 39
“9008 Server does not support SSL” on page 39

Range: 93xx

“9302 Unexpected error” on page 40
“9304 Unexpected error” on page 40
“9305 Unexpected error” on page 40
“9307 Unexpected error” on page 40
“9308 Unexpected error” on page 40
“9309 Unexpected error” on page 40

9007 Client not set up for SSL

Source: GroupWise® engine; client/server.

Explanation: The POA is configured to require SSL communicate with the GroupWise client, but the client is not capable of SSL communication.

Possible Cause: SSL communication was introduced for the GroupWise client in GroupWise 6.5. You are running an older GroupWise client against a post office that has been updated to GroupWise 6.5 or later.

Action: Update the client to GroupWise 6.5 or later.

Action: Reconfigure the POA so that SSL is enabled rather than required. See “[Enhancing Post Office Security with SSL Connections to the POA](#)” in “[Configuring the POA](#)” in the *GroupWise 7 Administration Guide*.

9008 Server does not support SSL

Source: GroupWise engine; client/server.

Explanation: The GroupWise client is trying to use an SSL connection to the POA but the POA is not configured for SSL.

Possible Cause: The POA has been reconfigured without SSL since the client logged in.

Action: Restart the GroupWise client. It does not try to use SSL when it detects that the POA is not configured for SSL.

9302 Unexpected error

Source: GroupWise engine; loadable language resource.

Action: See “9xxx Unexpected error” on page 40.

9304 Unexpected error

Source: GroupWise engine; loadable language resource.

Action: See “9xxx Unexpected error” on page 40.

9305 Unexpected error

Source: GroupWise engine; loadable language resource.

Action: See “9xxx Unexpected error” on page 40.

9307 Unexpected error

Source: GroupWise engine; loadable language resource.

Action: See “9xxx Unexpected error” on page 40.

9308 Unexpected error

Source: GroupWise engine; loadable language resource.

Action: See “9xxx Unexpected error” on page 40.

9309 Unexpected error

Source: GroupWise engine; loadable language resource.

Action: See “9xxx Unexpected error” on page 40.

9xxx Unexpected error

Source: GroupWise engine; loadable language resource.

Explanation: An engine error has occurred for which GroupWise does not have a specific error message.

Action: Exit and then restart the GroupWise client.

Axxx Engine Error Codes

Range: A0xx

“A001 Unexpected error” on page 42

Range: A5xx

“A501 Unexpected error” on page 42

“A502 Unexpected error” on page 42

“A504 Unexpected error” on page 42

Range: A6xx

“A602 Unexpected error” on page 42

Range: A8xx

“A801 Auto-Date formula too long” on page 42

“A802 Auto-Date formula has incorrect syntax” on page 43

“A803 Auto-Date formula not specified” on page 43

“A804 Auto-Date formula generates too many occurrences” on page 43

Range: AAxx

“AA01 Unexpected error” on page 43

“AA02 Unexpected error” on page 43

“AA04 Unexpected error” on page 43

Range: ACxx

“AC01 Zipped file has unsupported version number” on page 44

“AC02 Zipped file has incorrect format” on page 44

“AC03 Zipped file damaged” on page 44

Range: ADxx

- “AD01 No LDAP Support” on page 44
- “AD06 The LDAP server information passed in is not valid” on page 44
- “AD08 No username or password specified for logging into the LDAP server” on page 44
- “AD09 The password for the LDAP user has expired” on page 45
- “AD0C No connection could be made to the LDAP server” on page 45
- “AD10 SSL certificate was not found” on page 45
- “AD11 SSL could not be initialized” on page 45
- “AD20 The attribute specified in the request does not exist in the entry” on page 46
- “AD21 The attribute specified in the request does not exist in the LDAP server’s schema” on page 46
- “AD25 The object DN passed in is invalid because the target object cannot be found” on page 46
- “AD29 The security (TLS versus plain) surrounding this request is not valid for the request” on page 46
- “AD2E A dynamic memory allocation function failed when calling an LDAP function” on page 47
- “AD2F The LDAP server cannot process the request because of server-defined restrictions” on page 47

A001 Unexpected error

Source: GroupWise® engine; sized string manipulation.

Action: See “Axxx Unexpected error” on page 47.

A501 Unexpected error

Source: GroupWise engine; data array management.

Action: See “Axxx Unexpected error” on page 47.

A502 Unexpected error

Source: GroupWise engine; data array management.

Action: See “Axxx Unexpected error” on page 47.

A504 Unexpected error

Source: GroupWise engine; data array management.

Action: See “Axxx Unexpected error” on page 47.

A602 Unexpected error

Source: GroupWise engine; data list management.

Action: See “Axxx Unexpected error” on page 47.

A801 Auto-Date formula too long

Source: GroupWise engine; Auto-Date.

Explanation: Formula is too long.

Possible Cause: The user either entered formula text that was too large (4 KB is maximum), or the user selected from the graphical Auto-Date window and the generated formula was too large.

Action: Enter a shorter formula or reduce the number of days selected in the Auto-Date window. Look up “auto-dates” in GroupWise client Help.

A802 Auto-Date formula has incorrect syntax

Source: GroupWise engine; Auto-Date.

Explanation: Formula is invalid.

Possible Cause: The user entered a formula which did not follow the correct syntax for Auto-Dates.

Action: Enter the correct formula by checking the syntax in your Auto-Date formula, or using the Dates tab to specify the dates you want to include. Look up “auto-dates” in GroupWise client Help.

A803 Auto-Date formula not specified

Source: GroupWise engine; Auto-Date.

Explanation: Formula is empty.

Possible Cause: An attempt might have been made to switch from the Auto-Date formula mode to graphical mode; however, no formula was entered.

Action: Enter a formula in the formula window, or exit and reenter the send window. This generates a default formula, which does not give the above error. Look up “auto-dates” in GroupWise client Help.

A804 Auto-Date formula generates too many occurrences

Source: GroupWise engine; Auto-Date.

Explanation: Auto-Date occurrences truncated.

Possible Cause: This error occurs when a user specifies a range for an Auto-Date that generates more than 365 occurrences. The first 365 instances will be generated.

Action: If the user does not want to see the warning, the range over which the given Auto-Date spans needs to be shortened. The user can then regenerate additional occurrences for the same Auto-Date for another subrange of his or her original range. Look up “auto-dates” in GroupWise client Help.

AA01 Unexpected error

Source: GroupWise engine; ASCII strings.

Action: See [“Axxx Unexpected error” on page 47](#).

AA02 Unexpected error

Source: GroupWise engine; ASCII strings.

Action: See [“Axxx Unexpected error” on page 47](#).

AA04 Unexpected error

Source: GroupWise engine; ASCII strings.

Action: See [“Axxx Unexpected error” on page 47](#).

AC01 Zipped file has unsupported version number

Source: GroupWise engine; zip/compression.

Explanation: The zipped file has an unsupported version number.

Action: None. GroupWise cannot unzip the file.

AC02 Zipped file has incorrect format

Source: GroupWise engine; zip/compression.

Explanation: The zipped file is not formatted correctly.

Action: None. GroupWise cannot unzip the file.

AC03 Zipped file damaged

Source: GroupWise engine; zip/compression.

Explanation: The zipped file failed a checksum test.

Action: None. GroupWise cannot unzip the file.

AD01 No LDAP Support

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Linux GroupWise Installation program requires that LDAP be running on the server during installation. This requirement is not being met.

Possible Cause: LDAP is not available on the Linux server where you are trying to install the Internet Agent or WebAccess Agent.

Action: Set up LDAP on the Linux server.

Action: Install the Internet Agent or WebAccess Agent on a Linux server where LDAP is already set up.

AD06 The LDAP server information passed in is not valid

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program cannot communicate with the LDAP server because it is using incorrect information.

Possible Cause: Required LDAP information includes an IP address for the LDAP server, a port number, a username (in LDAP format) and a password. You have provided incorrect information.

Action: Review **“Gathering LDAP Information (Linux Only)”** in **“Installing the GroupWise Internet Agent”** or **“LDAP Information (Linux Only)”** in **“Installing GroupWise WebAccess”** in the **“GroupWise 7 Installation Guide”** for details about the information that the Installation program requires, then provide the correct information.

Action: Make sure that the LDAP Server object is correctly configured in ConsoleOne®.

AD08 No username or password specified for logging into the LDAP server

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program cannot log in to the LDAP server.

Possible Cause: You have not supplied a username or password.

Action: Supply the required information.

AD09 The password for the LDAP user has expired

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program cannot log in to the LDAP server.

Possible Cause: The password you supplied is no longer valid.

Action: Update the password information for the user on the LDAP Server object.

Action: Specify a user whose password has not expired.

AD0C No connection could be made to the LDAP server

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program cannot communicate at all with the LDAP server you specified.

Possible Cause: The LDAP server is down.

Action: Check the status of the LDAP server and bring it up if necessary.

Possible Cause: Network problems are preventing communication between the Installation program and the LDAP server.

Action: Use the ping command to attempt to contact the LDAP server. If there is no response, resolve the network problem.

AD10 SSL certificate was not found

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: You selected to use an SSL connection with the LDAP server, but the Installation program cannot establish an SSL connection.

Possible Cause: You did not provide the correct SSL certificate file information to the Installation program.

Action: Review [“Gathering LDAP Information \(Linux Only\)”](#) in [“Installing the GroupWise Internet Agent”](#) or [“LDAP Information \(Linux Only\)”](#) in [“Installing GroupWise WebAccess”](#) in the [“GroupWise 7 Installation Guide”](#) for details about the SSL certificate file, then provide the correct information.

Possible Cause: The LDAP Server object in ConsoleOne is not properly configured for SSL.

Action: Make sure that the LDAP Server object is configured with the correct SSL certificate information in ConsoleOne.

AD11 SSL could not be initialized

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: You selected to use an SSL connection with the LDAP server, but the Installation program cannot establish an SSL connection.

Possible Cause: The LDAP Server object in ConsoleOne is not properly configured for SSL.

Action: Make sure that the LDAP Server object is configured with the correct SSL certificate information in ConsoleOne.

AD20 The attribute specified in the request does not exist in the entry

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program is trying to create an Agent object but eDirectory™ is not providing the necessary attribute.

Possible Cause: The eDirectory schema has not yet been extended to accommodate GroupWise objects.

Action: Extend the schema, as described in “[Check eDirectory Schema](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*.

Action: Run the Installation program again, as described in “[Setting Up a Basic GroupWise System](#)” in the *“GroupWise 7 Installation Guide”*.

AD21 The attribute specified in the request does not exist in the LDAP server’s schema

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program is trying to create an Agent object, but the LDAP server is not configured for the necessary attribute.

Possible Cause: The eDirectory schema has not yet been extended to accommodate GroupWise objects.

Action: Extend the schema, as described in “[Check eDirectory Schema](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*.

Action: Run the Installation program again, as described in “[Setting Up a Basic GroupWise System](#)” in the *“GroupWise 7 Installation Guide”*.

AD25 The object DN passed in is invalid because the target object cannot be found

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program is trying to create an Agent object, but the context you specified does not exist.

Possible Cause: You typed the context incorrectly.

Action: Browse to and select the context.

Possible Cause: You typed the context correctly, but the context does not exist.

Action: In ConsoleOne, create the container object you want to use, then browse to and select it in the Installation program.

Possible Cause: You typed an alias rather than a valid distinguished name.

Action: Check for the correct distinguished name in ConsoleOne.

AD29 The security (TLS versus plain) surrounding this request is not valid for the request

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program is trying to create an Agent object, but it does not have the necessary rights in eDirectory.

Possible Cause: The LDAP server is not configured to accept clear text passwords.

Action: In ConsoleOne, configure the LDAP Server object to accept clear text passwords.

Possible Cause: The LDAP server is not properly configured for SSL.

Action: Configure the LDAP server for SSL and make sure that the correct root certificate is used.

AD2D The LDAP server is busy, unavailable, has timed out, or is down

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program made initial contact with the LDAP server, but the LDAP server is no longer responding. Therefore, the Installation program cannot create an Agent object.

Action: Resolve the problem with the LDAP server.

Action: Restart the LDAP server.

AD2E A dynamic memory allocation function failed when calling an LDAP function

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program cannot function in the current environment.

Possible Cause: Insufficient memory.

Action: Stop some programs that are running on the server in order to free up some memory.

AD2F The LDAP server cannot process the request because of server-defined restrictions

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program cannot function in the current environment.

Possible Cause: The add entry request violates the server's structure rules.

Possible Cause: The modify attribute request specifies attributes that users cannot modify.

Possible Cause: Password restrictions prevent the action.

Possible Cause: Connection restrictions prevent the action.

Action: Make sure that the user who is running the installation has sufficient rights to modify objects.

Action: Make sure that the user who is running the installation does not have any login restrictions.

Axxx Unexpected error

Source: GroupWise engine.

Explanation: An engine error has occurred for which GroupWise does not have a specific error message.

Action: Exit and then restart the GroupWise client.

Bxxx Engine Error Codes

Range: B3xx

“B300 File transmission failed” on page 49

“B309 Port already in use” on page 49

“B30A No peer listening for connection” on page 49

B300 File transmission failed

- Source: GroupWise® engine; Message Transfer Protocol.
- Explanation: The POA was not able to transfer a message file to the MTA.
- Possible Cause: The MTA restarted during transmission of the file.
- Possible Cause: The network experienced a slow-down, causing the MTA to time out while waiting for the rest of the file.
- Action: None. The POA automatically resends the message until the message is sent successfully.

B309 Port already in use

- Source: GroupWise engine; Message Transfer Protocol.
- Explanation: The specified port is already in use.
- Possible Cause: You have set up the POA to communicate with the MTA by way of TCP/IP but the TCP port you have chosen for the Message Transfer Protocol (MTP) link between them is already in use by another program.
- Action: The message transfer port configured for the POA should be the same port number as the MTA is using to listen on. Make sure the MTA is set up correctly for TCP/IP links. Make sure the POA is configured with the message transfer port number matching the port number of the MTA. See “[Changing the Link Protocol between the Post Office and the Domain](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

B30A No peer listening for connection

- Source: GroupWise engine; Message Transfer Protocol.
- Explanation: The POA is attempting to communicate with the MTA by way of TCP/IP but the MTA is not responding.
- Possible Cause: The MTA is not running.
- Action: Start the MTA.

Possible Cause: The server where the MTA is running is overloaded so the MTA cannot respond to the POA in a timely manner.

Action: Check the load on the server where the MTA is running. If necessary, stop some other programs or upgrade the server so adequate resources are available for the MTA to function properly.

Possible Cause: The MTA is not configured for TCP/IP links.

Action: Reconfigure the MTA for TCP/IP links. See “[Changing the Link Protocol between Domains](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.

Cxxx Engine Error Codes

Range:

- ◆ C00x
- ◆ C01x
- ◆ C02x
- ◆ C03x
- ◆ C04x
- ◆ C05x
- ◆ C06x
- ◆ C07x
- ◆ C08x

Range: C00x

- “C003 Invalid object name has been passed in” on page 54
- “C005 Invalid container has been selected for the GW objects” on page 54
- “C006 Record, key, or key reference not found” on page 54
- “C007 Database error” on page 55
- “C008 Database error” on page 55
- “C009 Database error” on page 55
- “C00A Database error” on page 55
- “C00B Database error” on page 55
- “C00C Field type mismatch” on page 55
- “C00D Database error” on page 56
- “C00E Invalid index number” on page 56
- “C00F Invalid password” on page 56

Range: C01x

- “C010 Database error” on page 56
- “C011 Database being modified” on page 57
- “C012 Database error” on page 57
- “C013 Index full” on page 57

“C014 Database error” on page 57
“C015 Database error” on page 57
“C016 Database error” on page 57
“C017 Database error” on page 57
“C018 Database error” on page 57
“C019 Database error” on page 58
“C01A Database error” on page 58
“C01B Database error” on page 58
“C01C Database error” on page 58
“C01D Database error” on page 58
“C01E Database error” on page 58
“C01F Database error” on page 58

Range: C02x

“C020 Database error” on page 58
“C021 Database error” on page 58
“C022 Database damaged” on page 58
“C023 Database error” on page 60
“C024 Database dictionary damaged” on page 60
“C026 Database error” on page 60
“C027 Database error” on page 60
“C028 Database error” on page 60
“C029 Database version unsupported” on page 60
“C02A Cannot access database dictionary file” on page 60
“C02B Database error” on page 61
“C02C Database error” on page 61
“C02D Database error” on page 61
“C02E Database error” on page 61
“C02F Database error” on page 61

Range: C03x

“C032 Database error” on page 61
“C033 Database error” on page 61
“C034 Database error” on page 61
“C035 Database error” on page 62
“C037 Memory error” on page 62
“C038 Memory error” on page 62
“C03A Database requires newer version” on page 62
“C03B Database error” on page 62
“C03C Database error” on page 62
“C03D Unexpected error” on page 62
“C03F Database error” on page 62

Range: C04x

- “C040 Database error” on page 63
- “C042 Database being modified” on page 63
- “C043 Database error” on page 63
- “C044 Database error” on page 63
- “C045 Unexpected error” on page 64
- “C046 Database error” on page 64
- “C047 Database error” on page 64
- “C048 Unexpected error” on page 64
- “C04A Unexpected error” on page 64
- “C04B Database error” on page 64
- “C04C Database error” on page 64
- “C04D Memory error” on page 64
- “C04E Database error” on page 64
- “C04F Database checksum error” on page 64

Range: C05x

- “C050 Transaction aborted” on page 65
- “C055 Unexpected error” on page 65
- “C057 Database maintenance in progress; please exit” on page 65
- “C059 Database file already exists” on page 66
- “C05D Cannot open database file” on page 66
- “C05E Unexpected error” on page 67

Range: C06x

- “C060 Unexpected error” on page 67
- “C061 Unexpected error” on page 67
- “C062 Unexpected error” on page 67
- “C063 Database error” on page 67
- “C066 Unexpected error” on page 68
- “C067 Database error” on page 68
- “C068 Database error” on page 68
- “C069 Database error” on page 68
- “C06A Database error” on page 68
- “C06B Database error” on page 68
- “C06C Database error” on page 69
- “C06D Database error” on page 69
- “C06E Unexpected error” on page 69
- “C06F Store number mismatch” on page 69

Range: C07x

“C071 Unexpected error” on page 70
“C072 Database error” on page 70
“C073 Unexpected error” on page 70
“C076 Unexpected error” on page 70
“C077 Unexpected error” on page 70
“C078 Unexpected error” on page 70
“C079 Unexpected error” on page 70
“C07A Unexpected error” on page 70
“C07B Database error” on page 70
“C07C Unexpected error” on page 71
“C07D Unexpected error” on page 71
“C07E Unexpected error” on page 71
“C07F Unexpected error” on page 71

Range: C08x

“C080 Index not found” on page 71
“C081 Attachment missing” on page 71

C003 Invalid object name has been passed in

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program cannot create an Agent object with the name you specified.

Possible Cause: You did not specify the object name in the correct format.

Action: Use the following format:

cn=username,ou=organizational_unit,o=organization

Possible Cause: An object by the name you specified already exists.

Action: Specify a different object name.

C005 Invalid container has been selected for the GW objects

Source: Internet Agent Installation program or WebAccess Installation program on Linux

Explanation: The Installation program cannot create an Agent object in the context you specified.

Possible Cause: The container object you specified was not a GroupWise Domain object, an Organizational Unit object, or an Organization object.

Action: Specify an appropriate container for the Agent object.

C006 Record, key, or key reference not found

Source: GroupWise® engine; database services.

Explanation: A record or key was not found.

Possible Cause: In the GroupWise client, the user dragged away all the column headings.

Action: Restore the column headings. Right-click the bar where the column headings belong, then select the column headings such as From, Subject, and Date, from the drop-down list.

Possible Cause: If this error occurs when creating a post office, you might not be connected to the correct domain.

Action: If you try to create a post office in a secondary domain while connected to a different domain, you might not have sufficient rights to create the post office correctly. It might show up in the GroupWise View but not have a Novell® eDirectory™ object created for it. Connect to the secondary domain. See “[Connecting to a Domain](#)” in “[Domains](#)” in the *GroupWise 7 Administration Guide*. Then graft the post office into the correct domain. See “[GW / eDirectory Association](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs when deleting a Library object representing a remote document storage area, the remote document storage area and its directory might have already been deleted.

Action: In ConsoleOne®, display the GroupWise View. Right-click the Library object, then click Properties. Remove the path to the document storage area that no longer exists. Select Store Documents in Post Office, then click OK. Then delete the library object from the GroupWise View.

C007 Database error

Source: GroupWise engine; database services.

Action: See “[C0xx Database error \(Support assistance recommended\)](#)” on page 72.

C008 Database error

Source: GroupWise engine; database services.

Action: See “[C0xx Database error \(general database repair strategies\)](#)” on page 72.

C009 Database error

Source: GroupWise engine; database services.

Action: “[C0xx Database error \(Support assistance recommended\)](#)” on page 72.

C00A Database error

Source: GroupWise engine; database services.

Action: “[C0xx Database error \(Support assistance recommended\)](#)” on page 72.

C00B Database error

Source: GroupWise engine; database services.

Action: See “[C0xx Database error \(general database repair strategies\)](#)” on page 72.

C00C Field type mismatch

Source: GroupWise engine; database services.

Explanation: Invalid field type in record being added.

Possible Cause: If this error occurs when rebuilding a database, you might not be connected to the correct GroupWise system.

Action: Connect to the GroupWise system where the database is located. See “[Select Domain](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*. Then perform the rebuild again.

C00D Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (Support assistance recommended)” on page 72.

C00E Invalid index number

Source: GroupWise engine; database services.

Explanation: Invalid index number.

Possible Cause: When converting a post office from 5.x to 6.x, the post office database (wphost.db) was missing in the post office.

Action: Restore the **wphost.db** file to the post office. Although the conversion does not actually use the old wphost.db file, it does attempt to access a file by that name in order to rename it.

C00F Invalid password

Source: GroupWise engine; database services.

Explanation: Invalid password specified on database open.

Possible Cause: If this error occurs when a user has been moved to a different post office, the update to the post office database might not have completed.

Action: Move the user back to the original post office. Verify the user’s password. Make sure the agents are running. Repeat the move user procedure. See “Moving GroupWise Accounts” in “Users” in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs when rebuilding a database, you might not be connected to the correct GroupWise system.

Action: Connect to the GroupWise system where the database is located. See “Connecting to a Domain” in “Domains” in the *GroupWise 7 Administration Guide*. Then perform the rebuild again.

Possible Cause: The password information in the user database (**userxxx.db**) has been damaged.

Action: Check and, if necessary, repair the database. See “Maintaining User/Resource and Message Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck. See “Standalone Database Maintenance Programs” in “Databases” in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs in the GroupWise client when accessing archived messages, the archive might be damaged.

Action: In the GroupWise client, open the archive, then use the Repair Mailbox feature to repair the archive. See “Enabling GroupWise Check in the Windows Client” in “Client” in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck on the user’s archive. See “Standalone Database Maintenance Programs” in “Databases” in the *GroupWise 7 Administration Guide*.

C010 Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (Support assistance recommended)” on page 72.

C011 Database being modified

Source: GroupWise engine; database services.

Explanation: Read encountered a modified block.

Possible Cause: A read operation encountered a block in the database that was being modified by another user. The read is unable to continue because transaction logging has been disabled for the database.

Action: Perform the operation again. This is a temporary condition and usually corrects itself. As a general rule, transaction logging should never be disabled on GroupWise databases.

Action: If transaction logging has been disabled on the database, the only way to re-enable it is to rebuild the database. See [“Maintaining Domain and Post Office Databases”](#) and [“Maintaining User/Resource and Message Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

C012 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(general database repair strategies\)”](#) on page 72.

C013 Index full

Source: GroupWise engine; database services.

Explanation: B-tree is full.

Possible Cause: One of the B-trees in the database is full, which means either an index area or a record area in the database is full.

Action: Delete some items from the mailbox (messages, trash, and so on) to free up space in the database.

C014 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C015 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C016 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C017 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C018 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C019 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C01A Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C01B Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(general database repair strategies\)”](#) on page 72.

C01C Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C01D Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C01E Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C01F Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C020 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C021 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C022 Database damaged

Source: GroupWise engine; database services.

- Explanation: The integrity of an item or structure in the database has been compromised.
- Action: Check and, if necessary, repair the database. See “[Maintaining Domain and Post Office Databases](#)” and “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Action: If this error occurs on a message database (`msgnnn.db`) or user database (`userxxx.db`), run GWCheck. See “[Standalone Database Maintenance Programs](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Possible Cause: The `ngwguard.db` file has been damaged.
- Action: Check the size of the `ngwguard.rfl` file (roll forward log). If it is less than 24 KB, it is considered empty. Make backup copies of the `ngwguard.db`, `ngwguard.rfl`, and `ngwguard.fbk` files. Delete the `ngwguard.db` file, then copy `ngwguard.fbk` to `ngwguard.db`. Be sure to copy it; do not rename it. See “[Information Stored in the Post Office](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.
- Possible Cause: If this error occurs when administering GroupWise, a domain database (`wpdomain.db`) or post office database (`wphost.db`) might be damaged.
- Action: Validate and rebuild the domain or post office database. See “[Maintaining Domain and Post Office Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Action: If this error occurs from the POA after you have already rebuilt databases, restart the POA.
- Possible Cause: If this error occurs in the GroupWise client in Remote mode, there might be a problem with the structure or content of the Remote mailbox. For example, copying a GroupWise client installation from one laptop to another might introduce this problem.
- Action: Delete the `rofdata` directory on the remote computer, then request all information from the master mailbox again.
- Action: Reinstall the GroupWise client on the remote computer. See the platform-specific setup instructions for using Remote mode in “[Setting Up GroupWise Modes and Accounts](#)” in “[Client](#)” in the *GroupWise 7 Administration Guide*.
- Possible Cause: The hard disk where the GroupWise databases are stored is damaged.
- Action: Scan the hard disk for damage. Correct any problems with the hard disk.
- Action: Repair the database. See “[Maintaining Domain and Post Office Databases](#)” and “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Action: If the database cannot be repaired, you must restore it from backup. See “[Restoring GroupWise Databases from Backup](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Action: In ConsoleOne[®], you can set the proper user rights for all users in a post office or for an individual user. See “[GroupWise User Rights](#)” in “[Security](#)” in the *GroupWise 7 Administration Guide*.
- Possible Cause: If users are accessing a post office on a NetWare[®] server through a Windows workstation using the Microsoft* Gateway for NetWare, the gateway might not be providing adequate support for the number of users trying to access the post office.
- Action: The Microsoft Gateway for NetWare is not intended as a full service router for NetWare services. Use a more robust connection to the post office.
- Action: Make sure you have all the latest NetWare patches installed. If using the Novell IPX[™]/IP gateway, make sure you have the latest version.

C023 Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (Support assistance recommended)” on page 72.

C024 Database dictionary damaged

Source: GroupWise engine; database services.

Explanation: Database dictionary compromised.

Possible Cause: The database dictionary (*.dc file) has been damaged.

Action: Make sure the **ngwguard.dc** file exists in the post office directory. If it does not, copy it from the **po** subdirectory of your software distribution directory. For the specific locations of this file, see “Post Office Directory” and “Software Distribution Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

Action: If this does not solve the problem, check and repair the database. See “Maintaining User/Resource and Message Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

C026 Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (Support assistance recommended)” on page 72.

C027 Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (Support assistance recommended)” on page 72.

C028 Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (Support assistance recommended)” on page 72.

C029 Database version unsupported

Source: GroupWise engine; database services.

Explanation: Unsupported version of database.

Possible Cause: The database was created with an older version of GroupWise and cannot be opened by the current version.

C02A Cannot access database dictionary file

Source: GroupWise engine; database services.

Explanation: Dictionary file access error.

Possible Cause: In the GroupWise client, this error usually indicates there was a file I/O error accessing one of the database dictionary (*.dc) files which are used to create databases.

Action: Check for any problems accessing the disk where the dictionary files reside. To determine the standard locations for the various database dictionary files, see “Domain Directory” and “Post

Office Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

Action: Make sure the `ngwguard.dc` file exists in the post office directory. If it does not, copy it from the `po` subdirectory of your software distribution directory. For the specific locations of this file, see “Post Office Directory” and “Software Distribution Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

Action: The network might have gone down, or there might be some other transitory problem with the disk. The problem might go away simply by retrying.

C02B Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (database dictionary file)” on page 72.

C02C Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (database dictionary file)” on page 72.

C02D Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (database dictionary file)” on page 72.

C02E Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (database dictionary file)” on page 72.

C02F Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (database dictionary file)” on page 72.

C032 Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (general database repair strategies)” on page 72.

C033 Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (general database repair strategies)” on page 72.

C034 Database error

Source: GroupWise engine; database services.

Action: See “C0xx Database error (database dictionary file)” on page 72.

C035 Database error

Source: GroupWise engine; database services.

Action: See “**C0xx Database error (general database repair strategies)**” on page 72.

C037 Memory error

Source: GroupWise engine; database services.

Action: See “**C0xx Memory error**” on page 72.

C038 Memory error

Source: GroupWise engine; database services.

Action: See “**C0xx Memory error**” on page 72.

C03A Database requires newer version

Source: GroupWise engine; database services.

Explanation: Newer database error.

Possible Cause: GroupWise cannot access the database because it was created using a newer version of GroupWise.

Action: Make sure you are running a current version of the GroupWise software. For technical services and file updates, see [Novell Support \(http://support.novell.com\)](http://support.novell.com).

C03B Database error

Source: GroupWise engine; database services.

Action: See “**C0xx Database error (Support assistance recommended)**” on page 72.

C03C Database error

Source: GroupWise engine; database services.

Action: See “**C0xx Database error (general database repair strategies)**” on page 72.

C03D Unexpected error

Source: GroupWise engine; database services.

Action: See “**C0xx Unexpected error**” on page 72.

C03F Database error

Source: GroupWise engine; database services.

Explanation: GroupWise tried to open a file that could not be recognized as a valid GroupWise database.

Action: Check and, if necessary, repair the database. See “**Maintaining Domain and Post Office Databases**” and “**Maintaining User/Resource and Message Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

Action: If this error occurs on a message database (**msgnnn.db**) or user database (**userxxx.db**), run GWCheck. See “**Standalone Database Maintenance Programs**” in “**Databases**” in the *GroupWise*

7 Administration Guide. It can sometimes be helpful to run GWCheck multiple times, because as some errors are fixed, others are uncovered.

Action: If the damaged database cannot be repaired successfully, restore it from backup.

Action: If a damaged user database cannot be repaired or restored, it can be rebuilt. First, archive all personal appointments, tasks, and notes. Make a backup copy of the user database. Then, re-create the user database. See “*Re-creating a User Database*” in “*Databases*” in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs each time the user exits the GroupWise client, the archive database might be damaged.

Action: In the GroupWise client, open the archive, then use the Repair Mailbox feature to repair the archive. See “*Enabling GroupWise Check in the Windows Client*” in “*Client*” in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck on the archive. See “*Standalone Database Maintenance Programs*” in “*Databases*” in the *GroupWise 7 Administration Guide*.

C040 Database error

Source: GroupWise engine; database services.

Action: See “*C0xx Database error (Support assistance recommended)*” on page 72.

C042 Database being modified

Source: GroupWise engine; database services.

Explanation: Read consistent view of record not available.

Possible Cause: A read operation encountered data that was being modified by another concurrent program. The read operation needs to see a prior version of the data; however, no prior version is available. This error should be handled by the GroupWise engine in most cases. If it finally does come through to the end user, it might indicate there is a problem with the database. However, it might also indicate the update activity on the database is currently very high.

Action: Generally, the error is transitory and goes away when the operation is retried. Make sure that others are not doing updates to the database, and retry the action. If the problem persists, validate and rebuild the database as necessary. See “*Maintaining Domain and Post Office Databases*” and “*Maintaining User/Resource and Message Databases*” in “*Databases*” in the *GroupWise 7 Administration Guide*.

Action: If this error occurs on a message or user database, run GWCheck. See “*Standalone Database Maintenance Programs*” in the *GroupWise 7 Administration Guide*.

C043 Database error

Source: GroupWise engine; database services.

Action: See “*C0xx Database error (general database repair strategies)*” on page 72.

C044 Database error

Source: GroupWise engine; database services.

Action: See “*C0xx Database error (Support assistance recommended)*” on page 72.

C045 Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C046 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(general database repair strategies\)” on page 72.](#)

C047 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)” on page 72.](#)

C048 Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C04A Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C04B Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)” on page 72.](#)

C04C Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(Support assistance recommended\)” on page 72.](#)

C04D Memory error

Source: GroupWise engine; database services.

Action: See [“C0xx Memory error” on page 72.](#)

C04E Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(general database repair strategies\)” on page 72.](#)

C04F Database checksum error

Source: GroupWise engine; database services.

Explanation: Checksum error reading database.

Action: Check and, if necessary, repair the database. See “[Maintaining Domain and Post Office Databases](#)” and “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

If the error returns, check for bad network cards on workstations from which the GroupWise client updates the databases.

Action: If this error occurs on a message database (`msgnnn.db`) or user database (`userxxx.db`), run GWCheck. See “[Standalone Database Maintenance Programs](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: The guardian database (`ngwguard.db`) is damaged.

Action: Stop the POA. Make backup copies of the `ngwguard.db`, `ngwguard.rfl`, and `ngwguard.fbk` files. Delete the `ngwguard.db` file, then create a new, empty file named `ngwguard.db`.

Start the POA. The POA will recognize the invalid `ngwguard.db` file and rebuild it from the `ngwguard.fbk` file, merging in transactions from the `ngwguard.rfl` file.

See also “[Information Stored in the Post Office](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs in the GroupWise client in Remote mode, there might be a problem with the structure or content of the Remote mailbox.

Action: Delete the `rofdata` directory on the remote computer, then request all information from the master mailbox again.

Action: Reinstall GroupWise on the remote computer. See the platform-specific setup instructions for using Remote mode in “[Setting Up GroupWise Modes and Accounts](#)” in “[Client](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs in the GroupWise client in the Find Results dialog box, the POA has not indexed the documents yet and might not be running.

Action: Start the POA. Check its indexing cycle. See “[Regulating Indexing](#)” in “[Optimizing the POA](#)” in the *GroupWise 7 Administration Guide*.

After the documents have been indexed, the user will be able to use the Find feature in the GroupWise client to access them.

C050 Transaction aborted

Source: GroupWise engine; database services.

Explanation: Attempted operation after critical error; transaction aborted.

Possible Cause: If this error occurs during domain-related activities, such as adding users or synchronizing domains, the domain database has been damaged.

Action: Check and, if necessary, repair the domain database. See “[Maintaining Domain and Post Office Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

C055 Unexpected error

Source: GroupWise engine; database services.

Action: See “[C0xx Unexpected error](#)” on page 72.

C057 Database maintenance in progress; please exit

Source: GroupWise engine; database services.

- Explanation: Maintenance in progress error.
- Possible Cause: Database maintenance in progress (one of the databases is being recovered or rebuilt).
- Action: Exit GroupWise and try again later. Depending on the size of the database, the maintenance could take from a few seconds to several minutes.
- Possible Cause: If the condition continues for an extended period and no GroupWise maintenance is being performed, another program might already have the required file open with exclusive access.
- Action: Check the open/lock activity on GroupWise databases and other files. You might find that a backup program is holding the file open.
- Possible Cause: If this error occurs constantly from the POA, a damaged message file might be blocking its processing.
- Action: Check the priority subdirectories of the `\wpcout\ofs` directory. See “Post Office Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. Move message files out to a temporary location until the damaged message file is eliminated. Undamaged message files can then be returned to their original subdirectories for processing.

C059 Database file already exists

- Source: GroupWise engine; database services.
- Explanation: GroupWise attempted to create a user file, message file, or library file, but it could not create the file because the file already existed.
- Possible Cause: The `ngwguard.db` file has been renamed or deleted. When the POA detects the guardian database is missing, it creates a new one. The original guardian database contained a catalog of dependent databases (user, messages, library, and so on). The new guardian database lacks this catalog, so the POA attempts to create the needed dependent databases, but it cannot because they already exist. The POA does not overwrite existing files. See also “Information Stored in the Post Office” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.
- Action: Restore the original `ngwguard.db` file from backup. If the original guardian database is not available, seek assistance. For technical services, see [Novell Support \(http://support.novell.com\)](http://support.novell.com).
- Possible Cause: A user was moved to a different post office and then moved back to the original post office. When the user is moved back to the original post office, the POA attempts to create the user database. If the user database was not deleted when the user was moved out, the POA cannot create the new user database.
- Action: Delete the residual user database, then move the user back into the post office. See “Moving GroupWise Accounts” in “Users” in the *GroupWise 7 Administration Guide*.

C05D Cannot open database file

- Source: GroupWise engine; database services.
- Explanation: Store file not found.
- Possible Cause: GroupWise cannot open a file associated with a multi-file database. For example, one of the dependent databases listed in `ngwguard.db` has been deleted.
- Action: Restore the missing database from backup.
- Possible Cause: If this error occurs when users send mail, the message database (`msgnnn.db`) to which the users belong might be missing.

- Action: If the message database cannot be restored from backup, perform a structural rebuild on the user(s) experiencing the problem. See [“Performing a Structural Rebuild of a User Database”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*. This will create a new, empty message database. Old messages will no longer be available to the affected users.
- Possible Cause: If the message occurs for only a single user, that user’s user database (`userxxx.db`) might be missing.
- Action: If the user database cannot be restored from backup, re-create the user database. See [“Re-creating a User Database”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.
- Possible Cause: A library database is missing.
- Action: Library databases must be restored from backup. They cannot be re-created.
- Possible Cause: If this message occurs from the POA when starting its indexing cycle, a library directory structure might have been deleted without deleting the library object.
- Action: Run GWCheck to perform a structural rebuild on the `dmsh.db` file in the post office, then verify the library. See [“Standalone Database Maintenance Programs”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.
- Then delete the library. See [“Deleting a Library”](#) in [“Libraries and Documents”](#) in the *GroupWise 7 Administration Guide*.
- Possible Cause: If this message occurs in the GroupWise client in Remote mode, a database might be missing from the Remote mailbox.
- Action: Delete the `rofddata` directory on the remote computer, then request all information from the master mailbox again.

C05E Unexpected error

- Source: GroupWise engine; database services.
- Action: See [“C0xx Unexpected error”](#) on page 72.

C060 Unexpected error

- Source: GroupWise engine; database services.
- Action: See [“C0xx Unexpected error”](#) on page 72.

C061 Unexpected error

- Source: GroupWise engine; database services.
- Action: See [“C0xx Unexpected error”](#) on page 72.

C062 Unexpected error

- Source: GroupWise engine; database services.
- Action: See [“C0xx Unexpected error”](#) on page 72.

C063 Database error

- Source: GroupWise engine; database services.
- Action: See [“C0xx Database error \(Support assistance recommended\)”](#) on page 72.

C066 Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72](#).

C067 Database error

Source: GroupWise engine; database services.

Explanation: Invalid store number.

Possible Cause: The post office database ([wphost.db](#)) has been damaged.

Action: Check and, if necessary, repair the database. See [“Maintaining Domain and Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs when a new user starts the GroupWise client, there might be a problem with the user database ([userxxx.db](#)).

Action: Perform a structural rebuild on the user. See [“Performing a Structural Rebuild of a User Database”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

Action: Reset the client options for that user. See [“Resetting Client Options to Default Settings”](#) in [“Users”](#) in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs when new users exit GroupWise or try to archive items, the archive might be damaged.

Action: Copy a new [ngwguard.dc](#) file from the [po](#) subdirectory of the software distribution directory into the post office directory. Delete new users' archive directories, because they haven't been able to archive anything yet.

C068 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(general database repair strategies\)” on page 72](#)

C069 Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(database dictionary file\)” on page 72](#).

C06A Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(general database repair strategies\)” on page 72](#).

C06B Database error

Source: GroupWise engine; database services.

Explanation: Server not defined.

Possible Cause: The platform-specific definition needed by the database to identify the location of the database files is either missing or invalid.

Action: Check and repair the database. See “[Maintaining Domain and Post Office Databases](#)” and “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

C06C Database error

Source: GroupWise engine; database services.

Explanation: Driver not found.

Possible Cause: The platform-specific definition needed by the database to identify the location of the database files is either missing or invalid.

Action: Check and repair the database. See “[Maintaining Domain and Post Office Databases](#)” and “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

C06D Database error

Source: GroupWise engine; database services.

Explanation: Bad driver path.

Possible Cause: The platform-specific definition needed by the database to identify the location of the database files is either missing or invalid.

Action: Check and repair the database. See “[Maintaining Domain and Post Office Databases](#)” and “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

C06E Unexpected error

Source: GroupWise engine; database services.

Action: See “[C0xx Unexpected error](#)” on page 72.

C06F Store number mismatch

Source: GroupWise engine; database services.

Explanation: The store number in a database does not match the store number recorded in the store catalog.

Possible Cause: The database is damaged.

Action: Check and, if necessary, repair the database. See “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck. See “[Standalone Database Maintenance Programs](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: The database has been renamed to another valid database name (for example, renaming msg7.db to msg8.db). This circumstance could indicate tampering by a user attempting to access another user’s messages.

Action: Restore the original database. See “[Restoring GroupWise Databases from Backup](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*. For information about databases in the post office, see “[Post Office Directory](#)” in “[Directory Structure Diagrams](#)” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

C071 Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C072 Database error

Source: GroupWise engine; database services.

Explanation: Guardian transaction active.

Possible Cause: Attempted to synchronize a dependent database dictionary file. However, the parent database dictionary file, which contains the definitions, was locked by another process. See [“Information Stored in the Post Office”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

Action: Retry the operation.

C073 Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C076 Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C077 Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C078 Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C079 Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C07A Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C07B Database error

Source: GroupWise engine; database services.

Action: See [“C0xx Database error \(general database repair strategies\)” on page 72.](#)

C07C Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C07D Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C07E Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C07F Unexpected error

Source: GroupWise engine; database services.

Action: See [“C0xx Unexpected error” on page 72.](#)

C080 Index not found

Source: GroupWise engine; database services.

Explanation: A QuickFinder™ index is missing.

Action: Repair the indexes in the post office database (`wphost.db`). See [“Rebuilding Database Indexes”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

Action: Rebuild the post office database. See [“Rebuilding Domain or Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

C081 Attachment missing

Source: GroupWise engine; database services.

Explanation: An attachment file that should be available under **offiles** in the post office directory is missing.

Possible Cause: Files have been inadvertently removed from the offiles directory.

Action: Restore the files from backup.

Possible Cause: The post office has been copied to a new location and not all files in the offiles directory were copied successfully.

Action: Make sure that all files from the offiles directory are available in the new location.

Possible Cause: The user has archived the message with the attachment and the archive directory is not currently available.

Action: Check the current archive location. In the GroupWise client, click Tools > Options > Environment > File Location.

Possible Cause: A document in a GroupWise library is not accessible.

Action: Repair the library. See [“Maintaining Library Databases and Documents”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*. Under the Analyze/Fix action, select the following:

- ◆ Verify Library

- ◆ Fix Document/Version/Element
- ◆ Verify Document Files
- ◆ Validate All Document Security

C0xx Database error (Support assistance recommended)

Source: GroupWise engine; database services.

Explanation: Generic database error.

Action: Typically, database errors in this group require assistance from Support. However, you might want to try to repair the database yourself before contacting Support. See [“C0xx Database error \(general database repair strategies\)”](#) on page 72.

C0xx Database error (general database repair strategies)

Source: GroupWise engine; database services.

Explanation: Generic database error.

Action: Check and, if necessary, repair the database. See [“Maintaining Domain and Post Office Databases”](#) and [“Maintaining User/Resource and Message Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

Action: If this error occurs on a message database (`msgnnn.db`) or user database (`userxxx.db`), run GWCheck. See [“Standalone Database Maintenance Programs”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

Action: If the damaged database cannot be repaired successfully, restore it from backup.

Action: If a damaged user database cannot be repaired or restored, it can be rebuilt. First, archive all personal appointments, tasks, and notes. Make a backup copy of the user database. Then, re-create the user database. See [“Re-creating a User Database”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

C0xx Database error (database dictionary file)

Source: GroupWise engine; database services.

Explanation: Problem with a database dictionary (*.dc) file.

Action: Copy the `ngwguard.dc` file from the `po` subdirectory of the software distribution directory to the post office directory. For the specific locations of the file, see [“Software Distribution Directory”](#) and [“Post Office Directory”](#) in [“Directory Structure Diagrams”](#) in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

C0xx Memory error

Source: GroupWise engine; database services.

Explanation: Generic memory error.

Action: Retry the operation that caused the error. If it occurs again, restart GroupWise. If it occurs again, it might be necessary to run GroupWise in an environment with more available memory.

C0xx Unexpected error

Source: GroupWise engine; database services.

Explanation: An engine error has occurred for which GroupWise does not have a specific error message.

Action: Exit and then restart the GroupWise client.

Dxxx Engine Error Codes

Range:

- ◆ D00x
- ◆ D01x
- ◆ D02x
- ◆ D03x
- ◆ D04x
- ◆ D05x
- ◆ D06x
- ◆ D07x
- ◆ D10x
- ◆ D11x
- ◆ D12x
- ◆ D20x
- ◆ D50x
- ◆ D70x
- ◆ D71x
- ◆ D90x
- ◆ DA0x
- ◆ DA1x
- ◆ DB0x
- ◆ DB1x
- ◆ DB2x
- ◆ DB3x
- ◆ DB4x
- ◆ DB5x
- ◆ DB6x
- ◆ DExx
- ◆ DFxx

Range: D00x

- “D001 Unexpected error” on page 82
- “D002 Folder not empty” on page 82
- “D004 Database error” on page 82
- “D005 Settings field list is not valid” on page 83
- “D006 Unexpected error” on page 83
- “D009 Cannot use group name in distribution list” on page 83
- “D00A Syntax error in address” on page 83
- “D00B Missing closing quotation mark (”)” on page 83
- “D00C Unexpected error” on page 84
- “D00D Cannot match parentheses” on page 84
- “D00E Distribution list contains nested groups” on page 84
- “D00F Remote mail error” on page 84

Range: D01x

- “D017 Too many users in address” on page 84
- “D018 Unexpected error” on page 85
- “D019 Password incorrect” on page 85
- “D01A Password too long” on page 85
- “D01B Access to GroupWise denied” on page 85
- “D01C Remote mail error” on page 85
- “D01E Cannot execute rule” on page 86
- “D01F Archive path not specified” on page 86

Range: D02x

- “D020 Rule caused infinite loop” on page 86
- “D021 Cannot deliver message” on page 86
- “D023 User ID expired” on page 86
- “D024 Rule cannot forward, reply, accept, or delegate personal item” on page 87
- “D025 Users not specified” on page 87
- “D026 Missing opening brace in distribution list” on page 87
- “D027 Missing closing brace in distribution list” on page 87
- “D028 Lost attachment” on page 87
- “D029 Recipient not specified” on page 88
- “D02A Name for group not specified” on page 88
- “D02F Database error” on page 88

Range: D03x

- “D030 Missing post office number for status” on page 88
- “D039 Missing attachment” on page 88

“D03F Database error” on page 89

Range: D04x

“D040 Cannot delete folder used in rule” on page 89

“D041 No recipients in post office” on page 89

“D043 Inconsistent distribution list” on page 89

“D044 Auto-rebuild disabled” on page 90

“D049 Error reported from Novell NDS” on page 90

“D04A Unexpected error” on page 90

“D04B Unexpected error” on page 90

“D04F Unexpected error” on page 90

Range: D05x

“D050 Cannot connect to specified post office” on page 90

“D051 Cannot connect to specified post office” on page 91

“D054 Cannot connect to specified post office” on page 91

“D055 Cannot connect to specified post office” on page 91

“D057 Cannot connect to any post office” on page 91

“D058 Version mismatch on GroupWise client/POA/post office” on page 92

“D059 Recursion limit exceeded during delivery” on page 92

“D05A User database access denied” on page 92

“D05D Post office intruder lockout is enforced” on page 93

“D05E Message size exceeds limit” on page 93

“D05F Box size limit exceeded” on page 93

Range: D06x

“D060 Message size exceeds threshold limit” on page 94

“D061 Status denied to external Internet user” on page 94

“D062 Busy Search denied for external Internet user” on page 94

“D065 Attempt to purge item that has not been backed up” on page 94

“D066 Attempt to purge an item from a user that has not been backed up” on page 94

“D069 Attempt to open invalid backup location” on page 95

“D06B LDAP failure detected” on page 95

“D06E Lockout of older GroupWise clients being enforced” on page 95

“D06F This GroupWise client doesn't match the user's license” on page 95

Range: D07x

“D071 LDAP authentication failed because the password has expired” on page 96

“D072 Changing the LDAP password has been disabled” on page 96

“D073 Attempting to log in trusted without SSL” on page 96

“D074 Invalid key for trusted application” on page 96

“D075 Invalid IP address for trusted application” on page 96
“D076 Missing trusted application name” on page 97
“D077 The problem file is being rebuilt” on page 97
“D078 LDAP SSL key file not found” on page 97
“D07F Unexpected error” on page 97

Range: D10x

“D101 User not found” on page 97
“D102 Ambiguous user ID” on page 99
“D103 Post office not found during login” on page 99
“D104 Ambiguous post office” on page 99
“D105 Directory Services data missing” on page 99
“D106 Database error” on page 100
“D107 Record not found” on page 100
“D108 Unexpected error” on page 100
“D109 Bad parameter” on page 100
“D10A Unexpected error” on page 100
“D10B Database needs to be repaired” on page 101
“D10C Unexpected error” on page 101
“D10D Cannot open any more mailboxes” on page 101

Range: D11x

“D110 Unexpected error” on page 101
“D113 Open database maximum exceeded” on page 101
“D114 Group not found” on page 102
“D115 Database error” on page 102
“D116 File not database” on page 102
“D117 GroupWise version too old” on page 102
“D118 Database error” on page 103
“D119 Unexpected error” on page 103
“D11B Too many items in mailbox” on page 103
“D11C Cannot use group name” on page 103
“D11D GroupWise version newer than database” on page 103

Range: D12x

“D124 Access to user denied” on page 104

Range: D20x

“D201 Unexpected error” on page 104
“D202 General printing error” on page 104

Range: D50x

- “D506 Security violation” on page 104
- “D507 Administrator record not found in database” on page 105
- “D508 Transaction failed” on page 105

Range: D70x

- “D701 Unexpected error” on page 105
- “D704 Unexpected error” on page 106
- “D705 Unexpected error” on page 106
- “D706 Unexpected error” on page 106
- “D707 Unexpected error” on page 106
- “D708 Directory entry record not found” on page 106
- “D709 Unexpected error” on page 106
- “D70A Memory error” on page 106
- “D70B Database inconsistency detected” on page 107
- “D70D Unexpected error” on page 107
- “D70E Duplicate entry in database” on page 107
- “D70F Unexpected error” on page 107

Range: D71x

- “D710 Incompatible platform” on page 107
- “D712 Post office currently disabled” on page 108
- “D713 Database dictionary not found” on page 108
- “D714 User database temporarily disabled” on page 108
- “D715 User has failed in too many login attempts, login disabled” on page 108
- “D716 The System Address Book needs to be refreshed” on page 109

Range: D90x

- “D901 Unexpected error” on page 109
- “D902 Unexpected error” on page 109
- “D904 Unexpected error” on page 109
- “D90A Unexpected error” on page 109
- “D90B Unexpected error” on page 109
- “D912 Cannot process message file” on page 109

Range: DA0x

- “DA0C Incorrect DLL version” on page 110
- “DA0D Cannot create directory in post office” on page 110

“DA0E Path to post office database not specified” on page 110

Range: DA1x

“DA10 Cannot read post office configuration information” on page 110

“DA12 Invalid application configuration name” on page 111

“DA13 /name switch required” on page 111

“DA17 /user and /password switches required for this configuration” on page 111

Range: DB0x

“DB01 Operation cancelled” on page 112

“DB02 Database access error” on page 112

“DB03 Operation pending; cannot modify” on page 112

“DB04 Owner not valid user” on page 112

“DB05 Invalid path” on page 112

“DB08 Non-unique name” on page 112

“DB09 User owns resource” on page 113

“DB0A Record not found” on page 113

“DB0B Required field empty” on page 113

“DB0C Cannot close database” on page 113

“DB0E Insufficient memory to initialize database” on page 114

“DB0F Domain not found” on page 114

Range: DB1x

“DB10 Post office not found” on page 114

“DB11 Unexpected error” on page 114

“DB12 Maximum number of objects per post office reached” on page 114

“DB17 Domain already exists in specified directory” on page 115

“DB19 Local post office not found” on page 115

“DB1A Insufficient administrative rights to perform operation” on page 115

“DB1B Message Transfer Agent not installed” on page 115

“DB1C Invalid object name” on page 115

“DB1D Cannot delete post office” on page 115

“DB1F Cannot delete current domain” on page 116

Range: DB2x

“DB20 Unexpected error” on page 116

“DB21 Database inconsistency detected” on page 116

“DB23 Password incorrect” on page 116

“DB24 Invalid link” on page 116

“DB25 Duplicate domain name” on page 117

“DB26 Secondary domains exist” on page 117

“DB29 Invalid character” on page 117
“DB2A Invalid name” on page 117
“DB2B Non-unique entry” on page 118
“DB2C Invalid post office database” on page 118
“DB2D Platform error” on page 118
“DB2E Link record not found” on page 118
“DB2F Correct database type not found” on page 118

Range: DB3x

“DB30 Gateway directory not found” on page 118
“DB31 Required field missing or empty” on page 119
“DB32 Required field missing” on page 119
“DB33 Cannot open all post offices” on page 119
“DB34 Time zone definition not found” on page 119
“DB35 No pending operation for record” on page 119
“DB37 Cannot delete current domain” on page 120
“DB38 Cannot delete domain that has post offices” on page 120
“DB39 Domain database not found” on page 120
“DB3A Cannot delete domain that has links” on page 120
“DB3B Remote management message sent” on page 120
“DB3C Domain database in use” on page 121
“DB3D Database sorting language changed” on page 121
“DB3F Cannot delete required field” on page 121

Range: DB4x

“DB40 Cannot delete gateway used in link” on page 121
“DB41 Database does not match domain or post office” on page 121
“DB42 Information lost during recovery” on page 121
“DB43 Maximum number of open post offices reached” on page 122
“DB45 GroupWise system not found” on page 122
“DB46 Path too long” on page 122
“DB47 Invalid area” on page 122
“DB48 Cannot delete domain that has links” on page 122
“DB49 Cannot use limited visibility distribution list as administrator” on page 123
“DB4A External sync message from unknown system” on page 123
“DB4B Cannot delete Internet domain name that is still referenced” on page 123
“DB4D Database recovery required to update database structure” on page 123
“DB4E Cannot delete default gateway” on page 124
“DB4F Cannot delete POA that performs message transfer” on page 124

Range: DB5x

“DB50 Access to this library has been enabled by WebPublisher” on page 124

“DB51 Required network address information is missing” on page 124
“DB52 Required path information is missing” on page 125
“DB53 No message transfer POA has been selected” on page 125
“DB55 No POA is available for client/server” on page 125
“DB56 Specified e-mail address conflicts with the address of an existing gateway alias” on page 125
“DB57 Specified e-mail address conflicts with the address of an existing user” on page 125
“DB58 Specified e-mail address conflicts with an address from a post office alias record” on page 125
“DB59 This GroupWise administration version is older than the minimum allowed by the system administrator” on page 126

Range: DB6x

“DB60 The LDAP server is being used for eDirectory synchronization” on page 126
“DB61 The signature information is too large” on page 126
“DB62 The software area is being referenced” on page 126

Range: DExx

“DE02 Cannot perform delayed action request” on page 126
“DE05 Unexpected error” on page 127

Range: DFxx

“DF10 Required file or directory missing” on page 127
“DF15 Records lost during rebuild” on page 127
“DF17 Cannot create required directory” on page 128
“DF1C Document storage area definitions are not identical” on page 128
“DF27 Invalid NGWCHECK.DB database migration level” on page 128
“DF28 Failure using the NGWCHECK.DB database” on page 128

D001 Unexpected error

Source: GroupWise® engine.

Action: See “Dxxx Unexpected error” on page 128.

D002 Folder not empty

Source: GroupWise engine.

Explanation: Folder not empty.

Action: Delete all items in the folder before attempting to delete it.

D004 Database error

Source: GroupWise engine.

Explanation: Database error. Attempt to read or modify settings failed.

Possible Cause: The user database (**userxxx.db**) contains inconsistent information.

Action: Check and, if necessary, repair the user database. See “**Maintaining User/Resource and Message Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

D005 Settings field list is not valid

Source: GroupWise engine.

Possible Cause: The post office database (**wphost.db**) is damaged.

Action: Rebuild the post office database. See “**Rebuilding Domain or Post Office Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

D006 Unexpected error

Source: GroupWise engine.

Action: See “**Dxxx Unexpected error**” on page 128.

D009 Cannot use group name in distribution list

Source: GroupWise engine.

Explanation: A group has been included in a Workflow.

Possible Cause: A group name was entered in the distribution list for a routed item. Groups are not supported in a workflow step.

Action: Delete the group name, then provide the names of the individual users in the group.

D00A Syntax error in address

Source: GroupWise engine.

Explanation: Syntax error.

Possible Cause: A syntax error was detected in the distribution list. One of the following conditions exists:

- ◆ There is a colon (:), at-sign (@), or a period (.) inside a parenthesized list.
- ◆ There are parentheses with nothing between them () or an opening parenthesis followed by a comma (, in the distribution list. There must be a user ID between the parenthesis and the comma.
- ◆ There is a comma followed by a closing parenthesis ,) in the distribution list. There must be a user ID between the comma and the parenthesis.
- ◆ There is a colon (:) somewhere after a closing parenthesis.

Action: Locate the syntax error in the distribution list. A pointer indicates where the error is. Correct the syntax error, then retry the operation.

D00B Missing closing quotation mark (")

Source: GroupWise engine.

Explanation: No closing quotation mark.

Possible Cause: A closing quotation mark (") is missing in a distribution list.

Action: Type the closing quotation mark, then retry the operation.

D00C Unexpected error

Source: GroupWise engine.

Action: See [“Dxxx Unexpected error” on page 128](#).

D00D Cannot match parentheses

Source: GroupWise engine.

Explanation: Problem with parentheses.

Possible Cause: Cannot match the parentheses in the distribution list. While processing the To:, BC:, and CC: buffers of a send window, a problem was found matching up parentheses. See also [“D00A Syntax error in address” on page 83](#).

Action: Check the distribution list for incorrect usage of parentheses and resend.

D00E Distribution list contains nested groups

Source: GroupWise engine.

Explanation: Groups are nested too deep.

Possible Cause: The distribution list contains groups that are nested more than five levels deep or it might contain a circular reference. For example, if a personal group contains a recipient with the same name as the personal group, a circular reference is created.

Action: Edit the groups to remove the circular reference, or include the contents of one of the subgroups in a higher level group to reduce the levels in the structure.

D00F Remote mail error

Source: GroupWise engine.

Explanation: Invalid remote mail request.

Possible Cause: Remote mail error. This error is displayed whenever a more specific error is not available. The most common cause is a request for items that have already been deleted.

Action: Check and repair the databases of the master mailbox. See [“Maintaining User/Resource and Message Databases” in “Databases” in the *GroupWise 7 Administration Guide*](#).

Action: Run GWCheck. See [“Standalone Database Maintenance Programs” in “Databases” in the *GroupWise 7 Administration Guide*](#).

Action: In Remote mode, the GroupWise client should automatically repair any problems with the remote databases. If the client is unable to repair the problem, you can delete the **rofddata** directory on the remote computer, then request all information from the master mailbox again.

D017 Too many users in address

Source: GroupWise engine.

Explanation: Reply buffer full.

Possible Cause: When Reply to All is selected, personal groups and public distribution lists are expanded into a complete list of users. If the expanded list exceeds 6 KB, this error occurs. If the reply is sent, some of the users included in the original groups might not receive the reply.

Action: To reply to all the users, create a personal group that contains the users and send the reply to that group. If replying to these groups is common, the personal groups could be made into public distribution lists and selected manually when replying to all users.

D018 Unexpected error

Source: GroupWise engine.

Action: See “[Dxxx Unexpected error](#)” on page 128

D019 Password incorrect

Source: GroupWise engine.

Explanation: Invalid password.

Action: Type the correct password. Passwords are case sensitive.

Possible Cause: The password information in the post office database ([wphost.db](#)) has been damaged.

Action: Rebuild the post office database. See “[Rebuilding Domain or Post Office Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: If rebuilding the post office database does not resolve the problem, rebuild the domain database ([wpdomain.db](#)).

D01A Password too long

Source: GroupWise engine.

Explanation: The password is too long. Passwords can contain a maximum of 64 characters.

Action: Type a password with fewer than 64 characters.

D01B Access to GroupWise denied

Source: GroupWise engine.

Explanation: Access to the user database required for this operation has not been granted.

Possible Cause: You are trying to proxy to a user’s mailbox, or perform an action as a proxy on another user’s mailbox, but the mailbox owner has not granted you sufficient rights.

Action: Ask the owner to grant you the necessary rights. The user should add your user ID to his or her access list to grant proxy access. Look up “[proxy, rights](#)” and “[access](#)” in GroupWise client Help.

Possible Cause: You are trying to perform an action in a shared folder, but you do not have rights to perform the requested operation.

Action: Ask the owner of the shared folder to grant you the necessary rights. Look up “[shared folders](#)” in GroupWise client Help.

D01C Remote mail error

Source: GroupWise engine.

Explanation: Invalid remote mail request.

Possible Cause: Remote mail error. This error is displayed whenever a more specific error is not available. The most common cause is a request for items that have already been deleted.

- Action: Check and repair the databases of the master mailbox. See “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Action: Run GWCheck. See “[Standalone Database Maintenance Programs](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Action: In Remote mode, the GroupWise client should automatically repair any problems with the remote databases. If the client is unable to repair the problem, you can delete the **rofdata** directory on the remote computer, then request all information from the master mailbox again.

D01E Cannot execute rule

- Source: GroupWise engine.
- Explanation: Invalid rule action.
- Possible Cause: An archive rule was given an invalid execution type. GroupWise does not allow you to create a rule that automatically archives messages when they are received.
- Action: Edit the rule and select a valid execution type. Look up “rules” in GroupWise client Help.

D01F Archive path not specified

- Source: GroupWise engine.
- Explanation: No archive path.
- Possible Cause: No archive path specified in the GroupWise client.
- Action: Specify the archive path before attempting to archive items. Look up “archive, directory, setting up” in GroupWise client Help.

D020 Rule caused infinite loop

- Source: GroupWise engine.
- Explanation: Rule hop count exceeded.
- Possible Cause: The execution of a rule has caused a message to be sent, which caused the execution of a rule, and so on. To prevent the possibility of infinite looping, the rule execution has been terminated.
- Action: Edit the rule to correct the looping condition. Look up “rules” in GroupWise client Help.

D021 Cannot deliver message

- Source: GroupWise engine.
- Explanation: Remote send requested with no agents present.
- Possible Cause: A message cannot be delivered to a user in a different post office because the POA and MTA are not available.
- Action: Set up the POA for the post office. See “[Installing and Starting the POA](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.
- Action: Set up the MTA for the domain. See “[Installing and Starting the MTA](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.

D023 User ID expired

- Source: GroupWise engine.

Explanation: User account is expired.

Action: You can extend or remove the user's expiration date. See "Expiring a GroupWise Account" in "Users" in the *GroupWise 7 Administration Guide*.

D024 Rule cannot forward, reply, accept, or delegate personal item

Source: GroupWise engine.

Explanation: Action not valid for personal item.

Action: Edit the conditions of the rule so that personal items are not included. Look up "rules" in GroupWise client Help.

D025 Users not specified

Source: GroupWise engine.

Explanation: No users specified.

Possible Cause: No users have been specified in the distribution list.

Action: Type the names of users, or select users from the Address Book to include in the distribution list.

Possible Cause: If this message occurs from the POA, it might be attempting to process a damaged message file.

Action: Check the priority subdirectories of the `\wpcout\ofs` directory in the post office. Check the POA log to determine the offending message file. Delete the offending message file so that subsequent messages can be processed.

D026 Missing opening brace in distribution list

Source: GroupWise engine.

Explanation: No opening brace.

Possible Cause: Mismatched braces in the distribution list. While processing the To:, CC:, and BC: addresses in a message, the end of the input buffer was reached before finding the closing brace.

Action: Check the address for incorrect use of braces, then resend the message.

D027 Missing closing brace in distribution list

Source: GroupWise engine.

Explanation: No closing brace.

Possible Cause: Mismatched braces in the distribution list. While processing the To:, CC:, and BC: addresses in a message, the end of the input buffer was reached before finding the closing brace.

Action: Check the address for incorrect use of braces, then resend the message.

D028 Lost attachment

Source: GroupWise engine.

Explanation: Attachment could not be associated with a message.

Possible Cause: The attachment pointer was damaged.

Action: Resend the message.

D029 Recipient not specified

Source: GroupWise engine.

Explanation: No distribution list for a delegate rule.

Possible Cause: No recipient has been specified in a delegate rule. The delegate rule must contain a valid user ID to which to delegate the item. This error might indicate the user who sees the message, or some other user, has an incorrect delegate rule.

Action: Make sure the delegate rule contains a valid distribution list. Look up “rules” in GroupWise client Help.

D02A Name for group not specified

Source: GroupWise engine.

Explanation: No group name.

Possible Cause: No name has been specified for the distribution list.

Action: Enter a unique group name.

D02F Database error

Source: GroupWise engine.

Explanation: No document record number (DRN) for status.

Possible Cause: The domain database (**wpdomain.db**) or post office database (**wphost.db**) might be damaged.

Action: Rebuild the post office database. See “**Rebuilding Domain or Post Office Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

Action: If rebuilding the post office database does not resolve the problem, rebuild the domain database.

D030 Missing post office number for status

Source: GroupWise engine.

Explanation: Necessary information cannot be accessed.

Possible Cause: Inconsistent database information.

Action: Check and, if necessary, repair the database. See “**Maintaining Domain and Post Office Databases**” and “**Maintaining User/Resource and Message Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck. See “**Standalone Database Maintenance Programs**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

D039 Missing attachment

Source: GroupWise engine.

Explanation: An attachment for a message can no longer be found.

Possible Cause: If this error occurs in the GroupWise client in Remote mode, there might be a problem with the structure or content of the Remote mailbox.

Action: Delete the **rofdata** directory on the remote computer, then request all information from the master mailbox again.

D03F Database error

- Source: GroupWise engine.
- Explanation: No item type.
- Possible Cause: The user database (**userxxx.db**) and/or message database (**msgnnn.db**) for the user have been damaged.
- Action: Check and, if necessary, repair the user and/or message databases. See “**Maintaining User/Resource and Message Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.
- Action: Run GWCheck. See “**Standalone Database Maintenance Programs**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

D040 Cannot delete folder used in rule

- Source: GroupWise engine.
- Explanation: Folder being used in a rule.
- Possible Cause: User cannot delete the folder because it is referenced in a rule.
- Action: Change or delete the rule, then delete the folder. Look up “rules” in GroupWise client Help.

D041 No recipients in post office

- Source: GroupWise engine.
- Explanation: Insufficient recipient information.
- Possible Cause: A Remote user sent a message using a personal group that exists in the user’s master mailbox but has not been downloaded to Remote.
- Action: Download the personal group.

D043 Inconsistent distribution list

- Source: GroupWise engine.
- Explanation: Information in the distribution list does not match information elsewhere in the system.
- Possible Cause: Outdated information in a distribution list, a damaged distribution list, or a damaged message file could cause this error from the POA.
- Action: Check the priority subdirectories of the **\wpesout\ofs** directory in the post office. Check the POA log file to determine the offending message file. See “**Using POA Log Files**” in “**Post Office Agent**” in the *GroupWise 7 Administration Guide*. Determine the originator of the offending message. Check and, if necessary, repair the user database (**userxxx.db**) for that user. See “**Maintaining User/Resource and Message Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.
- Action: Run GWCheck. See “**Standalone Database Maintenance Programs**” in “**Databases**” in the *GroupWise 7 Administration Guide*.
- Possible Cause: The POA has been started with the **/norecover** startup switch and damage to a user or message database has been detected.
- Action: Repair the database. See “**Maintaining User/Resource and Message Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.
- Action: Start the POA without the **/norecover** startup switch so that the POA can automatically recover any databases where damage is detected.

D044 Auto-rebuild disabled

Source: GroupWise engine.

Explanation: Automatic recovery of damaged databases by the POA has been turned off.

Possible Cause: The POA has been started with the `/norecover` startup switch and damage has been detected in a database.

Action: Repair the database. See “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: Start the POA without the `/norecover` startup switch so that the POA can automatically recover any databases where damage is detected.

D049 Error reported from Novell NDS

Source: GroupWise engine.

Explanation: The GroupWise Administrator snap-in to ConsoleOne[®] was unable to retrieve information from Novell[®] eDirectory[™].

Possible Cause: You might be running ConsoleOne with insufficient Browse, Read, or Compare rights to the required eDirectory object.

Action: Check the rights to the GroupWise user, post office, and agent objects in eDirectory.

D04A Unexpected error

Source: GroupWise engine.

Action: See “[Dxxx Unexpected error](#)” on page 128.

D04B Unexpected error

Source: GroupWise engine.

Action: See “[Dxxx Unexpected error](#)” on page 128.

D04F Unexpected error

Source: GroupWise engine.

Action: See “[Dxxx Unexpected error](#)” on page 128.

D050 Cannot connect to specified post office

Source: GroupWise engine.

Explanation: No TCP/IP services.

Possible Cause: The GroupWise client cannot connect to the specified post office in client/server mode because an IP address has not been provided. The POA in a remote post office is required for cross-post office proxy and library access.

Action: Set up the IP address for the POA. See “[Using Client/Server Access to the Post Office](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: The GroupWise client cannot connect to the specified post office in client/server mode because the POA in that post office is not running. The POA in a remote post office is required for cross-post office proxy and library access.

- Action: Make sure the POA is running in the remote post office. See “[Monitoring the POA](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.
- Action: Make sure the POA in the remote post office is configured with the correct IP address and TCP port.
- Action: Make sure the POA in the remote post office is configured to allow TCP/IP connections. Make sure it has not been started with the `/notcip` switch.

D051 Cannot connect to specified post office

- Source: GroupWise engine.
- Explanation: TCP/IP not allowed.
- Possible Cause: An attempt to connect to a post office by way of a direct or mapped mode was rejected. No IP address information is available to attempt a client/server connection. The administrator hasn't set up the client/server addressing.
- Action: Set up the IP address for the POA. See “[Using Client/Server Access to the Post Office](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

D054 Cannot connect to specified post office

- Source: GroupWise engine.
- Explanation: Missing path for direct mode connection.
- Possible Cause: The post office rejected the client/server mode connection but is allowing direct mode. The path might be set up, but not for this platform.
- Action: Set up the path for the specified post office in the post office Identification page in ConsoleOne.
- Action: To start the GroupWise client in direct mode, use the `/ph` switch to provide the path to the post office.
- Action: If you want to use client/server mode, you can set up an additional POA to handle client/server communication. See “[Using Client/Server Access to the Post Office](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

D055 Cannot connect to specified post office

- Source: GroupWise engine.
- Explanation: Cannot use direct (mapped) connection.
- Possible Cause: The post office rejected the direct mode connection but is allowing client/server mode.
- Action: Make sure the IP address for the POA is set up correctly. See “[Using Client/Server Access to the Post Office](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

D057 Cannot connect to any post office

- Source: GroupWise engine.
- Explanation: TCP/IP default address failed.
- Possible Cause: An attempt to connect to a post office using the GroupWise IP address defaults (NGWNAMESESERVER and NGWNAMESESERVER2) was unsuccessful.
- Possible Cause: No client/server or direct information was specified or available.

Action: Make sure the GroupWise name server is properly set up and running. See “[Simplifying Client/Server Access with a GroupWise Name Server](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: The GroupWise name server cannot locate any post offices.

Action: Make sure the network connections to the servers where post offices reside are functioning properly.

D058 Version mismatch on GroupWise client/POA/post office

Source: GroupWise engine.

Explanation: The post office directory, with its associated user databases ([userxxx.db](#)) and message databases ([msgnnn.db](#)) was created by a version of GroupWise that is older than the version of the GroupWise client that is accessing the post office.

Possible Cause: A user is running the latest version of the GroupWise client, but the post office has not yet been updated.

Action: Update the post office. See “[Update](#)” in the “*GroupWise 7 Installation Guide*”.

Possible Cause: The post office has been updated, but the latest version of the POA has not yet been installed and started.

Action: Update the POA. See “[Updating Post Offices](#)” in “[Update](#)” in the “*GroupWise 7 Installation Guide*”.

D059 Recursion limit exceeded during delivery

Source: GroupWise engine.

Explanation: The POA received a message that contained more than 36 levels of encapsulation. The POA could not deliver the message.

Possible Cause: This can be caused by rule forwarding loops that include one hop to an external user, or by some Internet chain letters.

Action: Check the rule configuration of the GroupWise recipient. Disable any rules that forward mail to an external user who might be forwarding the mail back into GroupWise. Look up “rules” in GroupWise client Help.

D05A User database access denied

Source: GroupWise engine.

Explanation: The GroupWise client cannot start because it cannot access the user’s user database ([userxxx.db](#)).

Possible Cause: The user tried to access a mailbox that does not have a password using the wrong NetWare® user ID, in a post office with security set to high.

Action: Set a password on the user’s mailbox. See “[Creating or Changing a Mailbox Password](#)” in “[Users](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: The user’s current login ID, either from NetWare, eDirectory, or Windows, does not match the network login ID stored in the GroupWise user database.

Action: Make sure the user is using the correct login ID.

Possible Cause: Password information in the user database might be damaged.

- Action: Check and, if necessary, repair the database, including resetting user options to reset the password. See [“Maintaining User/Resource and Message Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.
- Action: Run GWCheck. See [“Standalone Database Maintenance Programs”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.
- Possible Cause: The post office database (**wphost.db**) might be damaged.
- Action: Rebuild the index of the post office database. See [“Rebuilding Database Indexes”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.
- Action: If rebuilding the index is not sufficient to resolve the problem, validate the database, then take the appropriate actions to either recover or rebuild the database. See [“Maintaining Domain and Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.
- Possible Cause: The IP address of the POA has changed, but GroupWise client users are still trying to start the client using old /ipa and /ipp client startup switch settings.
- Action: Update the information in users’ /ipa and /ipp switch settings with the current IP address information.
- Action: Remove the /ipa and /ipp switches and let the client and/or the POA resolve the address. See [“Simplifying Client/Server Access with a GroupWise Name Server”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

D05D Post office intruder lockout is enforced

- Source: GroupWise engine.
- Explanation: The POA has detected a possible intruder. The user has been locked out.
- Action: You have several options for handling the situation. See [“Enabling Intruder Detection”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

D05E Message size exceeds limit

- Source: GroupWise engine.
- Explanation: A user tried to send a message that exceeded the user’s message size limit as set by the administrator.
- Possible Cause: The user is not aware that there is a message size limit on his or her mailbox.
- Action: Notify the user of the message size limit so that the user can send messages of appropriate size.
- Possible Cause: The administrator has set a message size limit that is too restrictive. Increase the message size limit.
- Action: Increase the maximum message size for the user. See [“Send Options: Disk Space Management”](#) in [“Users”](#) in the *GroupWise 7 Administration Guide*.

D05F Box size limit exceeded

- Source: GroupWise engine.
- Explanation: A user’s GroupWise mailbox exceeds the size limit set by the administrator
- Possible Cause: The user is not aware that there is a size limit on his or her mailbox.
- Action: Notify the user of the mailbox size limit so that the user can delete unneeded messages from the mailbox.

Possible Cause: The administrator has set a mailbox size limit that is too restrictive. Increase the message size limit.

Action: Increase the maximum mailbox size for the user. See “[Send Options: Disk Space Management](#)” in “[Users](#)” in the *GroupWise 7 Administration Guide*.

D060 Message size exceeds threshold limit

Source: GroupWise engine.

Explanation: A user’s GroupWise mailbox is close to exceeding the size limit set by the administrator

Possible Cause: The user is not aware that there is a size limit on his or her mailbox.

Action: Notify the user of the mailbox size limit so that the user can delete unneeded messages from the mailbox.

Possible Cause: The administrator has set a mailbox size limit that is too restrictive. Increase the message size limit.

Action: Increase the maximum mailbox size for the user. See “[Send Options: Disk Space Management](#)” in “[Users](#)” in the *GroupWise 7 Administration Guide*.

D061 Status denied to external Internet user

Source: GroupWise engine.

Explanation: The local GroupWise system is configured so that users outside the local GroupWise system cannot receive status information about messages.

Action: To permit access to status information by external users, enable Allow External Status Tracking. See “[System Preferences](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*.

D062 Busy Search denied for external Internet user

Source: GroupWise engine.

Explanation: The local GroupWise system is configured so that users outside the local GroupWise system cannot perform Busy Searches on local users.

Action: To permit Busy Search access by external users, enable Allow External Busy Search. See “[System Preferences](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*.

D065 Attempt to purge item that has not been backed up

Source: GroupWise engine.

Explanation: Client Cleanup options are set so that items cannot be purged from users’ mailboxes until they have been backed up. A user has tried to purge an item that has not yet been backed up.

Action: You can allow users to purge items that have not yet been backed up. See “[Environment Options: Cleanup](#)” in “[Users](#)” in the *GroupWise 7 Administration Guide*. See also “[GroupWise Time Stamp Utility](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

D066 Attempt to purge an item from a user that has not been backed up

Source: GroupWise engine.

Explanation: Client Cleanup options are set so that items cannot be purged from users’ mailboxes until they have been backed up. A process has tried to purge an item that has not yet been backed up.

Action: You can allow purging of items that have not yet been backed up. See “[Environment Options: Cleanup](#)” in “[Users](#)” in the *GroupWise 7 Administration Guide*. See also “[GroupWise Time Stamp Utility](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

D069 Attempt to open invalid backup location

Source: GroupWise engine.

Explanation: The user attempted to open a backup location that did not contain a valid backup of a GroupWise post office or mailbox.

Possible Cause: The user is unsure of the backup location.

Action: Make sure users know where their backed-up messages have been restored. See “[Restoring Deleted Mailbox Items](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: The backup location path includes a directory name that has more than eight characters.

Action: Rename any long directory names to eight characters maximum, then make matching changes to the restore area information in ConsoleOne. See “[Setting Up a Restore Area](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: The restore area is in a location where the POA does not have the necessary rights to access it.

Action: If the restore area is on a different server from where the POA is running, provide a username and password for the POA to use to access the remote location. You can provide this information in ConsoleOne in the Remote File Server Settings box on the Post Office Settings page of the Post office object or in the POA startup file using the `/user` and `/password` switches.

Action: If the restore area is on the same server, add a trustee assignment to the restore area directory that provides the POA with object file system rights to the directory.

D06B LDAP failure detected

Source: GroupWise engine.

Explanation: GroupWise was unable to authenticate using LDAP.

Action: Make sure your LDAP server is functioning correctly.

D06E Lockout of older GroupWise clients being enforced

Source: GroupWise engine.

Explanation: The POA is not allowing GroupWise client users with older versions of the client software to access the post office.

Possible Cause: The administrator does not want older versions of the GroupWise client to access the post office. The client version can be controlled as described in “[Checking What GroupWise Clients Are in Use](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*

Action: GroupWise client users must update their client software before they can access the post office. See “[Updating Users' GroupWise Clients](#)” in “[Updating Your GroupWise 6.x System to Version 7](#)” in the “[GroupWise 7 Installation Guide](#)”.

D06F This GroupWise client doesn't match the user's license

Source: GroupWise engine.

Explanation: The GroupWise administrator has restricted client users to the WebAccess client and a user is attempting to access his or her mailbox using the Windows client.

Action: Explain to the user that he or she must use the WebAccess client.

Action: Allow the user to use the Windows client. See “[Setting Client Options](#)” in “[Users](#)” in the *GroupWise 7 Administration Guide*.

D071 LDAP authentication failed because the password has expired

Source: GroupWise engine.

Explanation: The GroupWise client was attempting to authenticate using LDAP, but the user’s LDAP password has expired.

Action: The user needs to contact the administrator of the LDAP server and get the password reset.

D072 Changing the LDAP password has been disabled

Source: GroupWise engine.

Explanation: A user tried to change his or her LDAP password from the GroupWise client but the administrator has disabled that capability for the user’s post office.

Action: Enable LDAP password changes in ConsoleOne. See “[Providing LDAP Authentication for GroupWise Users](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

Action: Show the user what application he or she needs to use to change the LDAP password.

D073 Attempting to log in trusted without SSL

Source: GroupWise engine.

Explanation: A trusted application tried to log in to the POA and was not successful because an SSL connection could not be established.

Possible Cause: The POA is not configured to support SSL connections.

Action: Enable SSL for the POA that the trusted application needs to log in to. See “[Enhancing Post Office Security with SSL Connections to the POA](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

D074 Invalid key for trusted application

Source: GroupWise engine.

Explanation: A trusted application tried to log in to the POA and was not successful because the key was invalid.

Possible Cause: The private key offered by the application did not match the private key the POA was configured to accept.

Action: Verify the private key that the POA is configured to accept. See “[Enhancing Post Office Security with SSL Connections to the POA](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

D075 Invalid IP address for trusted application

Source: GroupWise engine.

Explanation: A trusted application tried to log in to the POA and was not successful because the POA was configured for a specific IP address and the trusted application was not running there.

Possible Cause: The trusted application is running on a different server from where it was designed to run.

Action: Run the trusted application on the server with the IP address that the POA is expecting.

Possible Cause: The POA is configured with an incorrect IP address for the trusted application.

Action: In eDirectory, change the expected IP address to the IP address of the server where the trusted application is running. See “Trusted Applications” in “System” in the *GroupWise 7 Administration Guide*.

D076 Missing trusted application name

Source: GroupWise engine.

Explanation: A trusted application tried to log in to the POA and was not successful because no application name was provided.

Possible Cause: The trusted application is not providing an application name.

Action: Add an application name to the trusted application.

Possible Cause: The POA is configured with an incorrect application name for the trusted application.

Action: In eDirectory, change the expected application name to the application name that the trusted application is providing. See “Trusted Applications” in “System” in the *GroupWise 7 Administration Guide*.

D077 The problem file is being rebuilt

Source: GroupWise engine.

Explanation: The database you want to repair cannot be accessed.

Possible Cause: You are trying to perform database maintenance on a database that is currently being repaired.

Action: None. Your database maintenance request will be deferred until the build is completed.

D078 LDAP SSL key file not found

Source: GroupWise engine.

Explanation: The POA is configured to use SSL on its LDAP connection, but it cannot locate the SSL key file.

Possible Cause: The SSL key file has not been specified or has been specified incorrectly.

Action: Provide the full path to a valid SSL key file. See “Providing LDAP Authentication for GroupWise Users” in “Post Office Agent” in the *GroupWise 7 Administration Guide*. See also “Server Certificates and SSL Encryption” in “Security” in the *GroupWise 7 Administration Guide*.

D07F Unexpected error

Source: GroupWise engine.

Action: See “Dxxx Unexpected error” on page 128.

D101 User not found

Source: GroupWise engine; database interface.

Explanation: User not found.

Possible Cause: The GroupWise user ID is not found in the post office database during login.

Action: If using startup switches, check the /ph switch to make sure the path to the post office is correct.

Action: Start the GroupWise client using the /@u or /la startup option to specify the GroupWise user ID.

- Possible Cause: The user is not yet set up as a GroupWise user.
- Action: Set the user up as a GroupWise user. See “[Creating GroupWise Accounts](#)” in “[Users](#)” in the *GroupWise 7 Administration Guide*.
- Possible Cause: The user ID provided when the user was set up as a GroupWise user is not correct.
- Action: Check the GroupWise user information in ConsoleOne. Make sure the common name (CN) of the user is provided. No additional information is needed in the Network ID field.
- Possible Cause: User information has not replicated from the domain to the post office the user is trying to access.
- Action: Wait for replication to take place. Make sure the MTA is running. Check the current scan cycles of the MTA. See “[Adjusting MTA Polling of Input Queues in the Domain and Post Offices](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.
- Action: Synchronize the user manually. See “[Synchronizing Individual Users or Resources](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Possible Cause: The user is logging into a specific server, rather than into the tree, causing the network ID information not to match.
- Action: Log in to the tree rather than to a specific server.
- Possible Cause: If this error occurs when a user sends a message to a group, the group might contain user IDs that have been deleted from the system.
- Action: Recreate the group, selecting users from the Address Book to ensure they are valid GroupWise users.
- Possible Cause: If this error occurs when the user tries to delete users from the Subscribe to Notify window, the users might no longer exist in the GroupWise system.
- Action: Check the Address Book to see if the users are still valid. If they are not, repair the user database (`user:xx.db`). See “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Action: Run GWCheck on the post office database (`wphost.db`). See “[Standalone Database Maintenance Programs](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Possible Cause: The user was not found in the post office database (`wphost.db`) during the parsing of To: line or group.
- Action: Find the user in the To: line or Group. Either delete the user, or find the correct user ID in the Address Book.
- Possible Cause: If this error occurs for all users in a post office, the post office database might be damaged.
- Action: Rebuild the post office database (`wphost.db`). See “[Rebuilding Domain or Post Office Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Possible Cause: If this error occurs in systems where new users are added from multiple administrator workstations, preferences might be set differently on different administrator workstations.
- Action: On each workstation where users are added in ConsoleOne, click Tools > GroupWise System Operations > System Preferences. Make sure that the When Creating or Modifying Objects, For Network ID Use setting is the same on all workstations. If some workstations are set to Full Distinguished Name and some are set to Common Name, users will be set up differently depending on which workstation they were created from, causing problems when users access GroupWise.
- Possible Cause: If this error occurs only when using the GroupWise client in Remote mode, the user ID might be specified incorrectly under Remote Options.

Action: Check the user ID specified in the GroupWise client. Look up “Remote, specifying user and system information” in GroupWise client Help. Make sure the user ID specified is correct.

D102 Ambiguous user ID

Source: GroupWise engine; database interface.

Explanation: The GroupWise user ID is ambiguous.

Possible Cause: There is more than one user with same user ID in the same post office.

Action: Select the correct user ID in the pop-up list or select the user in the Address Book.

Possible Cause: If this error occurs when a user starts the GroupWise client, the user’s information in the post office database might not be correct.

Action: Check the information provided for the GroupWise user in ConsoleOne. Correct the information as needed. See “[Creating GroupWise Accounts for eDirectory Users](#)” in “[Users](#)” in the *GroupWise 7 Administration Guide*.

Action: Even if the information in the user record looks correct, make a change somewhere so the record is written out again.

Action: If the problem persists, rebuild the post office database (*wphost.db*). See “[Rebuilding Domain or Post Office Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

D103 Post office not found during login

Source: GroupWise engine; database interface.

Explanation: Post office not found.

Action: If using startup switches, check the */ph* switch to make sure the path to the post office is correct. If it is incorrect, enter the correct */ph* switch.

Action: If the path is correct, the post office was not found during parse of the To: line buffer. In that case, find the post office in To: line. Delete the post office qualifier, or select the user from the Address Book.

D104 Ambiguous post office

Source: GroupWise engine; database interface.

Explanation: The post office is ambiguous.

Possible Cause: There are multiple post offices in the same domain.

Action: The GroupWise client pops up a list so the user can correct the ambiguity manually. Select the correct user in the pop-up list, or use the Address Book to find the user.

D105 Directory Services data missing

Source: GroupWise engine; database interface.

Explanation: Directory Services error.

Possible Cause: Domain or post office not found during user or post office lookup.

Action: Check the */ph* switch when starting the GroupWise client to make sure it specifies the correct path to the user’s post office. Also check the */@u* switch to make sure it specifies a valid user in the specified post office. See “[Startup Switches for the GroupWise Client](#)” in “[Client](#)” in the *GroupWise 7 Administration Guide*.

D106 Database error

Source: GroupWise engine; database interface.

Explanation: General database error.

Possible Cause: The index is not synchronized with the data.

Action: Check and repair the database. See “[Maintaining Domain and Post Office Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

D107 Record not found

Source: GroupWise engine; database interface.

Explanation: Record not found.

Possible Cause: Relational integrity problem.

Possible Cause: The user database (*userxxx.db*) and/or message database (*msgnnn.db*) is damaged.

Action: Check and, if necessary, repair the database. See “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck. See “[Standalone Database Maintenance Programs](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: A user tried to read an attachment for which the corresponding file has already been deleted from the *offiles* directory in the post office.

Action: None, unless you want to restore the contents of the *offiles* directory from a backup.

D108 Unexpected error

Source: GroupWise engine; database interface.

Action: See “[Dxxx Unexpected error](#)” on page 128.

D109 Bad parameter

Source: GroupWise engine; database interface.

Explanation: A GroupWise program passed invalid information to another GroupWise program.

Possible Cause: The user’s mailbox contains a damaged message.

Action: Run a structural rebuild on the user database (*userxxx.db*) and message database (*msgnnn.db*). See “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: A delay in Directory replication is preventing the user from logging in to the GroupWise client.

Action: Start the client using the */@u-?* switch to bypass eDirectory authentication.

Action: Wait for eDirectory replication to complete.

Possible Cause: The user’s Client Options settings have been damaged.

Action: Reset the user’s Client Options setting back to the default. See “[Resetting Client Options to Default Settings](#)” in “[Client](#)” in the *GroupWise 7 Administration Guide*.

D10A Unexpected error

Source: GroupWise engine; database interface.

Action: See [“Dxxx Unexpected error” on page 128](#).

D10B Database needs to be repaired

Source: GroupWise engine; database interface.

Explanation: Database invalid or damaged.

Possible Cause: A record is no longer valid.

Action: Validate the database, then take the appropriate actions to either recover or rebuild the database. See [“Maintaining Domain and Post Office Databases”](#) and [“Maintaining User/Resource and Message Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck. See [“Standalone Database Maintenance Programs”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs when running the GroupWise client under Windows for Workgroups, the user login name might be incorrect.

Possible Cause: Check the user login name on the station where the error occurs. In Windows for Workgroups, click Main > Control Panel > Network > Login Name. The login name must match the user's GroupWise ID.

D10C Unexpected error

Source: GroupWise engine; database interface.

Action: See [“Dxxx Unexpected error” on page 128](#).

D10D Cannot open any more mailboxes

Source: GroupWise engine; database interface.

Explanation: Maximum databases open.

Possible Cause: The maximum number of databases that can be opened at one time has been exceeded. The maximum number is approximately 12.

Action: Shut down some databases by removing proxies. Look up [“proxy, deleting users from Access List”](#) in GroupWise client Help.

D110 Unexpected error

Source: GroupWise engine; database interface.

Action: See [“Dxxx Unexpected error” on page 128](#).

D113 Open database maximum exceeded

Source: GroupWise engine; database interface.

Explanation: The current operation has attempted to open more than the maximum number of databases allowed.

Possible Cause: You are proxied to too many users in direct mapped mode.

Action: Close some mailboxes that are currently proxied, then try the operation again. Look up [“proxy, deleting users from Access List”](#) in GroupWise client Help.

D114 Group not found

Source: GroupWise engine; database interface.

Explanation: Bad personal group or public distribution list.

Action: Check the spelling of the group name, or select the group in the Address Book.

D115 Database error

Source: GroupWise engine; database interface.

Explanation: Invalid database.

Possible Cause: Attempted to open an invalid database.

Action: Check and repair the database. See “[Maintaining Domain and Post Office Databases](#)” and “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck. See “[Standalone Database Maintenance Programs](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: This could represent a security breach of unauthorized, foreign packets being introduced into your GroupWise system.

Action: Check your system security.

D116 File not database

Source: GroupWise engine; database interface.

Explanation: Attempt to open a DOS file as a GroupWise database.

Possible Cause: The database is damaged.

Action: Check and, if necessary, repair the user database. See “[Maintaining Domain and Post Office Databases](#)” and “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck. See “[Standalone Database Maintenance Programs](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: If a user database cannot be repaired, you can rename the existing user database, then recreate it. See “[Re-creating a User Database](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: If the database cannot be recreated, you must restore it from backup. See “[Restoring GroupWise Databases from Backup](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

D117 GroupWise version too old

Source: GroupWise engine; database interface.

Explanation: Old program version.

Possible Cause: An attempt was made to open a database with an older version of GroupWise software. You are running an older version of the GroupWise client. Your post office has been updated to a newer version.

Action: Reinstall GroupWise with the version of the software that matches the database. See in “[Installing the GroupWise Windows and Cross-Platform Clients](#)” in the *GroupWise 7 Installation Guide*”.

D118 Database error

Source: GroupWise engine; database interface.

Explanation: Field not found.

Possible Cause: Unable to find the field in the database.

Action: Check and repair the database. See “[Maintaining Domain and Post Office Databases](#)” and “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck. See “[Standalone Database Maintenance Programs](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

D119 Unexpected error

Source: GroupWise engine; database interface.

Action: See “[Dxxx Unexpected error](#)” on page 128.

D11B Too many items in mailbox

Source: GroupWise engine; database interface.

Explanation: Too many records.

Possible Cause: There are more than 5,000 items in your mailbox. Only the first 5,000 items are displayed. When you delete messages, additional items are displayed.

Action: Have users clean out their mailboxes. You might want to run a statistics check on the mailboxes. “[Gathering Mailbox Statistics](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: Users could move items to different folders.

Action: Users could archive items. See “[archive, items](#)” in GroupWise client Help.

D11C Cannot use group name

Source: GroupWise engine; database interface.

Explanation: Groups cannot be listed as users here.

Possible Cause: A group name was used where a user name was expected. For example, the startup option `/@u-group_name` was used, or a group name was used in a domain where there is no entry in the Address Book for this group.

Action: Check your Address Book for correct addressing syntax. If the syntax is correct, you might want to add the group to the Address Book.

Possible Cause: The user has specified a distribution list in another post office that has visibility set to none.

Action: Change the visibility of the distribution list so that users in other post offices can use it. For information about visibility, see “[Creating and Managing Distribution Lists](#)” in “[Distribution Lists, Groups, and Organizational Roles](#)” in the *GroupWise 7 Administration Guide*.

D11D GroupWise version newer than database

Source: GroupWise engine; database interface.

Explanation: New program version.

Possible Cause: The GroupWise client has been installed on a workstation where the GroupWise demo that comes with the PerfectOffice Suite 3.0 had already been installed. The GroupWise demo creates a post office database (**wphost.db**) on the local workstation, which can interfere with the functioning of the full GroupWise client.

Action: Search the workstation for a local wphost.db file. If found, rename or delete it.

Possible Cause: The GroupWise client and agents were updated, but ConsoleOne was not. As a result, the database dictionary (*.dc) files do not get updated.

Action: Copy the *.dc files from the **domain** and **po** subdirectories of the new distribution media to the domain and post office directories of your GroupWise system.

Possible Cause: The version of GroupWise you are running is newer than the database. The software cannot do an auto-upgrade on the older database.

D124 Access to user denied

Source: GroupWise engine; database interface.

Explanation: Access rights failure. A required field was not found.

Possible Cause: Moving a resource causes the resource owner to lose access to the resource.

Action: In ConsoleOne, browse to and select the Resource object, then click Tools > GroupWise Utilities > Mailbox/Library Maintenance. Select Reset Client Options in the Action drop-down list.

D201 Unexpected error

Source: GroupWise engine; mail/calendar import and print services.

Action: See **“Dxxx Unexpected error” on page 128**.

D202 General printing error

Source: GroupWise engine; mail/calendar import and print services.

Explanation: You have attempted to print an item that is missing information.

Possible Cause: The user workstation is missing its temporary directory, or there is insufficient disk space available to create the temporary files needed to print the item.

Action: Check for the existence of the temporary directory on the user workstation.

Action: Check for available disk space.

Possible Cause: The link to the item to print has been damaged.

Action: Check and, if necessary, repair the message database (**msgnnn.db**). See **“Maintaining User/Resource and Message Databases”** in **“Databases”** in the *GroupWise 7 Administration Guide*.

D506 Security violation

Source: GroupWise engine; administration services.

Explanation: No authentication.

Possible Cause: An administration command was received that did not contain the proper authentication. This command might have originated outside the system, or the administration database (**wpdomain.db** or **wphost.db**) at the destination domain/post office has been replaced with an invalid version.

- Action: Monitor and log the source of the command. Rebuild the domain or post office database. See *“Rebuilding Domain or Post Office Databases”* in *“Databases”* in the *GroupWise 7 Administration Guide*.
- Possible Cause: If this error occurs after a configuration change (for example, after changing which domain is the primary domain of your GroupWise system), the configuration change might not have replicated throughout the system in time to support a following change (for example, adding a user).
- Action: Wait for replication to complete, then synchronize the object that caused the error. See *“Synchronizing Database Information”* in *“Databases”* in the *GroupWise 7 Administration Guide*.
- Action: If you do not want to wait for replication to complete, you can rebuild the secondary domain database. See *“Rebuilding Domain or Post Office Databases”* in *“Databases”* in the *GroupWise 7 Administration Guide*.
- Possible Cause: If this error occurs when synchronizing domains or post offices, the databases might be damaged.
- Action: Rebuild the databases, then synchronize the databases.

D507 Administrator record not found in database

- Source: GroupWise engine; administration services.
- Explanation: No administrator record found in database.
- Possible Cause: An agent has attempted to send a message to the defined administrator; however, no administrator record was found in the database.
- Action: To receive these messages, define an administrator for the domain. See *“Notifying the Domain Administrator”* in *“Message Transfer Agent”* in the *GroupWise 7 Administration Guide*.

D508 Transaction failed

- Source: GroupWise engine; administration services.
- Explanation: The transaction failed.
- Possible Cause: The database was locked by another process and could not be updated.
- Action: None. The message will be retried automatically.
- Possible Cause: One or more of the GroupWise databases might have an invalid owner or no owner.
- Action: For the locations of GroupWise databases in domains and post offices, see *“Domain Directory”* and *“Post Office Directory”* in *“Directory Structure Diagrams”* in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. Check the ownership of the GroupWise databases. If necessary, change the ownership to a valid user such as the system administrator.
- Possible Cause: The database has been damaged.
- Action: If the ownership on the problem database is correct or you are unable to reset it, repair the database. See *“Maintaining Domain and Post Office Databases”* and *“Maintaining User/Resource and Message Databases”* in *“Databases”* in the *GroupWise 7 Administration Guide*.
- Action: Run GWCheck. See *“Standalone Database Maintenance Programs”* in *“Databases”* in the *GroupWise 7 Administration Guide*.

D701 Unexpected error

- Source: GroupWise engine; directory services access.
- Action: See *“Dxxx Unexpected error”* on page 128.

D704 Unexpected error

Source: GroupWise engine; directory services access.

Action: See [“Dxxx Unexpected error” on page 128.](#)

D705 Unexpected error

Source: GroupWise engine; directory services access.

Action: See [“Dxxx Unexpected error” on page 128.](#)

D706 Unexpected error

Source: GroupWise engine; directory services access.

Action: See [“Dxxx Unexpected error” on page 128.](#)

D707 Unexpected error

Source: GroupWise engine; directory services access.

Action: See [“Dxxx Unexpected error” on page 128.](#)

D708 Directory entry record not found

Source: GroupWise engine; directory services access.

Explanation: Requested record not found.

Possible Cause: The directory entry record was not found. This can occur if multiple processes are updating the database at the same time.

Action: Cancel the current operation, refresh the listing, then select again from the available items.

Possible Cause: The database is damaged.

Action: Rebuild the problem database. See [“Maintaining Domain and Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

Possible Cause: The path to the software distribution directory might be incorrect.

Action: Make sure the post office where the problem is occurring has a software distribution directory assigned. See [“Editing Post Office Properties”](#) in [“Post Offices”](#) in the *GroupWise 7 Administration Guide*.

Action: Check the current path to the software distribution directory. See [“Software Directory Management”](#) in [“System”](#) in the *GroupWise 7 Administration Guide*. Correct the path as needed. Make sure the specified software distribution directory actually exists.

D709 Unexpected error

Source: GroupWise engine; directory services access.

Action: See [“Dxxx Unexpected error” on page 128.](#)

D70A Memory error

Source: GroupWise engine; directory services access.

Explanation: Memory error.

Possible Cause: Unable to lock or allocate memory.

Action: The GroupWise client user should exit and restart GroupWise.

D70B Database inconsistency detected

Source: GroupWise engine; directory services access.

Explanation: Database invalid or damaged.

Possible Cause: The directory services database (**wpdomain.db** or **wphost.db**) is inconsistent. The identifier used to identify which domain or post office owns this database has been lost.

Action: If the database is a primary domain, restore it from backup; otherwise, rebuild the database. See **“Rebuilding Domain or Post Office Databases”** in **“Databases”** in the *GroupWise 7 Administration Guide*.

D70D Unexpected error

Source: GroupWise engine; directory services access.

Action: See **“Dxxx Unexpected error”** on page 128.

D70E Duplicate entry in database

Source: GroupWise engine; directory services access.

Explanation: Duplicate entry found in database.

Possible Cause: You provided a non-unique entry in a field that requires a unique entry.

Action: Provide a new, unique value in the field.

Possible Cause: The database is damaged.

Action: Check and, if necessary, repair the database. See **“Maintaining Domain and Post Office Databases”** and **“Maintaining User/Resource and Message Databases”** in **“Databases”** in the *GroupWise 7 Administration Guide*.

D70F Unexpected error

Source: GroupWise engine; directory services access.

Action: See **“Dxxx Unexpected error”** on page 128.

D710 Incompatible platform

Source: GroupWise engine; directory services access.

Explanation: Requested platform path not found.

Possible Cause: In a multiple-platform environment, a path was requested for a given platform but none was found.

Action: This is not an error. It is a notification by the program of the return value.

Possible Cause: If this error occurs when the POA is trying to start, a path to a document storage area might be incorrect.

Action: Check the location and existence of any document storage areas for libraries associated with the post office. To list the available libraries, see **“Editing Post Office Properties”** in **“Post Offices”** in the *GroupWise 7 Administration Guide*.

To check the path to a document storage area, see **“Managing Document Storage Areas”** in

“Libraries and Documents” in the *GroupWise 7 Administration Guide*. Correct any incorrect path, then try to start the POA.

D712 Post office currently disabled

Source: GroupWise engine; directory services access.

Explanation: Post office is disabled.

Possible Cause: The system administrator has disabled the post office.

Action: This is not an error. It is a notification by the program of the return value. To enable the post office, deselect Disable Logins in the post office Identification page in ConsoleOne. See “Disabling a Post Office” in “Post Offices” in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs when the Disable Logins option is not selected, the flag might be set improperly on the post office database.

Action: After making sure the Disable Logins option is not selected, stop and restart the POA. See “Starting the POA” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

Action: Rebuild the post office database (*wphost.db*). See “Rebuilding Domain or Post Office Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

D713 Database dictionary not found

Source: GroupWise engine; directory services access.

Explanation: Dictionary not found.

Possible Cause: A database create request was made and the corresponding database dictionary file was not found.

Action: Make sure the *ngwguard.dc* file exists in the post office directory. If it does not, copy it from the *po* subdirectory of your software distribution directory. For the specific locations of this file, see “Post Office Directory” and “Software Distribution Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

D714 User database temporarily disabled

Source: GroupWise engine; directory services access.

Explanation: The administrator has temporarily disabled GroupWise login for a specific user.

Possible Cause: The user is being moved from GroupWise 5.x to 7.

Action: Wait for the move to be completed.

Action: If the problem persists, rebuild the user database (*userxxx.db*). See “Maintaining User/Resource and Message Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

D715 User has failed in too many login attempts, login disabled

Source: GroupWise engine; directory services access.

Explanation: The Intruder Lockout feature is preventing the user from logging in.

Possible Cause: A valid user is using an incorrect password or an intruder is attempting to gain access without having a valid password.

Action: Try again after the lockout period has passed. The default lockout period is 30 minutes.

Action: Manually enable the user's account. See [“Disabling and Enabling GroupWise Accounts”](#) in [“Users”](#) in the *GroupWise 7 Administration Guide*.

D716 The System Address Book needs to be refreshed

Source: GroupWise engine; directory services access.

Explanation: The Address Book updates that the Remote or Caching client is expecting to find in the post office database (`wphost.db`) are not available. For more information, see [“Address Book Delta Sync”](#) in [“What's New in GroupWise 7”](#) in the *“GroupWise 7 Installation Guide”*.

Possible Cause: The delta records that the client needs have already been removed from the post office database as part of scheduled maintenance to control the size of the post office database. You can control how often delta records are removed, as described in [“Controlling Address Book Synchronization for Remote Client Users”](#) in [“System”](#) in the *GroupWise 7 Administration Guide*.

Possible Cause: The post office database has been rebuilt, as described in [“Rebuilding Domain or Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*. The rebuild process removes all delta sync records.

Action: Manually download the complete Address Book from the post office. In the GroupWise Windows client, open the Address Book, then click View > Retrieve System Address Book.

D901 Unexpected error

Source: GroupWise engine; messaging services.

Action: See [“Dxxx Unexpected error”](#) on page 128.

D902 Unexpected error

Source: GroupWise engine; messaging services.

Action: See [“Dxxx Unexpected error”](#) on page 128.

D904 Unexpected error

Source: GroupWise engine; messaging services.

Action: See [“Dxxx Unexpected error”](#) on page 128.

D90A Unexpected error

Source: GroupWise engine; messaging services.

Action: See [“Dxxx Unexpected error”](#) on page 128.

D90B Unexpected error

Source: GroupWise engine; messaging services.

Action: See [“Dxxx Unexpected error”](#) on page 128.

D912 Cannot process message file

Source: GroupWise engine; messaging services.

Explanation: The message file has been opened too many times. It has been moved to the problem directory.

Possible Cause: The POA might be attempting to process a damaged message file and is unable to move it to the **problem** directory.

Action: Check the priority subdirectories of the `\wpcout\ofs` directory. Check the POA log file to determine the offending message file. See “Using POA Log Files” in “Post Office Agent” in the *GroupWise 7 Administration Guide*. Delete the offending message file so that subsequent messages can be processed.

DA0C Incorrect DLL version

Source: GroupWise engine; Post Office Agent.

Explanation: Wrong DLL.

Possible Cause: The DLL being used with the POA executable is either an older or a newer version. The DLL cannot be used with the executable.

Action: Make sure the POA executable is the same version as the POA DLL. For a list of agent files, see “Windows Installation Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

DA0D Cannot create directory in post office

Source: GroupWise engine; Post Office Agent.

Explanation: Post office directory structure problem.

Possible Cause: A required post office directory could not be created or one or more database dictionary files is missing.

Action: Make sure all of the database dictionary files are present. For file locations, see “Post Office Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

Action: Make sure the POA process has the required network rights. See “Creating a NetWare Account for Agent Access (Optional)” in “Installing GroupWise Agents” in the “GroupWise 7 Installation Guide”.

Possible Cause: The post office has been created in the root directory of a NetWare volume.

Action: Move all post office directories and files into a subdirectory off the root. See “Post Office Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. Adjust the path to the post office in the post office Identification page in ConsoleOne.

DA0E Path to post office database not specified

Source: GroupWise engine; Post Office Agent.

Explanation: No post office path.

Possible Cause: The path to the post office database (`wphost.db`) was not specified.

Action: Use the `/home` startup switch to specify the location of the post office database. See “Using POA Startup Switches” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

DA10 Cannot read post office configuration information

Source: GroupWise engine; Post Office Agent.

Explanation: Error reading post office configuration information.

Possible Cause: An error was detected while reading POA configuration information from the post office database (**wphost.db**). The post office database might be in an inconsistent state.

Action: Start the POA with **/noconfig**, and validate the post office database. See “**Maintaining Domain and Post Office Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

DA12 Invalid application configuration name

Source: GroupWise engine; Post Office Agent.

Explanation: Invalid application name.

Possible Cause: The eDirectory distinguished name (DN) specified on the command line when starting the POA was invalid. The DN might be misspelled.

Action: Specify a valid DN. A list of valid DNs for a given post office can be obtained by failing to specify one on the POA command line (with the **/name** switch) when the system is configured so that one is required. You can then choose one from the list. A DN must be specified in a system that has been configured to run more than one POA process for a single post office. In that case, the DN is used by the POA to find configuration information for a specific POA process (such as TCP/IP address, port, and other configuration information).

DA13 /name switch required

Source: GroupWise engine; Post Office Agent.

Explanation: Ambiguous application name.

Possible Cause: An eDirectory distinguished name (DN) was not specified where one is required. Your system is configured in a way that requires the **/name** switch to be specified when starting the POA.

Possible Cause: This post office has been configured to run more than one POA process for it. The DN is used by the POA to identify the configuration information and options that it should use when running.

Action: The **/name** switch should be used in conjunction with one of the DNs specified in the error message.

DA17 /user and /password switches required for this configuration

Source: GroupWise engine; Post Office Agent.

Explanation: The **/user** and **/password** switches are required when the POA must log into a remote server.

Possible Cause: The POA needs to log in to a remote server where a document storage area is located, but it does not have the necessary user and password information to log in with.

Action: See “**Using POA Startup Switches**” and “**Installing and Starting the POA**” in “**Post Office Agent**” in the *GroupWise 7 Administration Guide*.

Action: In ConsoleOne, specify the login information in the Remote File Server Settings box on the Post Office Settings page of the Post Office object.

Possible Cause: You have renamed the server where a document storage area is located. The POA can no longer access the original document storage area location, so the POA cannot start.

Action: First, provide the new location of the document storage area. See “**Moving a Document Storage Area**” in “**Libraries and Documents**” in the *GroupWise 7 Administration Guide*.

Next, start the POA using the **/noconfig**, **/user**, and **/password** switches so the POA can start and process the administrative message containing the new storage location without accessing the old storage location. Finally, exit, then restart the POA with its typical configuration.

DB01 Operation cancelled

Source: GroupWise engine; administration engine.

Explanation: Operation cancelled.

Possible Cause: Operation cancelled by user.

Action: None.

DB02 Database access error

Source: GroupWise engine; administration engine.

Explanation: Database access error.

Possible Cause: Cannot complete the requested operation because the database is being updated.

Action: Retry the operation later. If you still cannot access the database, check file activity using your network administration utilities.

Action: Rebuild the database. See **“Maintaining Domain and Post Office Databases”** in **“Databases”** in the *GroupWise 7 Administration Guide*.

DB03 Operation pending; cannot modify

Source: GroupWise engine; administration engine.

Explanation: Unsafe record modification.

Possible Cause: This record has a pending operation and cannot be modified. A remote operation has been requested for this record.

Action: Wait for the MTA or POA to complete the pending operation, or undo the operation. See **“Pending Operations”** in **“System”** in the *GroupWise 7 Administration Guide*.

DB04 Owner not valid user

Source: GroupWise engine; administration engine.

Explanation: Invalid owner.

Possible Cause: The owner you specified is not a valid user in the same post office as the resource.

Action: Select an owner for the resource from among the users in the same post office as the resource. See **“Changing a Resource's Owner”** in **“Resources”** in the *GroupWise 7 Administration Guide*.

Action: Create a new user in the post office to function as the owner of the resource. See **“Creating GroupWise Accounts”** in **“Users”** in the *GroupWise 7 Administration Guide*.

DB05 Invalid path

Source: GroupWise engine; administration engine.

Explanation: Invalid path specified.

Possible Cause: The specified path exists; however, it is not a directory.

Action: Enter a new path, or remove the invalid path.

DB08 Non-unique name

Source: GroupWise engine; administration engine.

Explanation: Non-unique name.

Possible Cause: The specified name (*object.po.domain*) conflicts with an existing user, resource, group, or nickname.

Action: Specify a new, unique name.

DB09 User owns resource

Source: GroupWise engine; administration engine.

Explanation: User owns a resource.

Possible Cause: The specified user cannot be deleted or moved because he or she owns a resource.

Action: Remove the resource. See “[Deleting a Resource](#)” in “[Resources](#)” in the *GroupWise 7 Administration Guide*.

Action: Reassign the resource to another owner. See “[Changing a Resource's Owner](#)” in “[Resources](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: If this error occurs after removing resources from a user to be deleted or moved, the change might not yet have replicated through the system.

Action: Wait for replication to occur or manually synchronize the resource(s) and user. See “[Synchronizing Database Information](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: Rebuild the post office database (*wphost.db*). See “[Rebuilding Domain or Post Office Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

DB0A Record not found

Source: GroupWise engine; administration engine.

Explanation: Record not found.

Possible Cause: Cannot find a record that was previously in the database. The record might have been deleted.

Action: Check Pending Operations to see if the command is still awaiting execution. See “[Pending Operations](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*.

Action: Retry the command.

Action: Make sure the record was replicated throughout the system. See “[Synchronizing Database Information](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

DB0B Required field empty

Source: GroupWise engine; administration engine.

Explanation: Required field empty.

Possible Cause: A required field has no value.

Action: Supply a value for all required fields.

DB0C Cannot close database

Source: GroupWise engine; administration engine.

Explanation: Error closing database.

Possible Cause: An error was encountered while attempting to close the database.

Action: Check the network connection to the database location.

DB0E Insufficient memory to initialize database

Source: GroupWise engine; administration engine.

Explanation: Database initialization failure.

Possible Cause: The database failed to initialize because of insufficient memory. ConsoleOne requires at least 500 KB of available RAM.

Action: Check the amount of available memory and reconfigure your system if necessary.

DB0F Domain not found

Source: GroupWise engine; administration engine.

Explanation: Domain not found.

Possible Cause: Cannot find the specified domain.

Action: Make sure that the domain exists and that the domain name is correct. In ConsoleOne, browse to and right-click the Domain object, then click Properties.

Possible Cause: If this error occurs from the POA, the post office database (**wphost.db**) might be damaged so that valid domain information is not available.

Action: Check and, if necessary, repair the database. See [“Maintaining Domain and Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

DB10 Post office not found

Source: GroupWise engine; administration engine.

Explanation: Post office not found.

Possible Cause: Cannot find the specified post office.

Action: Make sure that the post office exists and that the post office name is correct. In ConsoleOne, browse to and right-click the Post Office object, then click Properties.

DB11 Unexpected error

Source: GroupWise engine; administration engine.

Action: See [“Dxxx Unexpected error”](#) on page 128.

DB12 Maximum number of objects per post office reached

Source: GroupWise engine; administration engine.

Explanation: No more file ID combinations exist for the post office.

Possible Cause: The maximum user limit has been reached for this post office. The maximum number of FID combinations is approximately 46,000 per post office.

Action: Delete obsolete users. See [“Removing GroupWise Accounts”](#) in [“Users”](#) in the *GroupWise 7 Administration Guide*.

Action: Remove unneeded resources. See [“Deleting a Resource”](#) in [“Resources”](#) in the *GroupWise 7 Administration Guide*.

Action: Create additional post offices. See [“Creating a New Post Office”](#) in [“Post Offices”](#) in the *GroupWise 7 Administration Guide*.

DB17 Domain already exists in specified directory

Source: GroupWise engine; administration engine.

Explanation: Directory exists.

Possible Cause: A domain already exists in the specified directory.

Action: Specify a new domain directory or remove the existing domain. See [“Deleting a Domain”](#) in [“Domains”](#) in the *GroupWise 7 Administration Guide*.

DB19 Local post office not found

Source: GroupWise engine; administration engine.

Explanation: No local post office record found.

Possible Cause: GroupWise was unable to find a local post office. The post office database (`wphost.db`) might have been damaged.

Action: Validate the post office database and rebuild if necessary. See [“Maintaining Domain and Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

DB1A Insufficient administrative rights to perform operation

Source: GroupWise engine; administration engine.

Explanation: No administrative rights to perform action.

Possible Cause: The current domain has no administrative rights to perform the specified action for the selected record.

Action: Connect to the GroupWise system that owns this record. See [“Connecting to a Domain”](#) in [“Domains”](#) in the *GroupWise 7 Administration Guide*.

DB1B Message Transfer Agent not installed

Source: GroupWise engine; administration engine.

Explanation: The MTA is not installed.

Possible Cause: The MTA is not installed, or the MTA record is missing from the database.

Action: Set up the MTA. See [“Installing GroupWise Agents”](#) in the *“GroupWise 7 Installation Guide”*.

DB1C Invalid object name

Source: GroupWise engine; administration engine.

Explanation: Invalid object.

Possible Cause: An invalid object name was specified for an administrator, group name, or other object.

Action: Make sure the specified object ID is correct.

DB1D Cannot delete post office

Source: GroupWise engine; administration engine.

Explanation: Error deleting post office.

Possible Cause: You do not have sufficient rights to perform the operation.

Action: Make sure you have rights to delete files and directories by checking rights for file and directory removal.

Possible Cause: The post office directory or files in that directory are in use by another user.

Action: Check the open/lock activity on files.

DB1F Cannot delete current domain

Source: GroupWise engine; administration engine.

Explanation: Error deleting current domain.

Possible Cause: The attempt to delete the current domain failed.

Action: Connect to the primary domain. See [“Connecting to a Domain”](#) in [“Domains”](#) in the *GroupWise 7 Administration Guide*. Then delete the secondary domain from the primary domain. See [“Deleting a Domain”](#) in [“Domains”](#) in the *GroupWise 7 Administration Guide*.

Action: If the current domain is the primary domain, you cannot delete it unless you delete all secondary domains first (meaning that you want to delete your entire GroupWise system) or you designate a different domain as the primary domain. See [“Converting a Secondary Domain to a Primary Domain”](#) in [“Domains”](#) in the *GroupWise 7 Administration Guide*.

DB20 Unexpected error

Source: GroupWise engine; administration engine.

Action: See [“Dxxx Unexpected error”](#) on page 128.

DB21 Database inconsistency detected

Source: GroupWise engine; administration engine.

Explanation: Database invalid or damaged.

Possible Cause: The database is invalid.

Action: Rebuild the database. See [“Maintaining Domain and Post Office Databases”](#) and [“Maintaining User/Resource and Message Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

DB23 Password incorrect

Source: GroupWise engine; administration engine.

Explanation: Invalid password.

Action: Enter the correct password.

DB24 Invalid link

Source: GroupWise engine; administration engine.

Explanation: A link between domains is invalid.

Action: Select a valid link type and link protocol for the domain link. See [“Editing a Domain Link”](#) in [“Domains”](#) in the *GroupWise 7 Administration Guide*.

DB25 Duplicate domain name

Source: GroupWise engine; administration engine.

Explanation: Duplicate domain name.

Possible Cause: The name of the external domain being merged conflicts with the name of an existing local domain. The names of all primary and secondary domains must be unique in both systems when merging systems.

Action: Remove one of the duplicate domains. See “[Deleting a Domain](#)” in “[Domains](#)” in the *GroupWise 7 Administration Guide*.

DB26 Secondary domains exist

Source: GroupWise engine; administration engine.

Explanation: Secondary domains exist.

Possible Cause: Multiple local domains were found in an external domain being merged.

Action: Release all secondary domains from the domain to be merged, or release the domain to be merged from its owning primary domain. See “[Merging with GroupWise 5.x, 6.x, and 7 Systems](#)” in the *GroupWise 7 Multi-System Administration Guide*.

DB29 Invalid character

Source: GroupWise engine; administration engine.

Explanation: Invalid character.

Possible Cause: Invalid character in a domain, post office, or object name.

Action: Check the contents of the name strings for invalid characters. Do not use any of the following characters in GroupWise object names:

- Space
- Period .
- At-sign @
- Asterisk (*)
- Comma ,
- Colon :
- Double quote
- Parentheses ()
- Braces { }
- ASCII characters 0-13

Possible Cause: If this error occurs when trying to synchronize users through the GroupWise Gateway to Lotus Notes*, users might be defined under the gateway, rather than in a foreign domain.

Action: Define Lotus Notes users in a foreign domain. See “[Connecting to Non-GroupWise Messaging Systems](#)” in the *GroupWise 7 Multi-System Administration Guide*.

DB2A Invalid name

Source: GroupWise engine; administration engine.

Explanation: Invalid name.

Possible Cause: An invalid or restricted name has been specified.

Action: Enter a valid name.

DB2B Non-unique entry

Source: GroupWise engine; administration engine.

Explanation: Non-unique entry.

Possible Cause: A new entry conflicts with an existing entry in an index that must be unique. This can occur with a user's network ID.

Action: Check the network ID for uniqueness on the post office where the user will reside.

DB2C Invalid post office database

Source: GroupWise engine; administration engine.

Explanation: Invalid post office database (**wphost.db**).

Action: Rebuild the post office database. See [“Rebuilding Domain or Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

DB2D Platform error

Source: GroupWise engine; administration engine.

Explanation: Wrong platform.

Possible Cause: No valid path could be found for the current platform type.

Action: Enter a path for the current platform.

DB2E Link record not found

Source: GroupWise engine; administration engine.

Explanation: No link record exists.

Possible Cause: No link record has been defined between an external domain to be merged and any local domain.

Action: Define a link record between an external domain to be merged and any local domain. See [“Merging with GroupWise 5.x, 6.x, and 7 Systems”](#) in the *GroupWise 7 Multi-System Administration Guide*.

DB2F Correct database type not found

Source: GroupWise engine; administration engine.

Explanation: No database exists.

Possible Cause: Specified database type does not exist in the specified directory.

Action: Check the domain path. In ConsoleOne, browse to and right-click the Domain object, then click Properties.

Action: Check the setting of the **/home** switch in the MTA startup file. See [“Using MTA Startup Switches”](#) in [“Message Transfer Agent”](#) in the *GroupWise 7 Administration Guide*.

DB30 Gateway directory not found

Source: GroupWise engine; administration engine.

Explanation: Gateway directory does not exist.

Action: Check the specified gateway directory path and make sure the requested gateway is installed. For a list of gateways, see [GroupWise Gateways \(http://www.novell.com/documentation/gwgateways\)](http://www.novell.com/documentation/gwgateways).

DB31 Required field missing or empty

Source: GroupWise engine; administration engine.

Explanation: A required field is missing or empty.

Action: Provide a value for the required field(s).

DB32 Required field missing

Source: GroupWise engine; administration engine.

Explanation: A required field is missing.

Action: Check the record for a missing required field.

DB33 Cannot open all post offices

Source: GroupWise engine; administration engine.

Explanation: Unable to open all post offices.

Possible Cause: There are more post offices defined than the operating system file handles allow.

Action: All directory synchronized commands will be performed through the MTA for the closed post offices.

Possible Cause: The link to the post office has been lost.

Action: Reestablish the link to the post office. See “[Strategies for Message Delivery Problems](#)” in *GroupWise 7 Troubleshooting 2: Solutions to Common Problems*.

DB34 Time zone definition not found

Source: GroupWise engine; administration engine.

Explanation: No time zone defined.

Possible Cause: Unable to find a time zone definition for the current domain or post office.

Action: Select a time zone in the Identification page for the current domain or post office in ConsoleOne. See “[Time Zones](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*

DB35 No pending operation for record

Source: GroupWise engine; administration engine.

Explanation: No pending operation for record.

Possible Cause: The pending operation has been completed.

Action: Refresh the list of pending operations. See “[Pending Operations](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*.

DB37 Cannot delete current domain

Source: GroupWise engine; administration engine.

Explanation: Cannot delete the current domain.

Action: Connect to the primary domain. See “[Connecting to a Domain](#)” in “[Domains](#)” in the *GroupWise 7 Administration Guide*. Then delete the secondary domain from the primary domain. See “[Deleting a Domain](#)” in “[Domains](#)” in the *GroupWise 7 Administration Guide*.

Action: If the current domain is the primary domain, you cannot delete it unless you delete all secondary domains first (meaning that you want to delete your entire GroupWise system) or you designate a different domain as the primary domain. See “[Converting a Secondary Domain to a Primary Domain](#)” in “[Domains](#)” in the *GroupWise 7 Administration Guide*.

DB38 Cannot delete domain that has post offices

Source: GroupWise engine; administration engine.

Explanation: Post offices exist for this domain.

Possible Cause: An attempt was made to delete a domain that has post offices assigned to it.

Action: Move the post offices to another domain. See “[Moving a Post Office](#)” in “[Post Offices](#)” in the *GroupWise 7 Administration Guide*. Then delete the domain after it is empty. See “[Deleting a Domain](#)” in “[Domains](#)” in the *GroupWise 7 Administration Guide*.

Action: Delete the post offices. See “[Deleting a Post Office](#)” in “[Post Offices](#)” in the *GroupWise 7 Administration Guide*. Then delete the domain after it is empty. See “[Deleting a Domain](#)” in “[Domains](#)” in the *GroupWise 7 Administration Guide*.

DB39 Domain database not found

Source: GroupWise engine; administration engine.

Explanation: Database is not available. No domain database ([wpdomain.db](#)) was found; however, a [recover.ddb](#) file was found.

Possible Cause: The database is currently being rebuilt.

Action: Allow the rebuild operation to finish.

Possible Cause: A database rebuild failed.

Action: Rename [recover.ddb](#) to [wpdomain.db](#) in the domain directory, then rerun the rebuild. See “[Maintaining Domain and Post Office Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

DB3A Cannot delete domain that has links

Source: GroupWise engine; administration engine.

Explanation: Domain has indirect links.

Possible Cause: Cannot delete the domain because it is used in indirect routing.

Action: Reconfigure domain links before deleting the domain. See “[Editing a Domain Link](#)” in “[Domains](#)” in the *GroupWise 7 Administration Guide*.

DB3B Remote management message sent

Source: GroupWise engine; administration engine.

Explanation: Remote management message sent.

Action: None. This is not an error. It is a notification by the program that the operation to be performed has been sent to the parent domain.

DB3C Domain database in use

Source: GroupWise engine; administration engine.

Explanation: Exclusive open error.

Possible Cause: An exclusive open for a domain to be merged or released failed because the domain is already in use.

Action: Have all administrators exit the domain database (**wppdomain.db**) before running the merge or release.

Action: Stop the MTA in the domain to be merged or released.

DB3D Database sorting language changed

Source: GroupWise engine; administration engine.

Explanation: Database language has changed.

Action: Rebuild the database. See **“Rebuilding Domain or Post Office Databases”** in **“Databases”** in the *GroupWise 7 Administration Guide*.

DB3F Cannot delete required field

Source: GroupWise engine; administration engine.

Explanation: Cannot remove a required field.

Action: You must supply valid data for all required fields.

DB40 Cannot delete gateway used in link

Source: GroupWise engine; administration engine.

Explanation: Gateway links exist.

Possible Cause: The gateway you are attempting to delete is used in a gateway link.

Action: Reconfigure the links before deleting the gateway. See **“Editing a Domain Link”** in **“Domains”** in the *GroupWise 7 Administration Guide*.

DB41 Database does not match domain or post office

Source: GroupWise engine; administration engine.

Explanation: Incorrect database path

Possible Cause: The database found at the specified path does not match the specified domain/post office name.

Action: Enter the correct path.

DB42 Information lost during recovery

Source: GroupWise engine; administration engine.

Explanation: Information lost.

Possible Cause: Some records were lost during the recover operation.

Action: You might want to rebuild the database at this time. See [“Rebuilding Domain or Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

DB43 Maximum number of open post offices reached

Source: GroupWise engine; administration engine.

Explanation: Maximum number of post offices are opened.

Possible Cause: You have tried to open too many post offices.

Action: Close one or more post offices. See [“Disabling a Post Office”](#) in [“Post Offices”](#) in the *GroupWise 7 Administration Guide*.

DB45 GroupWise system not found

Source: GroupWise engine; administration engine.

Explanation: No system found.

Action: Verify the path to the domain database ([wpdomain.db](#)).

Action: Make sure you are logged in to the server where the GroupWise system resides.

DB46 Path too long

Source: GroupWise engine; administration engine.

Explanation: Path too long.

Action: You can map a drive to a lower level.

DB47 Invalid area

Source: GroupWise engine; administration engine.

Explanation: Invalid BLOB area specified.

Possible Cause: ConsoleOne is unable to copy the GroupWise client view files from the software distribution directory into the post office directory structure.

Action: Make sure the software distribution directory has been created in your GroupWise system. See [“Software Directory Management”](#) in [“System”](#) in the *GroupWise 7 Administration Guide* and [“Software Distribution Directory”](#) in [“Directory Structure Diagrams”](#) in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

DB48 Cannot delete domain that has links

Source: GroupWise engine; administration engine.

Explanation: System link exists.

Possible Cause: You are trying to delete a domain that is specified as the link domain for an external system.

Action: Remove the external system or specify a different external domain as the link for the system. See [“Using Direct Links”](#) in [“Connecting to GroupWise 5.x, 6.x, and 7 Systems”](#) in the *GroupWise 7 Multi-System Administration Guide*.

Possible Cause: You are trying to delete a domain that is set up for external system synchronization.

Action: Remove the external system synchronization entry, then delete the domain. See [“Using Direct Links”](#) in [“Connecting to GroupWise 5.x, 6.x, and 7 Systems”](#) in the *GroupWise 7 Multi-System Administration Guide*.

DB49 Cannot use limited visibility distribution list as administrator

Source: GroupWise engine; administration engine.

Explanation: The selected distribution list cannot be used for the administrator because it is not visible to all users in your GroupWise system.

Action: Create a new distribution list to use as the administrator that contains only users that can be visible throughout your GroupWise system. For information about changing distribution list properties, see [“Creating and Managing Distribution Lists”](#) in [“Distribution Lists, Groups, and Organizational Roles”](#) in the *GroupWise 7 Administration Guide*.

Action: Change the visibility of the selected distribution list to system so that all users can see it.

DB4A External sync message from unknown system

Source: GroupWise engine; administration engine.

Explanation: An external synchronization message was received from a system that the local GroupWise system cannot identify.

Possible Cause: The local GroupWise system is not set up to synchronize with the system that sent the synchronization message.

Action: Configure the local GroupWise system for external synchronization with that system. See [“Exchanging Information Between Systems”](#) in [“Connecting to GroupWise 5.x, 6.x, and 7 Systems”](#) in the *GroupWise 7 Multi-System Administration Guide*.

Possible Cause: The external synchronization record in the domain database has been damaged.

Action: Delete the external synchronization record. In ConsoleOne, click Tools > GroupWise System Operations > External System Synchronization. Select an external system, then click Delete > Close. Exit and restart the MTA and POA. Re-create the external synchronization record. See [“Exchanging Information Between Systems”](#) in [“Connecting to GroupWise 5.x, 6.x, and 7 Systems”](#) in the *GroupWise 7 Multi-System Administration Guide*.

DB4B Cannot delete Internet domain name that is still referenced

Source: GroupWise engine; administration engine.

Explanation: The specified Internet domain name is being referenced in a system, domain, post office, or user.

Possible Cause: You are trying to delete an Internet domain record that is still in use.

Action: Change or delete the Internet domain association. See [“Configuring Internet Addressing”](#) in [“System”](#) in the *GroupWise 7 Administration Guide*.

DB4D Database recovery required to update database structure

Source: GroupWise engine; administration engine.

Explanation: The database needs to be recovered.

Possible Cause: The database dictionaries (*.dc files) are newer than the current database, so a recover is needed to update the database.

Action: The admin thread of the POA or MTA should take care of this recovery automatically. If not, perform the recovery manually. See [“Recovering Domain or Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

DB4E Cannot delete default gateway

Source: GroupWise engine; administration engine.

Explanation: The gateway is used in default routing.

Possible Cause: You are trying to delete a GroupWise Internet Agent object that is used as the default gateway for routing Internet messages.

Action: Select a different Internet Agent as the default gateway for Internet messages. See [“Configuring Internet Addressing”](#) in [“System”](#) in the *GroupWise 7 Administration Guide*.

DB4F Cannot delete POA that performs message transfer

Source: GroupWise engine; administration engine.

Explanation: The POA is used as the message transfer recipient for its post office.

Possible Cause: You are trying to delete a POA that is part of the TCP/IP link between the post office and domain through which messages arrive in the post office.

Action: Set up a different POA to provide the link to the domain MTA. See [“Using Client/Server Access to the Post Office”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*. After another POA has been set up to provide the link with the MTA, the original POA can be deleted.

DB50 Access to this library has been enabled by WebPublisher

Source: GroupWise engine; administration engine.

Explanation: An action cannot be completed because of how the library is configured.

Possible Cause: A library cannot be deleted because it is configured for access by WebPublisher.

Action: Remove the WebPublisher access to the library. See [“Modifying WebPublisher Settings”](#) in [“WebAccess”](#) in the *GroupWise 7 Administration Guide*. Then delete the library.

DB51 Required network address information is missing

Source: GroupWise engine; administration engine.

Explanation: An action cannot be completed because of insufficient configuration information.

Possible Cause: An agent has not been properly configured with an IP address or TCP port.

Action: The POA is not properly configured. See [“Using Client/Server Access to the Post Office”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

Action: The MTA is not properly configured. See [“Changing the Link Protocol between Domains”](#) in [“Message Transfer Agent”](#) in the *GroupWise 7 Administration Guide*.

Action: The Internet Agent is not properly configured. In ConsoleOne, browse to and right-click the GWIA object, then click Properties. Click Post Office Links, then correct the link information as needed. See [“Internet Agent”](#) in the *GroupWise 7 Administration Guide*.

Action: The WebAccess Agent is not properly configured. See [“Managing Access to Post Offices”](#) in [“WebAccess”](#) in the *GroupWise 7 Administration Guide*.

DB52 Required path information is missing

Source: GroupWise engine; administration engine.

Explanation: An action cannot be completed because of insufficient configuration information.

Possible Cause: A domain or post office has not been properly configured with the path to the directory where the domain or post office is located.

Action: Check the UNC path information provided for the domain or post offices. See [“Editing Domain Properties”](#) in [“Domains”](#) or [“Editing Post Office Properties”](#) in [“Post Offices”](#) in the *GroupWise 7 Administration Guide*.

DB53 No message transfer POA has been selected

Source: GroupWise engine; administration engine.

Explanation: An action cannot be completed because of insufficient configuration information.

Possible Cause: A post office has been configured with a TCP/IP link to its domain, but no POA has been selected to provide the link to the MTA.

Action: Configure the link between the POA and the MTA. See [“Editing a Post Office Link”](#) in [“Domains”](#) in the *GroupWise 7 Administration Guide*.

DB55 No POA is available for client/server

Source: GroupWise engine; administration engine.

Explanation: An action cannot be completed because of incorrect configuration.

Possible Cause: A post office has been configured for client/server access mode, but no POA has been configured for client/server processing.

Action: Configure a POA for client/server mode. See [“Using Client/Server Access to the Post Office”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

DB56 Specified e-mail address conflicts with the address of an existing gateway alias

Source: GroupWise engine; administration engine.

Possible Cause: You are creating or modifying a gateway alias in such a way that its new name conflicts with an existing gateway alias.

Action: Choose a different name for the new gateway alias. Check for existing names first. See [“Email Address Lookup”](#) in [“System”](#) in the *GroupWise 7 Administration Guide*.

DB57 Specified e-mail address conflicts with the address of an existing user

Source: GroupWise engine; administration engine.

Possible Cause: You are creating, modifying, or moving a user in such a way that its new name conflicts with an existing user name.

Action: Choose a different name for the new user. Check for existing names first. See [“Email Address Lookup”](#) in [“System”](#) in the *GroupWise 7 Administration Guide*.

DB58 Specified e-mail address conflicts with an address from a post office alias record

Source: GroupWise engine; administration engine.

Possible Cause: You are creating or modifying a post office alias in such a way that its new name conflicts with an existing post office alias.

Action: Choose a different name for the new post office alias. Check for existing names first. See “[Email Address Lookup](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*.

DB59 This GroupWise administration version is older than the minimum allowed by the system administrator

Source: GroupWise engine; administration engine.

Explanation: Although you can start ConsoleOne, the GroupWise snap-ins are out of date.

Possible Cause: In ConsoleOne, the Lock Out Older GroupWise Administration Snapins option has been selected under Tools > GroupWise System Operations > System Preferences > Admin Lockout Settings and you are trying to run ConsoleOne with a version of the snap-ins that is too old.

Action: Update the GroupWise snap-ins. See “[ConsoleOne](#)” in “[Installing a Basic GroupWise System](#)” in the “*GroupWise 7 Installation Guide*”.

DB60 The LDAP server is being used for eDirectory synchronization

Source: GroupWise engine; administration engine.

Explanation: An MTA that performs eDirectory user synchronization obtains its eDirectory information from a server that is also being used in your GroupWise system as an LDAP server.

Possible Cause: You are trying to delete an LDAP server that is being used for eDirectory user synchronization as well as for LDAP.

Action: Reconfigure eDirectory synchronization. See “[Using eDirectory User Synchronization](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*. Then delete the LDAP server.

DB61 The signature information is too large

Source: GroupWise engine; administration engine.

Explanation: ConsoleOne cannot save the global signature you have created because it exceeds 2.43 MB.

Possible Cause: You have tried to create a global signature that is larger than 2.43 MB.

Action: Remove some text or objects from the global signature.

DB62 The software area is being referenced

Source: GroupWise engine; administration engine.

Explanation: The software distribution area is still in use by one or more post offices.

Possible Cause: You are trying to delete a software distribution area that is still in use.

Action: Configure the post offices to use other software distribution directories. In ConsoleOne, display the Post Office Settings property page of each Post Office object, then select a different software distribution directory. When no post offices reference the software distribution directory, it can be deleted.

DE02 Cannot perform delayed action request

Source: GroupWise engine; data store and deferment.

Explanation: Error in the defer routine. Unable to perform delayed action request.
Possible Cause: Insufficient memory.
Action: Wait and retry the operation later.

DE05 Unexpected error

Source: GroupWise engine; data store and deferment.
Action: See “Dxxx Unexpected error” on page 128.

DF10 Required file or directory missing

Source: GroupWise engine; mailbox/library maintenance.
Explanation: Path error.
Possible Cause: If this error occurs from the POA, the path specified by the /home switch might be incorrect.
Action: Check the /home setting in the POA startup file. Make sure the specified path exists. Make sure the path is provided in the format required for the platform on which the POA is running. See “Using POA Startup Switches” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.
NetWare Note: On a NetWare server, make sure the grpwise.ncf file contains the correct information.
Possible Cause: The **ngwguard.dc** file is missing from the post office directory.
Action: Copy the ngwguard.dc file from another post office or from the **po** subdirectory of the software distribution directory.
Possible Cause: Mailbox/Library Maintenance or GWCheck has been run more than 26 times in less than 2 weeks, so all possible temporary file names are already used and a new backup file cannot be created.
Action: Check for backup user databases (**userxxx.db**) files with extensions *.dba through *.dbz. If found, move these backup databases to another directory, then try Mailbox/Library Maintenance or GWCheck again.
If no userxxx.db file exists (that is, only backup files exist), rename the most recent backup (for example, userxxx.dbz) to userxxx.db.
Possible Cause: The post office has been created in the root directory of a NetWare volume.
Action: Move all post office directories and files into a subdirectory off the root. See “Post Office Directory” in “Directory Structure Diagrams” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*. Adjust the path to the post office in the post office Identification page in ConsoleOne.

DF15 Records lost during rebuild

Source: GroupWise engine; mailbox/library maintenance.
Explanation: The POA has been unable to rebuild a database.
Possible Cause: An administrative message requesting a rebuild in the POA input queue is damaged.
Action: Rename POA input queue (**wpcout**). Start the POA. This recreates the input queue. Repair the database again. See “Maintaining Domain and Post Office Databases” and “Maintaining User/Resource and Message Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

DF17 Cannot create required directory

Source: GroupWise engine; mailbox/library maintenance.

Explanation: The POA cannot create one or more directories required for processing messages.

Possible Cause: The POA has insufficient rights to create the directory.

Action: Make sure the POA has the necessary network rights to access the directories in the post office. See [“Creating a NetWare Account for Agent Access \(Optional\)”](#) in [“Installing GroupWise Agents”](#) in the [“GroupWise 7 Installation Guide”](#).

Action: Start the POA including the `/rights` switch to determine the specific problem the POA is encountering. See [“Using POA Startup Switches”](#) in [“Post Office Agent”](#) the [GroupWise 7 Administration Guide](#).

DF1C Document storage area definitions are not identical

Source: GroupWise engine; mailbox/library maintenance.

Explanation: The location of the document storage area, as stored in the post office database (`wphost.db`), does not match the guardian database (`ngwguard.db`). The error message includes the conflicting locations.

Action: Modify the UNC path to the document storage area as needed so that the post office database and the guardian database are both updated with the same current information. If the information looks correct as is, simply delete and retype one character so that the correct information is written out to all affected databases. See [“Managing Document Storage Areas”](#) in [“Libraries and Documents”](#) in the [GroupWise 7 Administration Guide](#).

DF27 Invalid NGWCHECK.DB database migration level

Source: GroupWise engine; mailbox/library maintenance.

Explanation: The GWCheck database (`ngwcheck.db`) contains invalid information.

Action: Delete the GWCheck database, then rerun GWCheck or Mailbox/Library Maintenance.

DF28 Failure using the NGWCHECK.DB database

Source: GroupWise engine; mailbox/library maintenance.

Explanation: The GWCheck database (`ngwcheck.db`) cannot be accessed by GWCheck.

Action: Delete the GWCheck database, then rerun GWCheck or Mailbox/Library Maintenance.

Dxxx Unexpected error

Source: GroupWise engine.

Explanation: An engine error has occurred for which GroupWise does not have a specific error message.

Action: Exit and then restart the GroupWise client

Exxx Engine Error Codes

Range:

- ◆ E50x
- ◆ E51x
- ◆ E52x
- ◆ E5xx
- ◆ E80x
- ◆ E81x
- ◆ E82x
- ◆ E584x

Range: E50x

- “E501 Document version not available” on page 131
- “E503 Unexpected error” on page 132
- “E507 Unexpected error” on page 132
- “E508 Unexpected error” on page 132
- “E50A Unexpected error” on page 132
- “E50B Unexpected error” on page 132
- “E50C Unexpected error” on page 132
- “E50D Maximum number of libraries per post office reached” on page 132
- “E50E Unexpected error” on page 133

Range: E51x

- “E511 Document version available” on page 133
- “E512 Invalid user ID” on page 133
- “E513 Unexpected error” on page 133
- “E514 Document version must be checked out and in by same user” on page 133
- “E515 Cannot delete last version of document” on page 134
- “E516 Unexpected error” on page 134
- “E517 Unexpected error” on page 134
- “E51B Access to feature denied” on page 134

“E51C Disk space limit exceeded” on page 134

Range: E52x

“E520 Unexpected error” on page 134

“E522 Library not empty” on page 134

“E523 Document not modified” on page 135

“E524 Document not available for synchronization to server” on page 135

“E525 Cannot delete lookup table; it is not empty” on page 135

“E526 Cannot delete lookup table; it is in use” on page 135

“E527 Cannot create library; record already exists” on page 135

“E528 Cannot transfer data to server” on page 135

“E529 All document blob areas full” on page 136

“E52A Document not available” on page 136

Range: E5xx

“E700 Invalid Address Book record” on page 136

“E716 Personal Address Book memory error” on page 136

Range: E80x

“E801 Unexpected error” on page 136

“E803 Unexpected error” on page 137

“E804 Unexpected error” on page 137

“E805 Unexpected error” on page 137

“E806 Unexpected error” on page 137

“E807 Unexpected error” on page 137

“E808 Unexpected error” on page 137

“E809 Unexpected error” on page 137

“E80C Unexpected error” on page 137

“E80D Unexpected error” on page 137

“E80F Unexpected error” on page 137

Range: E81x

“E810 Unexpected error” on page 138

“E811 Unexpected error” on page 138

“E812 Unexpected error” on page 138

“E813 Unexpected error” on page 138

“E814 Unexpected error” on page 138

“E815 Unexpected error” on page 138

“E816 Insufficient rights to perform operation” on page 138

“E818 Unexpected error” on page 138

Range: E82x

“E820 Invalid attribute value” on page 138
“E821 Unexpected error” on page 139
“E823 Unexpected error” on page 139
“E824 Unexpected error” on page 139
“E82B Unexpected error” on page 139
“E82C Unexpected error” on page 139
“E82E Unexpected error” on page 139
“E82F Unexpected error” on page 139

Range: E84x

“E848 Unexpected error” on page 139

Range: EAxx

“EA02 The item is not found in the container portion of the uid” on page 139
“EA03 Handling of SOAP protocol is not enabled” on page 140
“EA04 The response is too large” on page 140
“EA05 Invalid cursor” on page 140
“EA06 Invalid session string” on page 141
“EA07 Container string is missing” on page 141
“EA08 Display name is missing” on page 141
“EA09 User structure still busy” on page 142
“EA0A Item already accepted” on page 142
“EA0B Item not acceptable/declinable” on page 142
“EA0C The method called is not supported” on page 143
“EA0E Key is invalid” on page 143
“EA0F Missing cursor” on page 143
“EA10 Missing session string” on page 144
“EA11 Maximum event read threads” on page 144
“EA13 Redirect user to different post office” on page 144
“EA15 The method called is not supported on this container” on page 144
“EA16 The specified contentType is not supported with this call” on page 145
“EA17 The specified date/time range is invalid” on page 145
“EA18 Searching over the entire mailbox requires a filter” on page 145

E501 Document version not available

Source: GroupWise® engine; document management.
Explanation: Document version not available.
Possible Cause: The document is currently in use.
Action: Have the user who retrieved the document version close it.

Possible Cause: The document is currently checked out.

Action: Have the user who checked it out check it back in. Look up “documents, checking in” in GroupWise client Help.

Possible Cause: The document is neither in use nor checked out, but is erroneously marked as such. This situation can arise because:

- ◆ A user opened the document with a non-integrated application. A non-integrated application cannot check the document back into the GroupWise library when the user closes the document.
- ◆ A user’s workstation went down while the document was open.

Action: Manually reset the document status. Look up “document, status” in GroupWise client Help.

E503 Unexpected error

Source: GroupWise engine; document management.

Action: See “[Exxx Unexpected error](#)” on page 146.

E507 Unexpected error

Source: GroupWise engine; document management.

Action: See “[Exxx Unexpected error](#)” on page 146.

E508 Unexpected error

Source: GroupWise engine; document management.

Action: See “[Exxx Unexpected error](#)” on page 146.

E50A Unexpected error

Source: GroupWise engine; document management.

Action: See “[Exxx Unexpected error](#)” on page 146.

E50B Unexpected error

Source: GroupWise engine; document management.

Action: See “[Exxx Unexpected error](#)” on page 146.

E50C Unexpected error

Source: GroupWise engine; document management.

Action: See “[Exxx Unexpected error](#)” on page 146.

E50D Maximum number of libraries per post office reached

Source: GroupWise engine; document management.

Explanation: Maximum libraries reached.

Possible Cause: The maximum number of libraries allowed per post office has been reached. Each post office can have as many as 256 libraries. A user attempted to create the 257th library.

Action: Delete any unnecessary libraries on the post office. Then create the new library. See “[Creating and Managing Libraries](#)” in “[Libraries and Documents](#)” in the *GroupWise 7 Administration Guide*.

Action: Create the new library on another post office.

E50E Unexpected error

Source: GroupWise engine; document management.

Action: See “[Exxx Unexpected error](#)” on page 146.

E511 Document version available

Source: GroupWise engine; document management.

Explanation: Version is available.

Possible Cause: The user is attempting to check in a document version that is not checked out, or to end access to a version that is not in use.

Action: Do not attempt to check in or end access to a version that is already available.

E512 Invalid user ID

Source: GroupWise engine; document management.

Explanation: The user ID on a document is not valid.

Possible Cause: User information on the document has been damaged.

Action: Repair the document information in the library. See “[Maintaining Library Databases and Documents](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: Run GWCheck on the library. See “[Standalone Database Maintenance Programs](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: A user tried to start the GroupWise client as a resource, that is, using the `/@u-userID` startup switch and specifying a resource rather than a user.

Action: None. You cannot start the GroupWise client as a resource. You must use a valid user ID.

E513 Unexpected error

Source: GroupWise engine; document management.

Action: See “[Exxx Unexpected error](#)” on page 146.

E514 Document version must be checked out and in by same user

Source: GroupWise engine; document management.

Explanation: User IDs do not match.

Possible Cause: The user is attempting to check in or close a document version using a different user ID than the one used to check it out. A document version must be checked in or closed by same user who checked it out or opened it.

Action: Log in to GroupWise as the user who checked out or opened the document version, then check in or close the document. Look up “documents, checking in” in GroupWise client Help. You can find out who originally checked out or opened the document by checking its activity log. Look up “activity logs” in GroupWise client Help.

E515 Cannot delete last version of document

Source: GroupWise engine; document management.

Explanation: Cannot delete last version.

Action: Delete the entire document, not just the version. Look up “documents, deleting” in GroupWise client Help.

E516 Unexpected error

Source: GroupWise engine; document management.

Action: See “**Exxx Unexpected error**” on page 146.

E517 Unexpected error

Source: GroupWise engine; document management.

Action: See “**Exxx Unexpected error**” on page 146.

E51B Access to feature denied

Source: GroupWise engine; document management.

Explanation: Access to requested feature denied.

Possible Cause: The user is attempting to use a document management feature that is not available to this user on this library.

Action: If the user should be allowed to use this feature, grant the appropriate library membership rights. See “**Managing Library Access**” in “**Libraries and Documents**” in the *GroupWise 7 Administration Guide*.

E51C Disk space limit exceeded

Source: GroupWise engine; document management.

Explanation: The user has exceeded his or her limit of disk space in the library.

Possible Cause: The user is trying to add or modify a document and has run out of space in the library.

Action: The user must delete some documents or versions in order to free up disk space.

E520 Unexpected error

Source: GroupWise engine; document management.

Action: See “**Exxx Unexpected error**” on page 146.

E522 Library not empty

Source: GroupWise engine; document management.

Explanation: Library not empty.

Possible Cause: GroupWise cannot perform the requested operation until the library is empty.

Action: Delete all documents from the library. Look up “documents, deleting” in GroupWise client Help.

E523 Document not modified

Source: GroupWise engine; document management.

Explanation: Document not modified.

Possible Cause: The document has not been modified and does not need to be sent to the server.

Action: Make changes to the document, then save the document.

E524 Document not available for synchronization to server

Source: GroupWise engine; document management.

Explanation: Document not available for synchronization.

Possible Cause: The document is currently in use.

Action: Close the document.

Possible Cause: The document is archived.

Action: Restore the document. See [“Restoring Archived Documents”](#) in [“Libraries and Documents”](#) in the *GroupWise 7 Administration Guide*.

E525 Cannot delete lookup table; it is not empty

Source: GroupWise engine; document management.

Explanation: Lookup table not empty.

Possible Cause: Cannot delete the lookup table because it is not empty.

Action: Delete all entries from the lookup table, then retry the operation. See [“Customizing Document Properties”](#) in [“Libraries and Documents”](#) in the *GroupWise 7 Administration Guide* for information about lookup tables.

E526 Cannot delete lookup table; it is in use

Source: GroupWise engine; document management.

Explanation: Lookup table in use by a library.

Possible Cause: The lookup table cannot be deleted because it is being used by a library.

Action: Remove all library references to the lookup table, then retry the operation. See [“Customizing Document Properties”](#) in [“Libraries and Documents”](#) in the *GroupWise 7 Administration Guide* for information about lookup tables.

E527 Cannot create library; record already exists

Source: GroupWise engine; document management.

Explanation: Library already exists.

Action: Use a unique library name to create the library. See [“Creating and Managing Libraries”](#) in [“Libraries and Documents”](#) in the *GroupWise 7 Administration Guide*.

E528 Cannot transfer data to server

Source: GroupWise engine; document management.

Explanation: Transport to a server failed.

Possible Cause: The system was unable to contact a needed server.

Action: Make sure the needed server is up, and that all transport hardware is functioning correctly.

E529 All document blob areas full

Source: GroupWise engine; document management.

Explanation: All BLOB areas are full.

Possible Cause: All of the areas that hold binary large objects (BLOBs) are full, so the system was unable to create a new BLOB.

Action: Create a new library. See [“Creating and Managing Libraries”](#) in [“Libraries and Documents”](#) in the *GroupWise 7 Administration Guide*.

E52A Document not available

Source: GroupWise engine; document management.

Explanation: The document cannot be restored because it is no longer available on disk.

Possible Cause: The document has been moved from the library archive to a backup medium.

Action: Move the document back into the library so it is available to users. See [“Restoring Archived Documents”](#) in [“Libraries and Documents”](#) in the *GroupWise 7 Administration Guide*.

To see where the document belongs, right-click the document reference in the GroupWise client, then click Properties. Click Version, then check the current location and current filename information.

E700 Invalid Address Book record

Source: GroupWise engine; Personal Address Book.

Explanation: The POA could not access a user’s Personal Address Book.

Possible Cause: The POA is attempting to perform nightly user upkeep for a new user that has not yet used the GroupWise client, which means that the Personal Address Book does not yet exist.

Action: None. After the user starts the GroupWise client and sends or receives a message, the Personal Address Book will be created and the POA will no longer encounter the problem.

Action: If the error persists when the Personal Address Book already exists, see [“8101 Memory error”](#) on [page 15](#).

E716 Personal Address Book memory error

Source: GroupWise engine; Personal Address Book.

Explanation: An action involving the Personal Address Book could not be performed due to insufficient memory.

Action: Exit some programs so that more memory is available.

Action: Restart the workstation where the error is occurring.

E801 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error”](#) on [page 146](#).

E803 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146.](#)

E804 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146.](#)

E805 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146.](#)

E806 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146.](#)

E807 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146.](#)

E808 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146.](#)

E809 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146.](#)

E80C Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146.](#)

E80D Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146.](#)

E80F Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146.](#)

E810 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E811 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E812 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E813 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E814 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E815 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E816 Insufficient rights to perform operation

Source: GroupWise engine; object framework.

Explanation: Security access denied.

Possible Cause: User does not have rights to perform this operation on this object.

Action: Have the document owner grant you rights. Look up “documents, permission to access” in GroupWise client Help. Also see [“Managing Library Access”](#) in [“Libraries and Documents”](#) in the *GroupWise 7 Administration Guide*.

E818 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E820 Invalid attribute value

Source: GroupWise engine; object framework.

Explanation: Validation error when creating or updating a document.

Possible Cause: The user supplied a value for a document property that does not match the valid values specified by the corresponding lookup table. For example, the value was too large or too small.

Action: Retry the operation with valid values for document properties.

E821 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E823 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E824 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E82B Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E82C Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E82E Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E82F Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

E848 Unexpected error

Source: GroupWise engine; object framework.

Action: See [“Exxx Unexpected error” on page 146](#).

EA02 The item is not found in the container portion of the uid

Source: GroupWise engine; SOAP protocol.

Explanation: Your application looked for a GroupWise item in a particular container (a folder or an address book) in a GroupWise mailbox and did not find the item.

Possible Cause: Your application calls a method that requires a container as an argument and the item is not in the specified container.

Possible Cause: Your application passes a uid that does not have the container appended to the end. Therefore, the item cannot be found.

Action: Call `getItemsRequest` and compare the uid from that call to the uid that you used when the error was generated.

For more information, see:

- ◆ [uid element \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brwiocm.html#brwiocm\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brwiocm.html#brwiocm)

EA03 Handling of SOAP protocol is not enabled

Source: GroupWise engine; SOAP protocol.

Explanation: A SOAP client has attempted to contact the POA and the POA cannot respond successfully.

Possible Cause: The POA is not yet configured for SOAP.

Action: See “[Supporting SOAP Clients](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

EA04 The response is too large

Source: GroupWise engine; SOAP protocol.

Explanation: The POA received a response from your application that is too large for it to process.

Possible Cause: Your application responded to the POA with more than 1 MB of data.

Action: Refine the SOAP request so that the response is smaller.

Action: Use the `/soapsizelimit` startup switch on the POA to increase the maximum size of the data that the POA accepts.

EA05 Invalid cursor

Source: GroupWise engine; SOAP protocol.

Explanation: Your application cannot read the current cursor value. Cursors break lists of data into chunks. Your application cannot determine where the boundary of the data chunk is located.

Possible Cause: The cursor has already been freed using the `destroyCursor` method.

Action: Create a new cursor. A cursor cannot be used again after it has been freed.

Possible Cause: The current value of the cursor is not valid.

Action: Create a cursor before attempting to position or read from it.

For more information, see:

- ◆ [Cursors \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bwnsce.html#bwnsce\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bwnsce.html#bwnsce)
- ◆ [createCursor method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx85xo.html#brx85xo\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx85xo.html#brx85xo)
- ◆ [positionCursor method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx94t1.html#brx94t1\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx94t1.html#brx94t1)

- ◆ [readCursor method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx9f6t.html#brx9f6t\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx9f6t.html#brx9f6t)
- ◆ [destroyCursor method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8dol.html#brx8dol\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8dol.html#brx8dol)

EA06 Invalid session string

Source: GroupWise engine; SOAP protocol.

Explanation: Your application cannot access the current session with the POA.

Possible Cause: The SOAP client user has logged out of his or her GroupWise mailbox.

Possible Cause: The POA has timed out the session after 30 minutes.

Action: Your application needs to log in again for that user.

For more information, see:

- ◆ [session definition \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bs3a31o.html#bs3a31o\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bs3a31o.html#bs3a31o)
- ◆ [login method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8x54.html#brx8x54\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8x54.html#brx8x54)

EA07 Container string is missing

Source: GroupWise engine; SOAP protocol.

Explanation: The container string in a POA request is not found in your application.

Possible Cause: Your application calls a method that requires a container as an argument and you have not provided a container.

Possible Cause: Your application passes in a uid that does not have the container appended to the end.

Action: Call `getItemsRequest` and compare the uid from that call to the uid that you used when the error was generated.

For more information, see:

- ◆ [Item element \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brw59e1.html#brw59e1\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brw59e1.html#brw59e1)
- ◆ [uid element \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brwiocm.html#brwiocm\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brwiocm.html#brwiocm)
- ◆ [getItems method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8r5w.html#brx8r5w\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8r5w.html#brx8r5w)
- ◆ [ContainerRef element \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brw3u9a.html#brw3u9a\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brw3u9a.html#brw3u9a)
- ◆ [ContainerItem element \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brw3r28.html#brw3r28\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brw3r28.html#brw3r28)

EA08 Display name is missing

Source: GroupWise engine; SOAP protocol.

Explanation: A display name is the human-readable name of a GroupWise object. It is required when creating such objects as a contact or a resource.

Possible Cause: Your application tries to create a GroupWise item that should include a display name without providing the display name.

Action: Make sure you provide the display name when creating the object.

For more information, see:

- ◆ [displayName definition \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bs39q28.html#bs39q28\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bs39q28.html#bs39q28)
- ◆ [createItem method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8867.html#brx8867\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8867.html#brx8867)

EA09 User structure still busy

Source: GroupWise engine; SOAP protocol.

Explanation: A user structure contains the data about a user session. It cannot be accessed when it is busy.

Possible Cause: Your application is trying to log out of the POA when a lengthy activity such as a Busy Search is in progress.

Action: Program your application to wait when this error is encountered. The problem typically resolves itself in a short period of time.

EA0A Item already accepted

Source: GroupWise engine; SOAP protocol.

Explanation: The GroupWise item being processed has already been accepted and cannot be accepted again.

Possible Cause: Your application is trying to mark as Accepted a GroupWise item that has already been accepted by the SOAP client user.

Action: Accepted items are marked as accepted. Check the status of an item before trying to accept it.

For more information, see:

- ◆ [accept method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brwiukl.html#brwiukl\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brwiukl.html#brwiukl)

EA0B Item not acceptable/declinable

Source: GroupWise engine; SOAP protocol.

Explanation: The GroupWise item being processed is not eligible for being accepted or declined.

Possible Cause: Your application is trying to accept a GroupWise item that cannot be accepted or declined because it is not the right type of item.

Action: Check the following item status information before trying to accept an item:

- ◆ The item is a calendar item (appointment, note, or task).
- ◆ The item is a received item in the Mailbox folder.
- ◆ The item is not archived.
- ◆ The items is not in the Work in Progress folder.
- ◆ The item is not in the Trash folder.
- ◆ Your application has sufficient access rights to the item.

For more information, see:

- ♦ [accept method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brwiukl.html#brwiukl\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brwiukl.html#brwiukl)
- ♦ [decline method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8aih.html#brx8aih\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8aih.html#brx8aih)

EA0C The method called is not supported

Source: GroupWise engine; SOAP protocol.

Explanation: The action that your application is trying to perform is no longer accepted by the GroupWise SOAP protocol used by the POA.

Possible Cause: Your application contains a method that is out of date.

Action: Use a supported method.

For a list of currently supported methods, see:

- ♦ [Methods \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx9pkk.html#brx9pkk\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx9pkk.html#brx9pkk)

EA0E Key is invalid

Source: GroupWise engine; SOAP protocol.

Explanation: A key is a unique identifier that is used to create or modify an event configuration. Events notify your application when an event has occurred in a user's mailbox, for example, when an item is deleted.

Possible Cause: Your application did not provide a usable key.

Possible Cause: The key string is empty.

Action: Check the configureEvents request to see if it is passing a valid key element.

For more information, see:

- ♦ [Event object \(http://developer.novell.com/ndk/doc/gwevents/evnt_enu/data/buotgsx.html#buotgsx\)](http://developer.novell.com/ndk/doc/gwevents/evnt_enu/data/buotgsx.html#buotgsx)
- ♦ [configureEvents XML reference \(http://developer.novell.com/ndk/doc/gwevents/evnt_enu/data/buj9p3v.html#buj9p3v\)](http://developer.novell.com/ndk/doc/gwevents/evnt_enu/data/buj9p3v.html#buj9p3v)

EA0F Missing cursor

Source: GroupWise engine; SOAP protocol.

Explanation: A required cursor string is absent.

Possible Cause: Your application calls a method that requires a cursor, but no cursor was provided.

Action: Call createCursor to get a valid cursor before using positionCursor or readCursor.

For more information, see:

- ♦ [Cursors \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bwnscce.html#bwnscce\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bwnscce.html#bwnscce)
- ♦ [createCursor method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx85xo.html#brx85xo\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx85xo.html#brx85xo)
- ♦ [positionCursor method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx94t1.html#brx94t1\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx94t1.html#brx94t1)

- ◆ [readCursor method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx9f6t.html#brx9f6t\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx9f6t.html#brx9f6t)
- ◆ [destroyCursor method \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8dol.html#brx8dol\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8dol.html#brx8dol)

EA10 Missing session string

Source: GroupWise engine; SOAP protocol.

Explanation: A session string identifies a user and his or her GroupWise data. This information is missing.

Possible Cause: The POA has timed out the session after 30 minutes.

Action: Your application needs to log in again for that user.

Possible Cause: Your application does not use a loginResponse to obtain a session string before calling a method that requires a session string.

Action: Make sure you use the login method to obtain a session string.

For more information, see:

- ◆ [session definition \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bs3a31o.html#bs3a31o\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bs3a31o.html#bs3a31o)

EA11 Maximum event read threads

Source: GroupWise engine; SOAP protocol.

Explanation: Your application has started as many event read threads as the POA is configured to service. The POA cannot create additional event read threads.

Possible Cause: Your application is issuing more getEvents requests than the POA can respond to.

Action: Reduce the number of getEvents requests that your application issues at one time.

For more information, see:

- ◆ [getEvents method \(http://developer.novell.com/ndk/doc/gwevents/evnt_enu/data/bundmjo.html#bundmjo\)](http://developer.novell.com/ndk/doc/gwevents/evnt_enu/data/bundmjo.html#bundmjo)

EA13 Redirect user to different post office

Source: GroupWise engine; SOAP protocol.

Explanation: The specified user does not exist in the specified post office and needs to be redirected in order to log in to GroupWise successfully.

Possible Cause: The user resides in a different post office than your application specified in the login.

Action: Redirect the user to the correct post office.

For more information, see:

- ◆ [login method and loginResponse \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8x54.html#brx8x54\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx8x54.html#brx8x54)

EA15 The method called is not supported on this container

Source: GroupWise engine; SOAP protocol.

Explanation: The calling method is valid, but the container type on which it is being called is not appropriate.

- Possible Cause: Your application is calling a method that is not supported on the container type for which it was called. For example:
- ♦ The `getQuickMessages` method cannot be used on the Contacts folder, the Trash folder, or a query folder.
 - ♦ The `createCursor` method cannot be used on the Contacts folder.

Action: Use a method that is valid for the container type.

For more information, see:

- ♦ [Methods \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx9pkk.html#brx9pkk\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brx9pkk.html#brx9pkk)

EA16 The specified contentType is not supported with this call

Source: GroupWise engine; SOAP protocol.

Explanation: The call that generated this error supports only the text/plain content type. HTML is not yet supported for this call.

Possible Cause: Your application is trying to create a GroupWise item with HTML content type when only the text/plain content type is currently supported.

Action: Use the text/plain content type.

EA17 The specified date/time range is invalid

Source: GroupWise engine; SOAP protocol.

Explanation: The specified date/time range is not usable.

Possible Cause: Your application fails to specify a start date on a recurring item.

Possible Cause: Your application specifies an end date that is earlier than the start date.

Action: Specify a valid date/type range.

For more information, see:

- ♦ [startDate definition \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bwmwd74.html#bwmwd74\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bwmwd74.html#bwmwd74)
- ♦ [endDate definition \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bs3a12a.html#bs3a12a\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/bs3a12a.html#bs3a12a)

EA18 Searching over the entire mailbox requires a filter

Source: GroupWise engine; SOAP protocol.

Explanation: Because a GroupWise mailbox can be very large, the process of searching the entire mailbox should be limited, either by a filter or by restricting the search to a particular container in the mailbox.

Possible Cause: Your application is attempting to search an entire mailbox without limiting the search using either a filter or a container.

Action: Supply a filter.

For more information, see:

- ♦ [Filter element \(http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brw4l5r.html#brw4l5r\)](http://developer.novell.com/ndk/doc/gwsoap/soap_enu/data/brw4l5r.html#brw4l5r)

Action: Supply a container.

Exxx Unexpected error

Source: GroupWise engine.

Explanation: An engine error has occurred for which GroupWise does not have a specific error message.

Action: Exit and then restart the GroupWise client.

Fxxx Engine Error Codes

Range:

- ◆ F00x
- ◆ F01x
- ◆ F02x
- ◆ F03x
- ◆ F04x
- ◆ F05x
- ◆ F06x
- ◆ F07x
- ◆ F08x
- ◆ F09x
- ◆ F0Ax
- ◆ F0Bx
- ◆ F0Cx
- ◆ F1xx

Range: F00x

- “F000 Memory error” on page 151
- “F007 End of command reached unexpectedly” on page 151
- “F008 Missing parenthesis in search command” on page 151
- “F009 Missing operator in search command” on page 151
- “F00A Switch at end of search command ignored” on page 151
- “F00B Unknown switch in search command” on page 151
- “F00C Ambiguous switch; supply more characters” on page 152

Range: F01x

- “F010 Search cancelled” on page 152
- “F012 File I/O error” on page 152
- “F013 Database error” on page 152

“F014 Database error” on page 152
“F016 Database error” on page 152
“F018 Number contains non-numeric characters” on page 152
“F019 Search switch requires ‘=n’” on page 153
“F01A Document summary field name or number required” on page 153
“F01B Unknown field in search command” on page 153
“F01C Ambiguous field; supply more characters” on page 153
“F01D Empty quotation marks not allowed” on page 153
“F01E /nowildcard and /prefix cannot be used together” on page 153
“F01F Invalid syntax in search query” on page 153

Range: F02x

“F020 Date expected” on page 153
“F021 Dates of range in wrong order” on page 153
“F022 Missing switch after ‘/’” on page 153
“F023 Word missing between operators” on page 154
“F026 Database error” on page 154
“F02A Search query must specify words to search for” on page 154
“F02D Missing word after operator” on page 154
“F02E Invalid date” on page 154
“F02F Word too long for search” on page 154

Range: F03x

“F030 Empty parentheses not allowed” on page 154
“F037 Memory error” on page 154
“F03E Memory error” on page 154

Range: F04x

“F045 Unexpected error” on page 154
“F046 File I/O error” on page 155
“F047 File I/O error” on page 155
“F048 File I/O error” on page 155
“F049 File I/O error” on page 155
“F04A File I/O error” on page 155
“F04C File I/O error” on page 155
“F04D File I/O error” on page 155
“F04E File not found during QuickFinder indexing” on page 155
“F04F File I/O error” on page 155

Range: F05x

“F050 Database error” on page 155

“F051 Database error” on page 156

“F052 Database error” on page 156

“F056 Database error” on page 156

Range: F06x

“F060 Database error” on page 156

“F061 Database error” on page 156

“F062 Database error” on page 156

“F063 Database error” on page 156

“F064 Database error” on page 156

“F065 Database error” on page 156

“F066 Database error” on page 156

“F067 Database error” on page 157

“F068 Database error” on page 157

“F069 Database error” on page 157

“F06A Database error” on page 157

“F06B Database error” on page 157

“F06C Database error” on page 157

“F06D Database error” on page 157

“F06E Database error” on page 157

“F06F Database error” on page 157

Range: F07x

“F070 Database error” on page 157

“F071 Database error” on page 158

“F072 Database error” on page 158

“F073 Database error” on page 158

“F074 Database error” on page 158

“F075 Database error” on page 158

“F076 Database error” on page 158

“F077 Database error” on page 158

“F078 Database error” on page 158

“F079 Database error” on page 158

“F07A Database error” on page 158

“F07B Database error” on page 159

“F07C Database error” on page 159

“F07D Database error” on page 159

“F07E Database error” on page 159

“F07F Database error” on page 159

Range: F08x

“F080 Database error” on page 159

“F082 Database error” on page 159
“F083 Database error” on page 159
“F084 Database error” on page 159
“F085 Database error” on page 159
“F086 Database error” on page 160
“F087 Database error” on page 160
“F088 Database error” on page 160
“F089 Database error” on page 160
“F08A Database error” on page 160
“F08B Database error” on page 160
“F08D Database error” on page 160
“F08E Database error” on page 160
“F08F Database error” on page 160

Range: F09x

“F090 Database error” on page 160
“F091 Database error” on page 161
“F092 Database error” on page 161
“F093 Database error” on page 161
“F094 Database error” on page 161
“F095 Database error” on page 161
“F096 Database error” on page 161
“F097 Database error” on page 161
“F098 Database error” on page 161
“F099 Database error” on page 161
“F09A Database error” on page 161
“F09B Memory error” on page 162

Range: F0Ax

“F0A1 Memory error” on page 162

Range: F0Bx

“F0B2 Memory error” on page 162
“F0B5 File I/O error” on page 162
“F0B9 Unexpected error” on page 162
“F0BA Database error” on page 162
“F0BB Database error” on page 162
“F0BC Database error” on page 162
“F0BD Database error” on page 162
“F0BE Database error” on page 162
“F0BF Database error” on page 163

Range: F0Cx

“F0C0 Database error” on page 163

“F0C2 Database error” on page 163

“F0C4 Database error” on page 163

Range: F1xx

“F101 Cannot connect to remote server” on page 163

“F102 Cannot connect to remote server” on page 163

“F103 Cannot connect to remote server” on page 163

“F104 Cannot connect to remote server” on page 163

“F105 Cannot connect to remote server” on page 163

“F106 Cannot connect to remote server” on page 163

“F107 Cannot connect to remote server” on page 164

“F108 Cannot connect to remote server” on page 164

F000 Memory error

Source: GroupWise® engine; QuickFinder™.

Action: See “F0xx Memory error” on page 165.

F007 End of command reached unexpectedly

Source: GroupWise engine; QuickFinder.

Action: See “F0xx Query syntax error” on page 164.

F008 Missing parenthesis in search command

Source: GroupWise engine; QuickFinder.

Action: See “F0xx Query syntax error” on page 164.

F009 Missing operator in search command

Source: GroupWise engine; QuickFinder.

Action: See “F0xx Query syntax error” on page 164.

F00A Switch at end of search command ignored

Source: GroupWise engine; QuickFinder.

Action: See “F0xx Query syntax error” on page 164.

F00B Unknown switch in search command

Source: GroupWise engine; QuickFinder.

Action: See “F0xx Query syntax error” on page 164.

F00C Ambiguous switch; supply more characters

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164](#).

F010 Search cancelled

Source: GroupWise engine; QuickFinder.

Explanation: Search cancelled.

Action: Search was cancelled at user’s request.

F012 File I/O error

Source: GroupWise engine; QuickFinder.

Explanation: The QuickFinder process used by the Find feature cannot access a required file.

Possible Cause: The QuickFinder index is damaged.

Action: Rebuild the index of the database where the error occurred. See [“Rebuilding Database Indexes” in “Databases” in the *GroupWise 7 Administration Guide*](#).

Possible Cause: The disk is full where the QuickFinder index is located, so the QuickFinder process cannot write more information to disk.

Action: Free up disk space. See [“Managing Database Disk Space” in “Databases” in the *GroupWise 7 Administration Guide*](#).

Possible Cause: You do not have rights to the location where the QuickFinder index is located.

Action: Check your access rights. See [“GroupWise User Rights” in “Security” in the *GroupWise 7 Administration Guide*](#).

Action: In ConsoleOne, you can set the proper user rights for all users in a post office or for an individual user. See [“GroupWise User Rights” in “Security” in the *GroupWise 7 Administration Guide*](#).

F013 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error” on page 164](#).

F014 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error” on page 164](#).

F016 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164](#).

F018 Number contains non-numeric characters

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164](#).

F019 Search switch requires'=n'

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F01A Document summary field name or number required

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F01B Unknown field in search command

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F01C Ambiguous field; supply more characters

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F01D Empty quotation marks not allowed

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F01E /nowildcard and /prefix cannot be used together

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F01F Invalid syntax in search query

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F020 Date expected

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F021 Dates of range in wrong order

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F022 Missing switch after'/'

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F023 Word missing between operators

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F026 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F02A Search query must specify words to search for

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F02D Missing word after operator

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F02E Invalid date

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F02F Word too long for search

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F030 Empty parentheses not allowed

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Query syntax error” on page 164.](#)

F037 Memory error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Memory error” on page 165.](#)

F03E Memory error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Memory error” on page 165.](#)

F045 Unexpected error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Unexpected error” on page 165.](#)

F046 File I/O error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx File I/O error” on page 164.](#)

F047 File I/O error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx File I/O error” on page 164.](#)

F048 File I/O error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx File I/O error” on page 164.](#)

F049 File I/O error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx File I/O error” on page 164.](#)

F04A File I/O error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx File I/O error” on page 164.](#)

F04C File I/O error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx File I/O error” on page 164.](#)

F04D File I/O error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx File I/O error” on page 164.](#)

F04E File not found during QuickFinder indexing

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx File I/O error” on page 164.](#)

F04F File I/O error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx File I/O error” on page 164.](#)

F050 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F051 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F052 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F056 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Memory error” on page 165.](#)

F060 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F061 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F062 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F063 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F064 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F065 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F066 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F067 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F068 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F069 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F06A Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F06B Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F06C Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F06D Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F06E Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F06F Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F070 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F071 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F072 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F073 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F074 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F075 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F076 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F077 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F078 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F079 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F07A Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F07B Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F07C Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F07D Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F07E Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F07F Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F080 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F082 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F083 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F084 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F085 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F086 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F087 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F088 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F089 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F08A Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F08B Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F08D Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F08E Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F08F Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F090 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F091 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F092 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F093 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F094 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F095 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F096 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F097 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F098 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F099 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F09A Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)”](#) on page 164.

F09B Memory error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Memory error” on page 165](#).

F0A1 Memory error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Memory error” on page 165](#).

F0B2 Memory error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Memory error” on page 165](#).

F0B5 File I/O error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx File I/O error” on page 164](#).

F0B9 Unexpected error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Unexpected error” on page 165](#).

F0BA Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164](#).

F0BB Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164](#).

F0BC Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164](#).

F0BD Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164](#).

F0BE Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164](#).

F0BF Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F0C0 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F0C2 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F0C4 Database error

Source: GroupWise engine; QuickFinder.

Action: See [“F0xx Database error \(index\)” on page 164.](#)

F101 Cannot connect to remote server

Source: GroupWise engine; NetWare[®] remote server connection table.

Action: See [“F1xx Cannot connect to remote server” on page 165.](#)

F102 Cannot connect to remote server

Source: GroupWise engine; NetWare remote server connection table.

Action: See [“F1xx Cannot connect to remote server” on page 165.](#)

F103 Cannot connect to remote server

Source: GroupWise engine; NetWare remote server connection table.

Action: See [“F1xx Cannot connect to remote server” on page 165.](#)

F104 Cannot connect to remote server

Source: GroupWise engine; NetWare remote server connection table.

Action: See [“F1xx Cannot connect to remote server” on page 165.](#)

F105 Cannot connect to remote server

Source: GroupWise engine; NetWare remote server connection table.

Action: See [“F1xx Cannot connect to remote server” on page 165.](#)

F106 Cannot connect to remote server

Source: GroupWise engine; NetWare remote server connection table.

Action: See [“F1xx Cannot connect to remote server” on page 165.](#)

F107 Cannot connect to remote server

Source: GroupWise engine; NetWare remote server connection table.

Action: See “[F1xx Cannot connect to remote server](#)” on page 165.

F108 Cannot connect to remote server

Source: GroupWise engine; NetWare remote server connection table.

Action: See “[F1xx Cannot connect to remote server](#)” on page 165.

F0xx Query syntax error

Source: GroupWise engine; QuickFinder.

Explanation: While using the Find feature in the GroupWise client, you received a message indicating a problem with the syntax of your search query.

Action: Correct the query syntax, then retry the operation. Look up “find, using operators and conditions” in GroupWise client Help.

F0xx File I/O error

Source: GroupWise engine; QuickFinder.

Explanation: The QuickFinder process used by the Find feature cannot access a required file.

Possible Cause: The QuickFinder index is damaged.

Action: Rebuild the index of the database where the error occurs. See “[Rebuilding Database Indexes](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: The disk is full where the QuickFinder index is located, so the QuickFinder process cannot write more information to disk.

Action: Free up disk space.

Possible Cause: You do not have rights to the location where the QuickFinder index is located.

Action: Check your access rights.

Action: In ConsoleOne[®], you can set the proper user rights for all users in a post office or for an individual user. See “[GroupWise User Rights](#)” in “[Security](#)” in the *GroupWise 7 Administration Guide*.

F0xx Database error

Source: GroupWise engine; QuickFinder.

Explanation: Generic database error.

Action: Check and, if necessary, repair the database. See “[Maintaining Domain and Post Office Databases](#)” and “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: If this error occurs on a message database (*msgnnn.db*) or user database (*userxxx.db*), run GWCheck. See “[Standalone Database Maintenance Programs](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

F0xx Database error (index)

Source: GroupWise engine; QuickFinder.

Explanation: Generic database error.

Action: Rebuild the index of the database where the error occurs. See “[Rebuilding Database Indexes](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

F0xx Memory error

Source: GroupWise engine; QuickFinder.

Explanation: Generic QuickFinder memory error.

Action: Exit and restart the GroupWise client.

Action: Free up more memory before running the GroupWise client.

F0xx Unexpected error

Source: GroupWise engine; QuickFinder.

Explanation: An engine error has occurred for which GroupWise does not have a specific error message.

Action: Exit and then restart the GroupWise client.

F1xx Cannot connect to remote server

Source: GroupWise engine; NetWare remote server connection table.

Explanation: GroupWise cannot connect to a remote server where needed information is located.


Possible Cause: The POA can no longer access the remote server where a document storage area is located.

Action: Make sure the remote server is running.

Action: Make sure the POA startup file contains the `/user` and `/password` or `/dn` startup switches so the POA can log in to the remote server. See “[Using POA Startup Switches](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

Action: In ConsoleOne, specify the login information in the Remote File Server Settings box on the Post Office Settings page of the Post Office object.

Action: Make sure the user the POA is logging in as has sufficient rights to access the needed location on the remote server. See “[Creating a NetWare Account for Agent Access \(Optional\)](#)” in “[Installing GroupWise Agents](#)” in the *GroupWise 7 Installation Guide*”.



Agent Error Messages

The GroupWise® agents are responsible for message transfer and delivery throughout your GroupWise system.

This part of *Troubleshooting 1: Error Messages* helps you resolve agent error messages that appear in agent log files and other places where agent status information is displayed.

- ◆ “Post Office Agent Error Messages” on page 169
- ◆ “Message Transfer Agent Error Messages” on page 181
- ◆ “Internet Agent Error Messages” on page 201
- ◆ “WebAccess Agent Error Messages” on page 207
- ◆ “Monitor Agent and Application Error Messages” on page 219

Other sources of assistance include:

- ◆ Novell® Support (<http://support.novell.com>)
- ◆ Novell Support Knowledgebase (http://support.novell.com/search/kb_index.jsp)
- ◆ GroupWise 7 Support Forums (<http://support.novell.com/forums/2gw.html>)
- ◆ Novell GroupWise Support Community (<http://support.novell.com/products/groupwise>)
- ◆ GroupWise Cool Solutions (<http://www.novell.com/coolsolutions/gwmag/index.html>)

Post Office Agent Error Messages

- “GWPOA: Admin database for post_office could not be recovered” on page 170
- “GWPOA: Administrator record not found in database” on page 170
- “GWPOA: Application connection table full” on page 170
- “GWPOA: Authentication failed for the above object” on page 170
- “GWPOA: Cannot access remote post office; retrying” on page 171
- “GWPOA: Cannot access remote post office; user ID switch is missing” on page 171
- “GWPOA: Cannot find the help file” on page 171
- “GWPOA: Client/server login failed; no user ID supplied” on page 171
- “GWPOA: Configured address may not match actual address” on page 171
- “GWPOA: Database language has been updated; please rebuild this database” on page 172
- “GWPOA: Disk is full; turning disk logging off” on page 172
- “GWPOA: Error creating...” on page 172
- “GWPOA: Error creating file; turning disk logging off” on page 172
- “GWPOA: Error initializing communications protocol” on page 172
- “GWPOA: Error initializing HTTP” on page 173
- “GWPOA: Error listening for connection” on page 173
- “GWPOA: Error opening listener port” on page 173
- “GWPOA: Error putting item in queue” on page 173
- “GWPOA: Error writing to file; turning disk logging off” on page 173
- “GWPOA: Failed to redirect user; missing host configuration” on page 174
- “GWPOA: File I/O error” on page 174
- “GWPOA: Host refused connection” on page 174
- “GWPOA: HTTP port nn is already in use” on page 174
- “GWPOA: Internal UDP port is unusable” on page 174
- “GWPOA: Listen port already in use” on page 175
- “GWPOA: Low disk space for QuickFinder indexing” on page 175
- “GWPOA: Machine appears to have TCP/IP incorrectly configured” on page 175
- “GWPOA: Not enough disk space for QuickFinder indexing” on page 175
- “GWPOA: Not enough memory to complete operation” on page 175
- “GWPOA: One or more connections to a remote storage area have been lost and could not be reestablished” on page 176
- “GWPOA: Physical connection table full” on page 176
- “GWPOA: Possibly damaged blob in database” on page 176
- “GWPOA: Possibly dangerous message; temporarily suspending dispatcher” on page 176
- “GWPOA: Reached inbound connections limit” on page 177
- “GWPOA: StartServiceCtrlDispatcher failed when attempting to start Windows_agent service” on page 177

- “GWPOA: The Windows_agent service fails to set service status; service stopped” on page 177
- “GWPOA: The Windows_agent service fails to initialize memory system; service stopped” on page 177
- “GWPOA: Timed out waiting for end-of-file confirmation” on page 177
- “GWPOA: Transport header build failed” on page 178
- “GWPOA: Unable to add additional message handler; maximum reached” on page 178
- “GWPOA: Unable to change all configuration options” on page 178
- “GWPOA: Unable to load viewer” on page 178
- “GWPOA: Unable to remove document storage area” on page 178

GWPOA: Admin database for *post_office* could not be recovered

- Source: GroupWise® Post Office Agent; admin thread.
- Explanation: An attempt to recover the post office database (*wphost.db*) has failed.
- Possible Cause: The post office database requires repair beyond what can be done while in use.
- Action: Rebuild the post office database. See “*Rebuilding Domain or Post Office Databases*” in “*Databases*” in the *GroupWise 7 Administration Guide*.

GWPOA: Administrator record not found in database

- Source: GroupWise Post Office Agent; admin thread.
- Explanation: The POA admin thread can send a message to an administrator in case of database errors. However, no administrator has been designated.
- Possible Cause: No GroupWise administrator has been set up yet.
- Action: Set up a GroupWise administrator to receive messages about database errors. See “*Notifying the GroupWise Administrator*” in “*Post Office Agent*” in the *GroupWise 7 Administration Guide*.
- Action: Use the */noerrormail* switch when starting the POA to turn off administrator messages.

GWPOA: Application connection table full

- Source: GroupWise Post Office Agent; TCP agent.
- Explanation: The POA is configured for TCP/IP communication and it has run out of application connections.
- Possible Cause: The POA is very busy.
- Action: Increase the number of application connections configured for the POA. See “*Adjusting the Number of Connections for Client/Server Processing*” in “*Post Office Agent*” in the *GroupWise 7 Administration Guide*. Then exit and restart the POA

GWPOA: Authentication failed for the above object

- Source: GroupWise Post Office Agent; admin thread.
- Explanation: The POA admin thread attempted to process a record that has the wrong authentication key for the current GroupWise system.
- Possible Cause: The record did not originate in the current GroupWise system, which is a possible security violation.
- Action: Someone is trying to tamper with your GroupWise system. Check your system security measures.

GWPOA: Cannot access remote post office; retrying

Source: GroupWise Post Office Agent.

Explanation: The POA can no longer access its post office.

Possible Cause: The server where the post office is located is currently down.

Action: Wait for the server to come back up, or contact the administrator of that server.

GWPOA: Cannot access remote post office; user ID switch is missing

Source: GroupWise Post Office Agent.

Explanation: The POA cannot access its post office because it cannot log in to the server where the post office is located.

Possible Cause: The POA has not been started with the /user or /dn switch.

Action: Include the /user and /password, or /dn switches when the POA needs to access a post office on a remote server. See “Using POA Startup Switches” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

Action: In ConsoleOne, specify the login information in the Remote File Server Settings box on the Post Office Settings page of the Post Office object.

GWPOA: Cannot find the help file

Source: GroupWise Post Office Agent for Windows.

Explanation: The Help file for the agent is not available.

Action: For the name of the Help file the agent is trying to use, see “Agent Installation Directories” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

GWPOA: Client/server login failed; no user ID supplied

Source: GroupWise Post Office Agent.

Explanation: The POA cannot communicate with a GroupWise client process that is requesting services because the client is not providing a user ID.

Possible Cause: The GroupWise client was not started with the needed user ID information.

Action: Use the /@u startup switch to make sure the client has the correct user ID information. See “Client” in the *GroupWise 7 Administration Guide*.

GWPOA: Configured address may not match actual address

Source: GroupWise Post Office Agent; TCP agent.

Explanation: The POA is configured for TCP/IP communication, but a mismatch of IP addresses has been detected.

Possible Cause: DNS is not currently available, so the POA is unable to resolve a host name into its IP address.

Action: Make sure DNS is functioning correctly. Or specify the IP address instead of the host name when configuring the POA.

Possible Cause: The POA was started with the wrong /name switch setting, so that it is associated with the wrong configuration information.

Action: Make sure the /name switch setting specifies the correct POA configuration.

Possible Cause: TCP/IP is not set up correctly on the server where the POA is running.

Action: Make sure TCP/IP is set up correctly.

GWPOA: Database language has been updated; please rebuild this database

Source: GroupWise Post Office Agent; admin thread.

Explanation: The post office database ([wphost.db](#)) needs to be rebuilt because the language has been changed, which changes the sort order of the users listed in the database.

Action: Rebuild the post office database. See [“Rebuilding Domain or Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

GWPOA: Disk is full; turning disk logging off

Source: GroupWise Post Office Agent.

Explanation: Logging information to disk has been turned off because there is insufficient disk space to continue writing to the agent log file. See [“Using POA Log Files”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

Action: Free up disk space. The agent should resume disk logging after disk space is available. To ensure that disk logging has resumed, check the Logging Level setting in the Log Settings page for the agent in ConsoleOne®.

Action: Specify a different location for log files where sufficient disk space is available.

GWPOA: Error creating...

Source: GroupWise Post Office Agent; TCP agent.

Explanation: The POA is configured for TCP/IP communication. The TCP agent might display a large number of error messages that begin with "Error creating...".

Possible Cause: Insufficient memory.

Action: See [“GWPOA: Not enough memory to complete operation”](#) on page 175.

GWPOA: Error creating file; turning disk logging off

Source: GroupWise agents.

Explanation: Logging information to disk has been turned off because the agent cannot create a new log file.

Possible Cause: The agent cannot create a file in the location specified by the Log File Path setting on the Log Settings page for the agent in ConsoleOne or specified on the command line using the [/log](#) startup switch. See [“Using POA Log Files”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

Action: Make sure the location exists or specify a more appropriate location.

Action: Make sure the agent has rights to create files in the specified location. Start the POA including the [/rights](#) switch to determine the specific problem the POA is encountering.

Action: Make sure there is available disk space in the specified location.

GWPOA: Error initializing communications protocol

Source: GroupWise Post Office Agent; TCP agent.

Explanation: The POA is configured for TCP/IP communication but is unable to establish TCP/IP communication.

Possible Cause: TCP/IP is not set up correctly on the server where the POA is running.

Action: Make sure TCP/IP is set up correctly.

GWPOA: Error initializing HTTP

Source: GroupWise Post Office Agent.

Explanation: The HTTP port the POA is trying to use for its Web console is not responding correctly.

Action: Configure the POA to communicate on a different HTTP port. See [“Using the POA Web Console”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

GWPOA: Error listening for connection

Source: GroupWise Post Office Agent; TCP agent.

Explanation: The POA is configured for TCP/IP communication but is unable to connect.

Possible Cause: TCP/IP is not set up correctly on the server where the POA is running.

Action: Make sure TCP/IP is set up correctly.

Possible Cause: Insufficient memory.

Action: See [“GWPOA: Not enough memory to complete operation”](#) on page 175.

GWPOA: Error opening listener port

Source: GroupWise Post Office Agent; TCP agent.

Explanation: The POA is configured for TCP/IP communication, but the port it is configured to listen on is already in use by another program.

Action: See [“8555 Port in use”](#) on page 26.

GWPOA: Error putting item in queue

Source: GroupWise Post Office Agent; TCP agent.

Explanation: The TCP threads are not keeping up with the current workload.

Action: Increase the number of TCP handler threads for the POA. See [“Adjusting the Number of Connections for Client/Server Processing”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

GWPOA: Error writing to file; turning disk logging off

Source: GroupWise Post Office Agent.

Explanation: Logging of information to disk has been turned off because the agent can no longer write to the current log file. See [“Using POA Log Files”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

Possible Cause: If the log file is located on a server other than the one where the agent is running, that server might be down.

Action: Wait for the server to come back up, or contact the administrator of that server. When the server comes back up, the agent will resume disk logging.

Possible Cause: The log file has been damaged so the agent can no longer write to it.

Action: Remove the damaged log file and turn disk logging back on in the Log Settings page for the agent in ConsoleOne. The agent will create a new log file. You can also use Cycle Log from the POA agent console to start a new log file.

GWPOA: Failed to redirect user; missing host configuration

Source: GroupWise Post Office Agent.

Explanation: The GroupWise client is attempting to contact the POA in client/server mode, but the POA is not set up for client/server communication.

Action: Set up the POA for client/server communication. See [“Using Client/Server Access to the Post Office”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

GWPOA: File I/O error

Source: GroupWise Post Office Agent.

Explanation: The POA cannot access a required file.

Possible Cause: The POA cannot read its startup file.

Action: Check the existence, integrity, and rights of the POA startup file specified in the command to start the POA. See [“Installing and Starting the POA”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

Possible Cause: The POA cannot view its log file.

Action: Check the existence, integrity, and rights of the POA log file. See [“Using POA Log Files”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

GWPOA: Host refused connection

Source: GroupWise Post Office Agent; message transfer protocol.

Explanation: The POA is configured to communicate with the MTA by way of TCP/IP. The server where the MTA is located has refused the POA’s request for a connection.

Action: Check the TCP/IP configuration of the server to which the POA must connect.

GWPOA: HTTP port *nn* is already in use

Source: GroupWise Post Office Agent.

Explanation: The HTTP port the POA is trying to use for its Web console is already in use by another program.

Action: Configure the POA to communicate on a different HTTP port. See [“Using the POA Web Console”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

GWPOA: Internal UDP port is unusable

Source: GroupWise Post Office Agent; TCP agent.

Explanation: The POA is configured for TCP/IP communication but it cannot access the UDP port of the server where it is trying to run.

Possible Cause: TCP/IP is not set up correctly on the server where the POA is running.

Action: Make sure TCP/IP is set up correctly.

GWPOA: Listen port already in use

Source: GroupWise Post Office Agent; TCP agent.

Explanation: The POA is configured for TCP/IP communication, but the port it is configured to listen on is already in use by another program.

Action: See [“8555 Port in use” on page 26](#).

GWPOA: Low disk space for QuickFinder indexing

Source: GroupWise Post Office Agent.

Explanation: The POA requires at least 20 MB of free disk space to perform QuickFinder™ indexing. This warning appears when disk space drops below 30 MB. The POA performs QuickFinder indexing as specified by the QuickFinder Update Interval setting on the POA Agent Settings page in ConsoleOne or as specified using the `/qfinterval` startup switch. See [“Regulating Indexing” in “Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

Action: Free up disk space on the server where the POA is running to eliminate the warning. See [“Managing Database Disk Space” in “Databases”](#) in the *GroupWise 7 Administration Guide*.

GWPOA: Machine appears to have TCP/IP incorrectly configured

Source: GroupWise Post Office Agent; TCP agent.

Explanation: The POA is configured for TCP/IP communication but it is unable to determine the IP address of the server where it is trying to run.

Possible Cause: TCP/IP is not set up correctly on the server where the POA is running.

Action: Make sure TCP/IP is set up correctly, including assignment of an IP address.

GWPOA: Not enough disk space for QuickFinder indexing

Source: GroupWise Post Office Agent.

Explanation: The POA requires at least 20 MB of free disk space to perform QuickFinder indexing. A warning appears when disk space drops below 30 MB. This error appears when free disk space drops below 20 MB. The POA performs QuickFinder indexing as specified by the QuickFinder Update Interval setting on the POA Agent Settings page in ConsoleOne or as specified using the `/qfinterval` startup switch. See [“Regulating Indexing” in “Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

Action: Make sure sufficient free disk space is available on the server where the POA is running by the next time the POA needs to perform QuickFinder indexing.

GWPOA: Not enough memory to complete operation

Source: GroupWise Post Office Agent.

Explanation: Not enough memory is available for the POA to function properly.

Possible Cause: If the POA cannot start, you might be trying to run the agent in an environment where too few system resources are available. For information about POA memory requirements, see [“GroupWise System Requirements” in “Installing GroupWise Agents”](#) in the *“GroupWise 7 Installation Guide”*.

Action: Stop some other programs on the server to free up memory for use by the POA.

Action: Add memory to the server to accommodate the POA along with other existing programs.

Action: Select a different server to run the POA on, where adequate resources are available.

Possible Cause: If the POA starts successfully, then encounters a memory error later during otherwise normal processing, some other program on the server, or another agent thread, might have temporarily used a large quantity of memory.

Action: Wait to see if the memory problem resolves itself. The POA will retry its operations and should succeed at a later time, when the other program has released some memory.

Action: You can reduce the number of POA threads, which reduces the memory requirements for the POA. You can make the change in ConsoleOne by reducing the Message Handler Threads and/or TCP Handler Threads settings in the POA Agent Settings page. See “[Adjusting the Number of POA Threads for Message File Processing](#)” and “[Adjusting the Number of Connections for Client/Server Processing](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

Action: If the POA starts successfully but frequently encounters memory errors during later processing, treat the situation as if the POA cannot start and see the recommended actions above.

GWPOA: One or more connections to a remote storage area have been lost and could not be reestablished

Source: GroupWise Post Office Agent.

Explanation: The POA has lost its connection to the server where a document storage area is located.

Possible Cause: The server where the document storage area is located is down.

Action: Wait for the server to come back up. The POA will reconnect automatically when the server is available again.

Action: Contact the administrator of that server.

GWPOA: Physical connection table full

Source: GroupWise Post Office Agent; TCP agent.

Explanation: The POA is configured for TCP/IP communication and it has run out of physical connections.

Possible Cause: The POA is very busy.

Action: Increase the number of physical connections configured for the POA. See “[Adjusting the Number of Connections for Client/Server Processing](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*. Then exit and restart the POA

GWPOA: Possibly damaged blob in database

Source: GroupWise Post Office Agent

Explanation: During indexing, the POA has encountered a BLOB file that it could not process.

Possible Cause: The BLOB file is damaged

Action: Restore the BLOB file from backup.

Action: If the damaged BLOB file cannot be restored, you can delete it to eliminate the error.

GWPOA: Possibly dangerous message; temporarily suspending dispatcher

Source: GroupWise Post Office Agent

Explanation: No additional message file processor threads will be started until processing of the current message file has completed. The current message file is flagged as having caused the POA to shut down in a previous processing attempt.

Possible Cause: The current message file is damaged.

Action: If all existing message file processor threads successfully process their message files, the POA will resume normal processing. No action is necessary.

Action: If processing of a message file causes the POA to shutdown, do not put message files from the *post_office\wpcsout\problem* directory back into the POA input queue. Restart the POA.

GWPOA: Reached inbound connections limit

Source: GroupWise Post Office Agent; message transfer protocol.

Explanation: The POA is configured to communicate with the MTA by way of TCP/IP. The POA has reached the maximum number of inbound connections.

Action: None. Connections are automatically released and reopened as processing continues.

GWPOA: StartServiceCtrlDispatcher failed when attempting to start *Windows_agent* service

Source: GroupWise Post Office Agent for Windows.

Explanation: The Windows POA cannot start its dispatcher thread.

Possible Cause: The Windows server is not functioning properly.

Action: Reboot the Windows server.

GWPOA: The *Windows_agent* service fails to set service status; service stopped

Source: GroupWise Post Office Agent for Windows.

Explanation: The Windows POA cannot start as a service.

Possible Cause: The Windows POA cannot communicate with the service control manager (SCM).

Action: Reboot the Windows server.

GWPOA: The *Windows_agent* service fails to initialize memory system; service stopped

Source: GroupWise Post Office Agent for Windows.

Explanation: The Windows POA cannot start as a service.

Possible Cause: The Windows POA has insufficient memory resources.

Action: Reboot the Windows server.

Action: Run fewer programs on the server.

GWPOA: Timed out waiting for end-of-file confirmation

Source: GroupWise Post Office Agent; message transfer protocol.

Explanation: The POA is configured to communicate with the MTA by way of TCP/IP. The MTA has stopped responding in the middle of a communication.

Possible Cause: The MTA is running on an overburdened server, so it cannot respond to the POA in a timely manner.

Action: Add resources to the MTA server so that the MTA can function properly.

Action: Move the MTA to a different server where more resources are available. See “[Moving the MTA to a Different Server](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: The server where the MTA is running has gone down.

Action: Check the status of the MTA server. Reboot if necessary.

GWPOA: Transport header build failed

Source: GroupWise Post Office Agent; message transfer protocol.

Explanation: The POA is configured to communicate with the MTA by way of TCP/IP. The POA was unable to create a packet of information to send to the MTA.

Possible Cause: Insufficient memory.

Action: See “[GWPOA: Not enough memory to complete operation](#)” on page 175.

GWPOA: Unable to add additional message handler; maximum reached

Source: GroupWise Post Office Agent.

Explanation: The maximum number of message handler threads for the POA is 32. You cannot create any more message handler threads for this POA.

Action: You can run another POA for the post office on the same server if the server has sufficient resources.

You can run another POA for the post office on a different server if your network can handle the additional traffic.

See “[Configuring a Dedicated Message File Processing POA](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

GWPOA: Unable to change all configuration options

Source: GroupWise Post Office Agent.

Explanation: POA configuration settings have been changed in ConsoleOne, but some cannot be put into effect until the POA is restarted.

Action: Exit and restart the POA.

GWPOA: Unable to load viewer

Source: GroupWise Post Office Agent for Windows.

Explanation: The POA cannot run the program used to view agent log files or edit agent startup files.

Possible Cause: The viewer program is not available on the current path or is incorrectly specified.

Action: The default viewer used by the POA is Notepad, which is typically available. You can change the viewer specification by selecting View Log Files in the Windows POA agent console and changing the information in the Viewer field. Check the viewer and path specified in the View Log Files dialog box in the POA agent console.

GWPOA: Unable to remove document storage area

Source: GroupWise Post Office Agent.

Explanation: The POA cannot delete the document storage area.

Possible Cause: The library database (**dmsb.db**) is damaged, so that the POA cannot read the information necessary to delete the storage area.

Action: Repair the library. See “**Maintaining Library Databases and Documents**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

Message Transfer Agent Error Messages

- “GWMTA: Access denied” on page 182
- “GWMTA: Admin database for domain cannot be recovered” on page 183
- “GWMTA: Administrator record not found in database” on page 183
- “GWMTA: Authentication failure for the above object” on page 183
- “GWMTA: Cannot attach to server or volume” on page 183
- “GWMTA: Cannot create a new receiver thread” on page 184
- “GWMTA: Cannot create/read/write files/directories” on page 184
- “GWMTA: Cannot find domain database” on page 184
- “GWMTA: Cannot find startup file” on page 185
- “GWMTA: Cannot move files” on page 185
- “GWMTA: Cannot proceed; incompatible GWENN5.NLM” on page 185
- “GWMTA: Cannot proceed; insufficient memory available” on page 185
- “GWMTA: Cannot read domain database; insufficient memory” on page 185
- “GWMTA: Cannot read post office database; insufficient memory” on page 186
- “GWMTA: Cannot route message(s); out of memory” on page 186
- “GWMTA: Cannot start server; insufficient memory available” on page 186
- “GWMTA: Closed for inbound traffic” on page 186
- “GWMTA: Command line parameter /home is required” on page 186
- “GWMTA: Could not launch the editor” on page 187
- “GWMTA: Database language has been updated; please rebuild this database” on page 187
- “GWMTA: Disk full; disk logging turned off” on page 187
- “GWMTA: Domain database error; circular transfer domain link” on page 187
- “GWMTA: Domain database error; transfer domain not found” on page 187
- “GWMTA: Domain database open failed” on page 188
- “GWMTA: Domain database read error” on page 188
- “GWMTA: Domain now closed” on page 188
- “GWMTA: Domain open failed” on page 188
- “GWMTA: Error initializing HTTP” on page 189
- “GWMTA: Error validating post office members” on page 189
- “GWMTA: Expired en route to destination” on page 189
- “GWMTA: File create error; disk logging turned off” on page 189
- “GWMTA: File write error; disk logging turned off” on page 189
- “GWMTA: File not found” on page 190
- “GWMTA: Gateway now closed” on page 190
- “GWMTA: Gateway open failed” on page 190
- “GWMTA: Host refused connection” on page 190
- “GWMTA: IDomain now closed” on page 190

“GWMTA: Incompatible GWENVIA.DLL; GWMTA cannot continue” on page 191
“GWMTA: Insufficient disk space” on page 191
“GWMTA: Insufficient memory” on page 191
“GWMTA: Insufficient memory to read/process startup file” on page 192
“GWMTA: Internet mail to address is undeliverable because no default GWIA is configured” on page 192
“GWMTA: Invalid /log parameter” on page 192
“GWMTA: Invalid /work parameter” on page 193
“GWMTA: Link or transport down” on page 193
“GWMTA: Logging permanently suspended; insufficient memory” on page 193
“GWMTA: Login not completed; timeout” on page 194
“GWMTA: Login to directory failed” on page 194
“GWMTA: Maximum number of inbound connections reached” on page 194
“GWMTA: No agent record found” on page 194
“GWMTA: No domain record found” on page 195
“GWMTA: No path configured” on page 195
“GWMTA: No post offices found” on page 195
“GWMTA: No response from peer” on page 195
“GWMTA: No sender IDomain; Internet address lookup not attempted” on page 195
“GWMTA: Path to domain database (/home) is invalid or blocked” on page 196
“GWMTA: Post office database open failed; insufficient memory” on page 196
“GWMTA: Post office database read error” on page 196
“GWMTA: Post office now closed” on page 196
“GWMTA: Post office open failed” on page 197
“GWMTA: Received unsupported request; request ignored” on page 197
“GWMTA: StartServiceCtrlDispatcher failed when attempting to start Windows_agent service” on page 197
“GWMTA: Target queue temporarily locked” on page 197
“GWMTA: The Windows_agent service fails to set service status; service stopped” on page 197
“GWMTA: The Windows_agent service fails to initialize memory system; service stopped” on page 197
“GWMTA: Timed out waiting for end-of-file confirmation” on page 198
“GWMTA: Unable to initialize message log database” on page 198
“GWMTA: Unable to open connection; no response” on page 198
“GWMTA: Unable to register with SNMP agent” on page 198
“GWMTA: Unable to retrieve TCP/IP address” on page 198
“GWMTA: Undefined link” on page 199
“GWMTA: Unknown connection header received” on page 199
“GWMTA: Unknown destination” on page 199
“GWMTA: Waiting for busy listen socket to become available” on page 199

GWMTA: Access denied

Source: GroupWise® Message Transfer Agent; last closure reason.

Explanation: A domain or post office is closed because the MTA cannot access the database (**wppdomain.db** or **wpphost.db**) at the location.

Possible Cause: An MTA is already running against the domain database.

Action: Do not try to run more than one MTA for a domain.

GWMTA: Admin database for *domain* cannot be recovered

Source: GroupWise Message Transfer Agent; admin thread.

Explanation: An attempt to recover the domain database (**wpdomain.db**) has failed.

Possible Cause: The domain database requires repair beyond what can be done while in use.

Action: Rebuild the domain database. See “**Rebuilding Domain or Post Office Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

GWMTA: Administrator record not found in database

Source: GroupWise Message Transfer Agent; admin thread.

Explanation: The MTA admin thread can send a message to an administrator in case of database errors. However, no administrator has been designated.

Possible Cause: No GroupWise administrator has been set up yet.

Action: Set up a GroupWise administrator to receive messages about database errors. See “**Notifying the Domain Administrator**” in “**Message Transfer Agent**” in the *GroupWise 7 Administration Guide*.

Action: Use the **/noerrormail** switch when starting the MTA to turn off administrator messages.

GWMTA: Authentication failure for the above object

Source: GroupWise Message Transfer Agent; admin thread.

Explanation: The MTA admin thread attempted to process a record that has the wrong authentication key for the current GroupWise system.

Possible Cause: The record did not originate in the current GroupWise system, which is a possible security violation.

Action: Someone is trying to tamper with your GroupWise system. Check your system security measures.

GWMTA: Cannot attach to server or volume

Source: GroupWise Message Transfer Agent; last closure reason.

Explanation: A domain or post office is closed because the NetWare[®] MTA cannot access the server or volume where the domain or post office is located.

Possible Cause: The domain or post office is located on a different server from where the MTA is running and the MTA has not been configured with user information to enable it to log in.

Action: Make sure the MTA startup file includes the **/user** and **/password**, or **/dn** switches, so the MTA can log into the remote server. Make sure the user and password information is correct and current. Make sure the information is formatted correctly. In some configurations, you might need to specify a distinguished name (for example, *user.org_unit.org*) for the **/user** switch, rather than just a simply user ID. In some configurations, you might need to include the type (for example, *.CN=user.org_unit.org*).

Action: If the MTA still cannot log in to the remote server after appropriate user information has been supplied, start the MTA with **/tracelogin-2** to display NetWare error codes. Look up the error codes at [Novell Error Codes \(http://www.novell.com/documentation/nwec/index.html\)](http://www.novell.com/documentation/nwec/index.html).

Possible Cause: The NetWare MTA cannot log into the server where a domain or post office is located because all available NetWare licenses are already in use.

Action: Increase the number of licenses on the server.

GWMTA: Cannot create a new receiver thread

Source: GroupWise Message Transfer Agent; message transfer protocol.

Explanation: The MTA cannot create a new receiver thread.

Possible Cause: Insufficient memory.

Action: See [“GWMTA: Insufficient memory” on page 191](#).

GWMTA: Cannot create/read/write files/directories

Source: GroupWise Message Transfer Agent; last closure reason.

Explanation: A domain or post office is closed because the MTA cannot write files into its output queue in the closed domain or post office.

Possible Cause: The user specified with the `/user` switch in the MTA startup file does not have sufficient rights to create files in the domain or post office directory.

Action: Make sure the user the MTA is logging in as has sufficient rights in the domain or post office directory. See [“Creating a NetWare Account for Agent Access \(Optional\)”](#) in [“Installing GroupWise Agents”](#) in the *“GroupWise 7 Installation Guide”*.

Possible Cause: The MTA cannot write message files across a mapped or UNC link into the MTA input queue in a closed domain (`domain\wpcsin` directory) or a closed post office (`post_office\wpcout` directory) because the directory is inaccessible or damaged.

Action: Make sure the input queue directory exists and that the MTA has sufficient rights to create files there. If necessary, and if the input queue subdirectories are empty, you can rename the original input queue directory and then manually recreate it, along with its required subdirectories.

Possible Cause: The server where the closed domain or post office is located does not have sufficient disk space for the MTA to create message files.

Action: Free up disk space.

NetWare Note: On a NetWare server, you might need to purge deleted files to free up disk space.

Possible Cause: The name of the domain directory contains more than 8 characters.

Action: Rename the domain directory. The MTA currently does not support long names. Also update the domain directory path in ConsoleOne®.

Possible Cause: The network type specified for the domain is incorrect.

Action: Check the network type selected for the domain. In ConsoleOne, right-click the Domain object, then click Properties. Make sure the Network Type field is correct for the MTA running for the domain.

GWMTA: Cannot find domain database

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot access a domain database (`wpdomain.db`) in the directory specified by the `/home` switch.

Possible Cause: The MTA has been able to access the directory specified by the /home switch, but it cannot locate a valid domain database in that directory.

Action: Make sure the location provided by the /home startup switch specifies a valid domain directory. See “Using MTA Startup Switches” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

GWMTA: Cannot find startup file

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot start because it cannot locate or read its startup file.

Possible Cause: The name of the startup file as provided in the command to start the MTA is incorrect.

Action: Make sure you are providing the name of the startup file correctly. See “Installing and Starting the MTA” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

Possible Cause: The startup file is not located on the current path.

Action: Specify the full path to the startup file in the command to start the MTA.

GWMTA: Cannot move files

Source: GroupWise Message Transfer Agent; last closure reason.

Explanation: The MTA cannot move message files from its input queue (*domain\wpcsin* or *post_office\wpcsin*) to its in progress" queue (*gwinprog*).

Explanation: Insufficient disk space on the server where the *mslocal* directory structure is located.

Action: Free up disk space so the MTA has sufficient space to process message files.

GWMTA: Cannot proceed; incompatible GWENN5.NLM

Source: NetWare GroupWise Message Transfer Agent.

Explanation: The MTA cannot start because the agent engine (*gwenn5.nlm*) is not compatible with the MTA itself (*gwmta.nlm*).

Possible Cause: Some agent files have been updated but the update is not complete.

Action: When updating the agents, make sure all agent files are installed. For a complete list of files, see “Agent Installation Directories” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

Possible Cause: The agent engine (*gwenn5.nlm*) was not unloaded prior to updating the agent software. The agent software cannot be successfully updated if the agent engine is still loaded.

Action: After exiting all the agents, unload the *gwenn5.nlm*, then perform the update. See the “Updating Secondary Domains” in “Updating Your GroupWise 6.x System to Version 7” in the *GroupWise 7 Installation Guide*.

GWMTA: Cannot proceed; insufficient memory available

Source: GroupWise Message Transfer Agent.

Action: See “GWMTA: Insufficient memory” on page 191.

GWMTA: Cannot read domain database; insufficient memory

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot access its domain database ([wpdomain.db](#)).

Possible Cause: Insufficient memory.

Action: See [“GWMTA: Insufficient memory” on page 191](#).

Possible Cause: The domain database has been damaged.

Action: Rebuild the domain database. See [“Rebuilding Domain or Post Office Databases” in “Databases” in the *GroupWise 7 Administration Guide*](#).

GWMTA: Cannot read post office database; insufficient memory

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot access the post office database ([wphost.db](#)).

Possible Cause: Insufficient memory.

Action: See [“GWMTA: Insufficient memory” on page 191](#).

Possible Cause: The post office database has been damaged.

Action: Rebuild the post office database. See [“Rebuilding Domain or Post Office Databases” in “Databases” in the *GroupWise 7 Administration Guide*](#).

GWMTA: Cannot route message(s); out of memory

Source: GroupWise Message Transfer Agent.

Action: See [“GWMTA: Insufficient memory” on page 191](#).

GWMTA: Cannot start server; insufficient memory available

Source: GroupWise Message Transfer Agent.

Action: See [“GWMTA: Insufficient memory” on page 191](#).

GWMTA: Closed for inbound traffic

Source: GroupWise Message Transfer Agent.

Explanation: The MTA is not accepting inbound connections on its TCP/IP link.

Possible Cause: The MTA has been manually suspended.

Action: Resume the MTA for the domain. See [“Suspending/Resuming MTA Processing for a Location” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*](#).

Possible Cause: If you are running multiple MTAs on the same server, the same TCP port might be in use by more than one MTA.

NetWare Note: On a NetWare server, you would see the message "Waiting for busy listen socket to become available."

Action: Check the setup of the MTAs. Make sure each MTA is using a unique port. See [“Configuring the MTA for TCP/IP” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*](#).

GWMTA: Command line parameter /home is required

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot start without a /home switch specifying the domain directory.

Possible Cause: The **/home** switch has not been provided in the command to start the MTA.

Action: Add the **/home** switch to the command to start the MTA. See **“Using MTA Startup Switches”** in **“Message Transfer Agent”** in the *GroupWise 7 Administration Guide*.

Possible Cause: The agent was not able to access the startup file where the **/home** switch was specified.

Action: Make sure the startup file exists.

GWMTA: Could not launch the editor

Source: GroupWise Message Transfer Agent for Windows.

Explanation: The MTA cannot run the program used to view agent log files or edit agent startup files.

Possible Cause: The viewer program is not available on the current path or is incorrectly specified.

Action: The default viewer used by the agents is Notepad, which is typically available. You can change the viewer specification by selecting View Log Files in the agent window and changing the information in the Viewer field. Check the viewer and path specified in the View Log Files dialog box in the agent window.

GWMTA: Database language has been updated; please rebuild this database

Source: GroupWise Message Transfer Agent; admin thread.

Explanation: The database needs to be rebuilt because the language has been changed, which changes the sort order of the users listed in the database.

Action: Rebuild the database. See **“Rebuilding Domain or Post Office Databases”** in **“Databases”** in the *GroupWise 7 Administration Guide*.

GWMTA: Disk full; disk logging turned off

Source: GroupWise Message Transfer Agent.

Explanation: Logging information to disk has been turned off because there is insufficient disk space to continue writing to the agent log file.

Action: Free up disk space. The agent should resume disk logging after disk space is available. To ensure that disk logging has resumed, check the Logging Level setting in the Log Settings page for the MTA in ConsoleOne. See **“Using MTA Log Files”** in **“Message Transfer Agent”** in the *GroupWise 7 Administration Guide*.

Action: Specify a different location for log files where sufficient disk space is available.

GWMTA: Domain database error; circular transfer domain link

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot route a message to the domain it is addressed to because available indirect links create a circular reference.

Possible Cause: Links between domains in your GroupWise system are not set up correctly.

Action: Check, and if necessary, adjust the indirect links between domains in your GroupWise system. See **“Editing a Domain Link”** in **“Domains”** in the *GroupWise 7 Administration Guide*.

GWMTA: Domain database error; transfer domain not found

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot locate the domain to which a message is addressed, nor can it locate an indirect link to that domain.

Possible Cause: Links between domains in your GroupWise system are not set up correctly.

Action: Check, and if necessary adjust, the indirect links between domains in your GroupWise system. See [“Link Configuration between Domains and Post Offices”](#) in [“Domains”](#) in the *GroupWise 7 Administration Guide*.

GWMTA: Domain database open failed

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot access the domain database (`wpdomain.db`).

Possible Cause: The domain database has been damaged.

Action: Rebuild the domain database. See [“Rebuilding Domain or Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

GWMTA: Domain database read error

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot access its domain database (`wpdomain.db`).

Possible Cause: The domain database has been damaged.

Action: Rebuild the domain database. See [“Rebuilding Domain or Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

GWMTA: Domain now closed

Source: GroupWise Message Transfer Agent.

Explanation: The MTA has lost its connection to a domain with which it could previously communicate.

Possible Cause: The server where the domain is located is currently down.

Action: Wait for the server to come back up, or contact the administrator of that server.

Possible Cause: If using TCP/IP communication between domains, TCP/IP might be down.

Action: Make sure TCP/IP is running in both domains.

GWMTA: Domain open failed

Source: GroupWise Message Transfer Agent.

Explanation: The MTA in the local domain cannot contact the MTA in a different domain in your GroupWise system.

Possible Cause: Links between the domains are not set up correctly.

Action: Check the links between the domains. See [“Editing a Domain Link”](#) in [“Domains”](#) in the *GroupWise 7 Administration Guide*.

Possible Cause: The local MTA cannot access the MTA input queue in the other domain.

Action: Check the directory structure of the closed domain. See [“Domain Directory”](#) in [“Directory Structure Diagrams”](#) in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

GWMTA: Error initializing HTTP

Source: GroupWise Message Transfer Agent.

Explanation: The HTTP port the MTA is trying to use for its Web console is not responding correctly.

Action: Configure the MTA to communicate on a different HTTP port. See “Using the MTA Web Console” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

GWMTA: Error validating post office members

Source: GroupWise Message Transfer Agent, Novell® eDirectory™ user synchronization.

Explanation: When attempting eDirectory user synchronization, the MTA could not access the user information stored in eDirectory.

Action: Look up the NetWare error code that accompanies this error at [Novell Error Codes \(http://www.novell.com/documentation/nwec/index.html\)](http://www.novell.com/documentation/nwec/index.html).

Possible Cause: The MTA does not have sufficient rights to access the user information in eDirectory.

Action: Make sure the MTA is properly set up to perform eDirectory user synchronization. See “Using eDirectory User Synchronization” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

GWMTA: Expired en route to destination

Source: GroupWise Message Transfer Agent.

Explanation: The MTA was unable to deliver a message because it passed through the maximum of 15 hops without reaching its destination.

Possible Cause: Links between domains are not set up correctly.

Action: Check the links between domains. Look for a more efficient route. See “Link Configuration between Domains and Post Offices” in “Domains” in the *GroupWise 7 Administration Guide*.

GWMTA: File create error; disk logging turned off

Source: GroupWise Message Transfer Agent.

Explanation: Logging information to disk has been turned off because the MTA cannot create a new log file.

Possible Cause: The agent cannot create a file in the location specified by the Log File Path setting on the Log Settings page for the agent in ConsoleOne or specified on the command line using the `/log` startup switch. See “Using MTA Log Files” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

Action: Make sure the location exists or specify another location.

Action: Make sure the agent has rights to create files in the specified location.

Action: Make sure there is available disk space in the specified location.

GWMTA: File write error; disk logging turned off

Source: GroupWise agents.

Explanation: Logging information to disk has been turned off because the agent can no longer write to the current log file.

Possible Cause: If the log file is located on a server other than the one where the agent is running, that server might be down.

Action: Wait for the server to come back up, or contact the administrator of that server. When the server comes back up, the agent will resume disk logging.

Possible Cause: The log file has been damaged so the agent can no longer write to it.

Action: Remove the damaged log file and turn disk logging back on in the Log Settings page for the agent in ConsoleOne. See “Using MTA Log Files” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*. The agent will create a new log file.

You can also use Cycle Log from the MTA agent console to start a new log file. See “Cycling the MTA Log File” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

GWMTA: File not found

Source: GroupWise Message Transfer Agent; agent console

Explanation: From the MTA agent console, you are trying to edit or view either the MTA log file or startup file and the MTA cannot access it.

Action: Verify the existence and rights to the file.

GWMTA: Gateway now closed

Source: GroupWise Message Transfer Agent.

Explanation: The MTA has lost its connection to a gateway with which it could previously communicate

Possible Cause: The server where the gateway is located is currently down.

Action: Wait for the server to come back up, or contact the administrator of that server.

GWMTA: Gateway open failed

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot contact a gateway to which a message needs to be routed.

Possible Cause: The MTA cannot access the gateway input queue under the **wpgate** directory of the domain.

Action: Check the directory structure of the closed Internet gateway.

GWMTA: Host refused connection

Source: GroupWise Message Transfer Agent.

Explanation: The MTA is configured to communicate with another MTA or a POA by way of TCP/IP. The server where the other MTA or the POA is located has refused the MTA's request for a connection.

Action: Check the TCP/IP configuration of the server to which the MTA must connect.

GWMTA: IDomain now closed

Source: GroupWise Message Transfer Agent.

Explanation: The MTA has lost its connection to a domain across the Internet with which it could previously communicate.

Possible Cause: The server where the domain is located is currently down.

Action: Wait for the server to come back up, or contact the administrator of that server.

Action: Make sure the Internet link between domains is set up correctly. See “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

GWMTA: Incompatible GWENV1A.DLL; GWMTA cannot continue

Source: GroupWise Message Transfer Agent for Windows.

Explanation: The MTA cannot start because the agent engine ([gwenv1a.exe](#)) is not compatible with the MTA itself ([gwmta.exe](#)).

Possible Cause: Some agent files have been updated but the update is not complete.

Action: When updating the agents, make sure all agent files are installed. For a complete list, see “[Agent Installation Directories](#)” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

GWMTA: Insufficient disk space

Source: GroupWise Message Transfer Agent.

Explanation: The MTA does not have sufficient disk space to write files into its input queues or holding queues. The MTA requires at least 1 MB of free disk space to run.

Possible Cause: One or more locations are closed, resulting in a backlog of messages in the MTA holding queues in the directory.

Action: Resolve the problems with the closed facilities so that normal message flow resumes. See “[MTA Status Box Shows a Closed Location](#)” in *GroupWise 7 Troubleshooting 2: Solutions to Common Problems*.

Possible Cause: Other programs running the same server with the MTA have used up all available disk space.

Action: Free up disk space so the MTA can continue processing messages. Check the MTA log file to see which queue the MTA can no longer write to so you know where more disk space is required. See “[Using MTA Log Files](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: The MTA cannot write message files across a mapped or UNC link into the MTA input queue in a closed domain ([domain\wpcsin](#) directory) or a closed post office ([post_office\wpcsin](#) directory) because the directory is damaged.

Action: If the input queue subdirectories are empty, you can rename the original input queue directory and then manually re-create it, along with its required subdirectories.

GWMTA: Insufficient memory

Source: GroupWise Message Transfer Agent.

Explanation: Not enough memory is available for the MTA to function properly.

Possible Cause: If the MTA cannot start, you might be trying to run the MTA in an environment where too few system resources are available.

Action: For requirements, see “[GroupWise System Requirements](#)” in “[Installing GroupWise Agents](#)” in the “[GroupWise 7 Installation Guide](#)”.

Action: Stop some other programs on the server to free up memory for use by the MTA.

Action: Add memory to the server to accommodate the MTA along with other existing programs.

Action: Select a different server to run the MTA on, where adequate resources are available. See “[Moving the MTA to a Different Server](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.

- Possible Cause: If the MTA starts successfully, then encounters a memory error later during otherwise normal processing, some other program on the server, or another agent thread, might have temporarily used a large quantity of memory.
- Action: Wait to see if the memory problem resolves itself. The MTA will retry its operation and should succeed at a later time, when the other program has released some memory.
- Action: If the MTA starts successfully but frequently encounters memory errors during later processing, treat the situation as if the MTA cannot start and see the recommended actions above.

GWMTA: Insufficient memory to read/process startup file

Source: GroupWise Message Transfer Agent.

Possible Cause: Insufficient memory.

Action: See [“GWMTA: Insufficient memory” on page 191](#).

GWMTA: Insufficient resources to accept inbound connection

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot start a receiver thread.

Possible Cause: Insufficient memory.

Action: If the problem does not resolve itself in a short time, see [“GWMTA: Insufficient memory” on page 191](#).

GWMTA: Insufficient system resources

Source: GroupWise Message Transfer Agent.

Explanation: The MTA was unable to start another thread.

Possible Cause: Insufficient memory.

Action: If the problem does not resolve itself in a short time, see [“GWMTA: Insufficient memory” on page 191](#).

GWMTA: Internet mail to *address* is undeliverable because no default GWIA is configured

Source: GroupWise Message Transfer Agent.

Explanation: A message addressed to a user across the Internet cannot be delivered.

Possible Cause: A default GroupWise Internet Agent has not been configured.

Action: Designate a default Internet Agent. See [“Configuring Internet Addressing”](#) in [“System”](#) in the *GroupWise 7 Administration Guide*.

GWMTA: Invalid /log parameter

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot use the location specified by the `/log` startup switch to store its log files.

Possible Cause: The location specified by the `/log` startup switch does not exist.

Action: Check, and if necessary change, the location specified by the `/log` startup switch when starting the MTA. If the `/log` switch is not specified, it defaults to the `mslocal` directory in the directory specified by the `/work` switch.

- Possible Cause: The location specified by the /log startup switch is on a server that is currently not available.
- Action: Check the status of the server where the specified directory is located. Wait for the server to come back up or contact the administrator of that server.
- Action: It is recommended that the /log switch be set to a location local to where the MTA is running to avoid this problem.

GWMTA: Invalid /work parameter

- Source: GroupWise Message Transfer Agent.
- Explanation: The MTA cannot use the location specified by the /work startup switch for its **mslocal** directory.
- Possible Cause: The location specified by the /work startup switch does not exist.
- Action: Check, and if necessary change, the location specified by the /work startup switch when starting the MTA. If the /work switch is not specified, it defaults to the domain directory. See [“Using MTA Startup Switches”](#) in [“Message Transfer Agent”](#) in the *GroupWise 7 Administration Guide*.
- Possible Cause: The location specified by the /work startup switch is on a server that is currently not available.
- Action: Check the status of the server where the specified directory is located. Wait for the server to come back up or contact the administrator of that server.
- Action: It is recommended that the /work switch be set to a location local to where the MTA is running to avoid this problem.

GWMTA: Link or transport down

- Source: GroupWise Message Transfer Agent.
- Explanation: The MTA is using TCP/IP to communicate with an MTA or POA and the other agent is not responding.
- Possible Cause: The MTA in the other domain is not properly set up for TCP/IP communication.
- Action: Check the setup of the MTA in the other domain. See [“Using TCP/IP Links between Domains”](#) in [“Message Transfer Agent”](#) in the *GroupWise 7 Administration Guide*.
- Possible Cause: The POA in the post office is not properly set up for TCP/IP communication.
- Action: Check the setup of the POA. See [“Using TCP/IP Links between a Domain and its Post Offices”](#) in [“Message Transfer Agent”](#) in the *GroupWise 7 Administration Guide*.

GWMTA: Logging permanently suspended; insufficient memory

- Source: GroupWise Message Transfer Agent.
- Explanation: The MTA could not start a new thread for disk logging. Therefore, disk logging has been turned off.
- Possible Cause: Insufficient memory.
- Action: See [“GWMTA: Insufficient memory”](#) on page 191.
- Action: After sufficient memory is available, turn disk logging back on in the Log Settings page for the agent in ConsoleOne. See [“Using MTA Log Files”](#) in [“Message Transfer Agent”](#) in the *GroupWise 7 Administration Guide*.

GWMTA: Login not completed; timeout

Source: GroupWise Message Transfer Agent; message transfer protocol.

Explanation: An MTA or POA started to request TCP/IP communication from the MTA, but stopped responding in the middle of the login process.

Possible Cause: The server where the other agent was running went down.

Action: Check the status of the other server. Reboot if necessary.

GWMTA: Login to directory failed

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot communicate with another domain or post office because it cannot access the server where the domain or post office is located.

Possible Cause: The `/user` and `/password` switches do not provide the correct information for the MTA to log in to the server.

Action: Check the settings for the `/user` and `/password` switches in the command that starts the MTA. Make sure you can log in to the server using the user name and password the MTA is trying to use.

Possible Cause: The server where the domain or post office is located is currently down.

Action: Wait for the server to come back up or contact the administrator of that server.

Action: See also [“GWMTA: Cannot attach to server or volume” on page 183](#).

GWMTA: Maximum number of inbound connections reached

Source: GroupWise Message Transfer Agent.

Explanation: The MTA could not start another thread for an inbound connection.

Possible Cause: The maximum number of inbound connections as specified by the `/tcpinbound` startup switch has been reached. The default is 40 inbound connections.

Action: Increase the setting of the `/tcpinbound` switch to allow for more inbound connections. There is no maximum number of inbound connections. They are limited only by available system resources. See [“Adjusting the Number of MTA TCP/IP Connections”](#) in [“Message Transfer Agent”](#) in the *GroupWise 7 Administration Guide*.

GWMTA: No agent record found

Source: GroupWise Message Transfer Agent.

Explanation: The MTA object in the eDirectory tree is missing.

Possible Cause: When a domain is created, an MTA object is automatically created for it. It might have been deleted.

Action: Check for the MTA object in the domain. Make sure it is configured correctly. See [“Configuring the MTA in ConsoleOne”](#) in [“Message Transfer Agent”](#) in the *GroupWise 7 Administration Guide*.

Possible Cause: The domain database (`wpdomain.db`) is damaged.

Action: Check and, if necessary, repair the domain database. See [“Rebuilding Domain or Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

GWMTA: No domain record found

- Source: GroupWise Message Transfer Agent.
- Explanation: The MTA cannot find the domain record in the domain database (`wppdomain.db`).
- Possible Cause: The domain database is damaged.
- Action: Rebuild the domain database. See “[Rebuilding Domain or Post Office Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

GWMTA: No path configured

- Source: GroupWise Message Transfer Agent.
- Explanation: Path information for links between domains is missing.
- Possible Cause: Links between domains are not set up correctly.
- Action: Check the links between domain. See “[Editing a Domain Link](#)” in “[Domains](#)” in the *GroupWise 7 Administration Guide*.

GWMTA: No post offices found

- Source: GroupWise Message Transfer Agent; eDirectory user synchronization.
- Explanation: The MTA has been configured to perform eDirectory user synchronization for a domain which has no post offices and, hence, no users; for example, a routing domain.
- Action: Remove the domain from the list of domains for which eDirectory user synchronization should be performed. See “[Using eDirectory User Synchronization](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.

GWMTA: No response from peer

- Source: GroupWise Message Transfer Agent; message transfer protocol.
- Explanation: The MTA is attempting to communicate with another MTA or a POA by way of TCP/IP, but the other agent does not answer.
- Possible Cause: The server where the other MTA or the POA is located is down.
- Action: Check the status of the other server. Reboot if necessary.

GWMTA: No sender IDomain; Internet address lookup not attempted

- Source: GroupWise Message Transfer Agent.
- Explanation: The address the MTA is trying to resolve does not contain IDomain information.
- Possible Cause: The MTA is configured for GWMTTP between GroupWise systems, but the link is not set up properly.
- Action: Correct any problems in the setup of links between the two systems. See “[Using Dynamic Internet Links](#)” in “[Connecting to GroupWise 5.x, 6.x, and 7 Systems](#)” in the *GroupWise 7 Multi-System Administration Guide*.
- Action: If the message is destined for a non-GroupWise system across the Internet, it will be routed through the GroupWise Internet Agent. No action is required, provided a preferred Internet Agent has been designated. See “[Configuring Internet Addressing](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*.

GWMTA: Path to domain database (/home) is invalid or blocked

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot access the domain database (**wpdomain.db**) in the directory specified by the /home switch.

Possible Cause: The location specified by the /home startup switch does not exist.

Action: Check, and if necessary change, the location specified by the /home startup switch when starting the MTA. It must specify the domain directory. See [“Using MTA Startup Switches”](#) in [“Message Transfer Agent”](#) in the *GroupWise 7 Administration Guide*.

Possible Cause: The location specified by the /home startup switch is on a server that is currently not available.

Action: Check the status of the server where the specified directory is located. Wait for the server to come back up or contact the administrator of that server.

Possible Cause: If running the MTA on a Windows server, the location might be on a server that is not currently mapped.

Action: Make sure the server where the MTA is running has a drive mapped to the domain directory on the server where the domain is located if it is using a mapped link.

Action: See [“GWMTA: Cannot attach to server or volume”](#) on page 183.

GWMTA: Post office database open failed; insufficient memory

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot access one of its post office databases (**wphost.db**).

Possible Cause: Insufficient memory.

Action: See [“GWMTA: Insufficient memory”](#) on page 191.

Possible Cause: The post office database has been damaged.

Action: Rebuild the post office database. See [“Rebuilding Domain or Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

GWMTA: Post office database read error

Source: GroupWise Message Transfer Agent.

Explanation: The MTA cannot access the post office database (**wphost.db**).

Possible Cause: The post office database has been damaged.

Action: Rebuild the post office database. See [“Rebuilding Domain or Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

GWMTA: Post office now closed

Source: GroupWise Message Transfer Agent.

Explanation: The MTA has lost its connection to a post office with which it could previously communicate.

Possible Cause: The server where the post office is located is currently down.

Action: Wait for the server to come back up, or contact the administrator of that server.

Possible Cause: If using TCP/IP communication between post offices, TCP/IP might be down.

Action: Make sure TCP/IP is running on the servers where the post offices are located.

GWMTA: Post office open failed

- Source: GroupWise Message Transfer Agent.
- Explanation: The MTA cannot contact the POA in one of the local post offices.
- Possible Cause: The MTA cannot access the POA input queue in the post office.
- Action: Check the directory structure of the closed post office. See “Post Office Directory” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

GWMTA: Received unsupported request; request ignored

- Source: GroupWise Message Transfer Agent.
- Explanation: The MTA received an administrative message from GroupWise Administrator that it could not respond to.
- Possible Cause: GroupWise Administrator has been updated, but the GroupWise agent software has not yet been updated.
- Action: Install the latest version of the GroupWise agent software. See the “Installing the GroupWise 7 Software” in “Update” in the *“GroupWise 7 Installation Guide”*.

GWMTA: StartServiceCtrlDispatcher failed when attempting to start *Windows_agent* service

- Source: GroupWise Message Transfer Agent for Windows.
- Explanation: The Windows MTA cannot start its dispatcher thread.
- Possible Cause: The Windows server is not functioning properly.
- Action: Reboot the Windows server.

GWMTA: Target queue temporarily locked

- Source: GroupWise Message Transfer Agent.
- Explanation: The MTA is in the process of clearing out a backlog of messages and is not accepting any additional messages into its queues. The MTA processes existing messages first, before processing new messages, so that messages arrive in the order in which they were sent.
- Possible Cause: The backlog of messages might have been caused by one or more closed facilities in the domain.
- Action: Wait until the backlog clears, then the MTA will resume its regular processing of new messages. Backlogged messages are stored in subdirectories of the **mslocal** directory.

GWMTA: The *Windows_agent* service fails to set service status; service stopped

- Source: GroupWise Message Transfer Agent for Windows.
- Explanation: The Windows MTA cannot start as a Windows service.
- Possible Cause: The Windows MTA cannot communicate with the Windows service control manager (SCM).
- Action: Reboot the Windows server.

GWMTA: The *Windows_agent* service fails to initialize memory system; service stopped

- Source: GroupWise Message Transfer Agent for Windows.
- Explanation: The Windows MTA cannot start as a Windows service.

Possible Cause: The Windows server has insufficient memory resources available.

Action: Reboot the Windows server. Run fewer programs on the Windows server.

GWMTA: Timed out waiting for end-of-file confirmation

Source: GroupWise Message Transfer Agent.

Explanation: The MTA is in the process of clearing out a backlog of messages and is not accepting any additional messages into its queues. The MTA processes existing messages first, before processing new messages, so that messages arrive in the order in which they were sent.

Possible Cause: The backlog of messages might have been caused by one or more closed facilities in the domain.

Action: Wait until the backlog clears, then the MTA will resume its regular processing of new messages. Backlogged messages are stored in subdirectories of the **mslocal** directory.

GWMTA: Unable to initialize message log database

Source: GroupWise Message Transfer Agent; message transfer protocol.

Explanation: The MTA was unable to create the database where it stores information about messages waiting for processing in its in progress (**gwinprog**) queue. the **msglog** subdirectory of **mslocal** cannot be created.

Possible Cause: Insufficient disk space.

Action: Free up disk space on the server where the MTA runs.

GWMTA: Unable to open connection; no response

Source: GroupWise Message Transfer Agent; message transfer protocol.

Explanation: The MTA is attempting to communicate with another MTA or a POA by way of TCP/IP, but the other agent does not answer.

Possible Cause: The server where the other MTA or the POA is located is down.

Action: Check the status of the other server. Reboot if necessary.

GWMTA: Unable to register with SNMP agent

Source: GroupWise agents.

Explanation: The MTA is unable to contact the SNMP agent on the server where the agent is running.

Possible Cause: SNMP has not been installed and set up properly on the server.

Action: Install SNMP as required by the server operating system.

GWMTA: Unable to retrieve TCP/IP address

Source: GroupWise Message Transfer Agent.

Explanation: The MTA is configured for GWMTA between GroupWise systems, but the MTA cannot find the IDomain name of the destination system

Possible Cause: GWMTA is not properly set up between the two GroupWise systems.

Action: Correct any problems in the setup of links between the two systems. See [“Using Dynamic Internet Links”](#) in [“Connecting to GroupWise 5.x, 6.x, and 7 Systems”](#) in the *GroupWise 7 Multi-System Administration Guide*.

GWMTA: Undefined link

- Source: GroupWise Message Transfer Agent; last closure reason.
- Explanation: MTAs cannot communicate because no link has been established between them.
- Action: Configure a link between the MTAs. See [“Changing the Link Protocol between Domains”](#) in [“Configuring the MTA”](#) in the *GroupWise 7 Administration Guide*.

GWMTA: Unknown connection header received

- Source: GroupWise Message Transfer Agent; message transfer protocol.
- Explanation: The MTA received a request for a TCP/IP connection from a process other than a GroupWise agent.
- Possible Cause: Some non-GroupWise program on the server where the MTA is running is configured to send packets to the port the MTA is configured to listen on.
- Action: Check the network address information of the MTA. See [“Configuring the MTA for TCP/IP”](#) in [“Configuring the MTA”](#) in the *GroupWise 7 Administration Guide*. Make sure no other programs on the server besides GroupWise agents are configured to use this port.

GWMTA: Unknown destination

- Source: GroupWise Message Transfer Agent.
- Explanation: The MTA is unable to route a message because it does not recognize the domain to which it is addressed.
- Possible Cause: The sender manually typed in an invalid address.
- Action: Have the user select the recipient from the Address Book, then resend the message.
- Possible Cause: During a reconfiguration of your system, a user has addressed a message to a location that either no longer exists or does not exist yet, because the reconfiguration information has not yet replicated throughout the GroupWise system.
- Action: Wait until replication is complete. The MTA will retry the operation.
- Possible Cause: The message has been damaged so that the destination information is no longer readable.
- Action: Remove the damaged message from the MTA input queue so it can process subsequent messages. Have the user resend the message.

GWMTA: Waiting for busy listen socket to become available

- Source: GroupWise Message Transfer Agent; message transfer protocol.
- Explanation: The TCP port the MTA is configured to listen on is already in use by another program.
- Possible Cause: Another MTA is already running on the server where you are trying to start this MTA.
- Action: Configure this MTA to use a different TCP port. See [“Using TCP/IP Links between Domains”](#) in [“Configuring the MTA”](#) in the *GroupWise 7 Administration Guide*.

Internet Agent Error Messages

Some error and informational messages you might receive when using the Internet Agent originate from the program engine or from SMTP when the program makes connections with hosts, and from other sources as well. This section includes the error messages generated by the Internet Agent.

Variables, such as strings or numbers, are shown in italics and are represented by the following:

- ◆ ASCII strings are represented by *xxx*, *yyy*, or *zzz*
- ◆ Decimal characters are represented by *nnn*
- ◆ Hexadecimal characters are represented by *hhh*

“GWIA: Command task could not be added to message body, rc =*xxxx*” on page 202

“GWIA: Configuration data is missing from the database” on page 202

“GWIA: ConvertPerfect Error while converting attachment file filename” on page 202

“GWIA: Currently unhandled command value, *xxxx*, was received by the gateway” on page 202

“GWIA: Database initialization error: *xxxx*” on page 202

“GWIA: Database open error: *xxxx*” on page 202

“GWIA: Deferred delivery file I/O error--encryption error” on page 203

“GWIA: Deferred delivery file I/O error-memory error” on page 203

“GWIA: Deferred delivery file I/O error-message undeliverable” on page 203

“GWIA: Deferred file, filename, has been moved to the PROBLEM directory” on page 203

“GWIA: File close error on file filename in module *xxxx*” on page 203

“GWIA: File creation error on file filename in module *xxxx*” on page 203

“GWIA: File open error on file filename in module *xxxx*” on page 203

“GWIA: File read error on file filename in module *xxxx*” on page 204

“GWIA: File write error on file filename in module *xxxx*” on page 204

“GWIA: Gateway that uses this directory is not yet defined” on page 204

“GWIA: Gateway Configuration Database could not be found” on page 204

“GWIA: Memory exhausted” on page 204

“GWIA: Memory exhausted while processing an Administrator Command” on page 204

“GWIA: Message File open failed” on page 204

“GWIA: Message re-queuing failed. The message must be deleted” on page 205

“GWIA: Message transport session open error: *xxxx*” on page 205

“GWIA: Processing inbound message...” on page 205

“GWIA: Processing outbound command...” on page 205

“GWIA: Processing outbound message...” on page 205

“GWIA: Scratch-pad file creation error: *xxxx*” on page 205

“GWIA: Scratch-pad file write error: filename” on page 205

“GWIA: Unable to find TCPIP Kernel” on page 206

GWIA: Command task could not be added to message body, rc =xxxx

Source: GroupWise® Internet Agent.

Explanation: A file output error occurred, probably because of a full disk or an inaccessible directory.

Action: If rc = D109, check access rights and privileges in the **wpcsin** directory.

or

If rc = D907, check access rights and privileges in the wpcsin directory.

GWIA: Configuration data is missing from the database

Source: GroupWise Internet Agent.

Explanation: The domain database (**wpdomain.db**) is damaged.

Action: Rebuild the database using ConsoleOne®. See “**Rebuilding Domain or Post Office Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

GWIA: ConvertPerfect Error while converting attachment file filename

Source: GroupWise Internet Agent.

Explanation: The user sent the message using the Convert Attachment feature of the Advanced Send Option, which invokes ConvertPerfect*. ConvertPerfect might not know how to convert this type of file, the file could not be decrypted, or a file I/O error occurred. This problem might generate a different error message than the one listed above.

Action: None.

GWIA: Currently unhandled command value, xxxx, was received by the gateway

Source: GroupWise Internet Agent.

Explanation: An unrecognized command was received from ConsoleOne.

Action: Resend the command.

GWIA: Database initialization error: xxxx

Source: GroupWise Internet Agent.

Explanation: The Internet Agent database management code could not be initialized

Action: You might need to rebuild the domain database (**wpdomain.db**) for the domain where the Internet Agent is installed. See “**Rebuilding Domain or Post Office Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

GWIA: Database open error: xxxx

Source: GroupWise Internet Agent.

Explanation: The domain database path could not be created, or the database did not open.

Action: Make sure that the domain database (**wpdomain.db**) is in the domain directory.

GWIA: Deferred delivery file I/O error--encryption error

Source: GroupWise Internet Agent.

Explanation: An encrypted non-queue file was moved to the **gwhold** directory.

Action: Do not put any files in gwhold, remove any files not named with a HEX time stamp, and restart the Internet Agent.

GWIA: Deferred delivery file I/O error-memory error

Source: GroupWise Internet Agent.

Explanation: The Internet Agent server ran out of memory.

Action: Free more memory.

GWIA: Deferred delivery file I/O error-message undeliverable

Source: GroupWise Internet Agent.

Explanation: The message could not be written to disk in the **qfiles** directory.

Action: Check to see if the disk is full, and check access to the directory.

GWIA: Deferred file, *filename*, has been moved to the PROBLEM directory

Source: GroupWise Internet Agent.

Explanation: After the Internet Agent retry schedule expired, the message was moved to the **problem** directory. The destination host was temporarily down (it sent back a 400-level SMTP reply code) so the program could not transfer the message.

Action: Contact the postmaster for the destination host to make sure the host is up. Have the user resend the message.

GWIA: File close error on file *filename* in module *xxxx*

Source: GroupWise Internet Agent.

Explanation: A close of the named file resulted in an error.

Action: Check if some other process on the server is holding the file open. Check for network problems.

GWIA: File creation error on file *filename* in module *xxxx*

Source: GroupWise Internet Agent.

Explanation: An open of the named file resulted in an error.

Action: Check access in the named directory.

GWIA: File open error on file *filename* in module *xxxx*

Source: GroupWise Internet Agent.

Explanation: An open of the named file resulted in an error.

Action: Check access to the named file and directory, and check access to the file.

GWIA: File read error on file *filename* in module *xxxx*

Source: GroupWise Internet Agent.

Explanation: A read of the named file resulted in an error.

Action: Check access to the named file.

GWIA: File write error on file *filename* in module *xxxx*

Source: GroupWise Internet Agent.

Explanation: A write to the named file resulted in an error.

Action: Check access in the named directory, and check to see if the disk is full.

GWIA: Gateway that uses this directory is not yet defined

Source: GroupWise Internet Agent.

Explanation: The Internet Agent has been installed, but it is not yet configured.

Action: Configure the Internet Agent in ConsoleOne. See “Internet Agent” in the *GroupWise 7 Administration Guide*.

GWIA: Gateway Configuration Database could not be found

Source: GroupWise Internet Agent.

Explanation: The directory where the domain database (*wpdomain.db*) resides cannot be found, given the Internet Agent’s default directory and the Internet Agent startup options.

Action: Use the Internet Agent directory startup option */work* to reference the directory below *wpgate* in the domain where the Internet Agent executable file resides, or simply invoke the executable from that directory. Check network rights.

GWIA: Memory exhausted

Source: GroupWise Internet Agent.

Explanation: The Internet Agent was not able to allocate sufficient memory.

Action: Free up more memory.

GWIA: Memory exhausted while processing an Administrator Command

Source: GroupWise Internet Agent.

Explanation: The Internet Agent ran out of memory while processing a command sent to the Internet Agent by ConsoleOne.

Action: Free up more memory.

GWIA: Message File open failed

Source: GroupWise Internet Agent.

Explanation: The Internet Agent could not open a message file.

Action: The message file is moved to the *problem* directory in the domain directory.

GWIA: Message re-queuing failed. The message must be deleted

Source: GroupWise Internet Agent.

Explanation: A message could not be put into or removed from the delayed delivery and the retry queue maintained under the gwhold directory because of a disk or a memory error.

Action: Check access to the **gwhold** and **qfiles** subdirectories.

Action: Check to see if the disk is full.

Action: Free more memory.

GWIA: Message transport session open error: xxxx

Source: GroupWise Internet Agent.

Explanation: This is almost always caused by a memory error.

Action: Free up memory.

GWIA: Processing inbound message...

Source: GroupWise Internet Agent.

Explanation: This is an informational message. A message is being received by the Internet Agent from the foreign system.

Action: None.

GWIA: Processing outbound command...

Source: GroupWise Internet Agent.

Explanation: This is an informational message. ConsoleOne has sent a command to the Internet Agent. Commands are STATE, REQUEST STATS, REBOOT, and DIRECTORY SYNCHRONIZATION.

Action: None.

GWIA: Processing outbound message...

Source: GroupWise Internet Agent.

Explanation: This is an informational message. A message is being received by the Internet Agent from the GroupWise system.

Action: None.

GWIA: Scratch-pad file creation error: xxxx

Source: GroupWise Internet Agent.

Explanation: The Internet Agent settings file, SET, could not be created.

Action: Check access (write or create) to the **000.prc** directory.

Action: Check to see if the disk is full.

GWIA: Scratch-pad file write error: filename

Source: GroupWise Internet Agent.

Explanation: The Internet Agent settings file, SET, could not be written.

Action: Check access (write or create) to the **000.prc** directory.

Action: check to see if the disk is full.

GWIA: Unable to find TCPIP Kernel

Source: GroupWise Internet Agent.

Explanation: The Internet Agent must find the TCP/IP kernel already loaded or the Internet Agent automatically loads the TCP/IP kernel. If the TCP/IP kernel is not or cannot be loaded automatically, this error results.

Action: Check to see that the TCP/IP kernel is installed and configured.

GWIA: Unable to listen on SMTP port

Source: GroupWise Internet Agent.

Explanation: The TCP/IP kernel is not installed correctly or the Internet Agent is unable to take control of port 25 (SMTP port number). Other processes might have control of port 25, thereby preventing the Internet Agent from taking control of port 25.

Action: Unload the TCP/IP kernel then reload it. If another process has control of port 25, unloading the TCP/IP kernel shows it.

WebAccess Agent Error Messages

- “WEBACC: CMC encountered a problem accessing the GroupWise domain” on page 208
- “WEBACC: CMC was not able to access this GroupWise gateway directory” on page 208
- “WEBACC: CMC was not able to establish a connection to the post office” on page 208
- “WEBACC: Conversation timed out” on page 209
- “WEBACC: Could not start logging thread” on page 209
- “WEBACC: Error accessing directory” on page 209
- “WEBACC: Error accessing startup file” on page 209
- “WEBACC: File I/O error” on page 209
- “WEBACC: GWINTER NLM cannot initialize screen” on page 210
- “WEBACC: GWINTER NLM initialization error: Invalid GWENN5.NLM loaded” on page 210
- “WEBACC: Hash value changed” on page 210
- “WEBACC: If necessary, the system will attempt a forced shutdown ...” on page 210
- “WEBACC: Invalid command line syntax” on page 210
- “WEBACC: Invalid log level” on page 211
- “WEBACC: Invalid startup parameter” on page 211
- “WEBACC: Invalid startup parameter file” on page 211
- “WEBACC: Invalid startup parameter value” on page 211
- “WEBACC: Logging: Disk is full - turning file logging off” on page 211
- “WEBACC: Logging: Error creating file - turning file logging off” on page 211
- “WEBACC: Logging: Error writing to file - turning file logging off” on page 212
- “WEBACC: Login failed” on page 212
- “WEBACC: Login rejected: No valid password specified” on page 212
- “WEBACC: Login rejected: No valid userid specified” on page 212
- “WEBACC: Login rejected: Password is incorrect” on page 212
- “WEBACC: No gateway alias was specified in NW Admin” on page 213
- “WEBACC: No gateway directory was specified” on page 213
- “WEBACC: No message is currently open” on page 213
- “WEBACC: No NetWare password was specified” on page 213
- “WEBACC: No NetWare user ID was specified” on page 213
- “WEBACC: No UNC path specified for the post office” on page 214
- “WEBACC: Not able to bind to specified port” on page 214
- “WEBACC: Not able to open configuration file” on page 214
- “WEBACC: Not enough memory to complete operation” on page 214
- “WEBACC: Request aborted while waiting on locked conversation” on page 214
- “WEBACC: Request rejected because all threads are busy” on page 215
- “WEBACC: Startup file not found” on page 215
- “WEBACC: TCP socket accept failed” on page 215

“WEBACC: The post office is closed” on page 215

“WEBACC: The system is busy, please try again later” on page 215

“WEBACC: Unable to establish a connection to the default log path” on page 216

“WEBACC: Unable to establish a connection to the log path” on page 216

“WEBACC: Unable to find the specified user” on page 216

“WEBACC: Unknown keyword.” on page 216

WEBACC: CMC encountered a problem accessing the GroupWise domain

Source: GroupWise® WebAccess Agent

Explanation: The WebAccess Agent could not access the GroupWise domain in which its gateway directory is located.

Possible Cause: The WebAccess Agent was not started with the /ph switch.

Action: Start the WebAccess Agent by using the /ph switch. For example, gwinter /ph-j:\advert\wpgate\webac70a. For more information, see “Using WebAccess Startup Switches” in “WebAccess” in the *GroupWise 7 Administration Guide*.

Possible Cause: The WebAccess Agent lost its connection to the domain directory or does not have sufficient rights in the directory structure.

Action: Reestablish the connection to the domain directory and make sure the WebAccess Agent has sufficient rights. See “WebAccess Security Requirements” in “Installing GroupWise WebAccess” in the *GroupWise 7 Installation Guide*.

WEBACC: CMC was not able to access this GroupWise gateway directory

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not access its gateway directory in domain directory (*domain*\wpgate\webac70a, where *domain* is the domain directory and *webac70a* is the gateway directory).

Possible Cause: The WebAccess Agent does not have sufficient rights in the domain directory structure.

Action: Make sure the WebAccess Agent has sufficient rights. See “WebAccess Security Requirements” in “Installing GroupWise WebAccess” in the *GroupWise 7 Installation Guide*.

WEBACC: CMC was not able to establish a connection to the post office

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not connect to the WebAccess user’s post office.

Possible Cause: The WebAccess Agent lost its direct connection (UNC path or mapped drive) to the post office directory or does not have sufficient rights in the directory structure.

Action: Reestablish the connection to the post office directory and make sure the WebAccess Agent has sufficient rights. See “WebAccess Security Requirements” in “Installing GroupWise WebAccess” in the *GroupWise 7 Installation Guide*.

Possible Cause: The WebAccess Agent lost its TCP/IP connection to the Post Office Agent (POA).

Action: Make sure the Post Office Agent is up and running and that TCP/IP is configured properly on the servers running the WebAccess Agent and Post Office Agent. See “Managing Access to Post Offices” in “WebAccess” in the *GroupWise 7 Administration Guide*.

Possible Cause: The WebAccess Agent's post office link information is not defined correctly in Novell® eDirectory™.

Action: Check the post office link information. See “[Modifying Links to Post Offices](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

WEBACC: Conversation timed out

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent automatically logs a user out of GroupWise if he or she does not use GroupWise WebAccess for a certain period of time (the timeout interval). This message indicates that the GroupWise WebAccess user's session has timed out.

Possible Cause: The GroupWise WebAccess user did not perform any actions in GroupWise WebAccess during the timeout interval.

Action: Have the user log in again. Lengthen the timeout interval. See “[Creating a Class of Service](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

WEBACC: Could not start logging thread

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent uses a separate thread other than the regular worker threads for logging. The WebAccess Agent could not open the logging thread.

Possible Cause: Low memory resources.

Action: Free up memory or add additional memory.

WEBACC: Error accessing directory

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not access the specified directory.

Possible Cause: The WebAccess Agent lost its connection to the server where the directory resides or does not have sufficient rights to the directory.

Action: Reestablish the connection to the server and make sure the WebAccess Agent has sufficient rights to the directory. See “[WebAccess Security Requirements](#)” in “[Installing GroupWise WebAccess](#)” in the *“GroupWise 7 Installation Guide”*.

WEBACC: Error accessing startup file

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not access the startup file specified by the *@filename* switch.

Possible Cause: The WebAccess Agent does not have the rights needed to access the startup file or the startup file does not exist in the specified location.

Action: Make sure the WebAccess Agent has rights to the startup file.

Action: Make sure the startup file is in the same directory as the WebAccess Agent program or that *filename* includes the full path to the file.

WEBACC: File I/O error

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not view a log file.
Possible Cause: The WebAccess Agent does not have access to log file directory, or does not have rights to the file.
Action: Make sure the WebAccess Agent has access to the log file directory and that it has rights to view the file.

WEBACC: GWINTER NLM cannot initialize screen

Source: GroupWise WebAccess Agent
Explanation: The WebAccess Agent cannot display its agent console.
Possible Cause: Insufficient memory.
Action: Free up memory or add additional memory.

WEBACC: GWINTER NLM initialization error: Invalid GWENN5.NLM loaded

Source: GroupWise WebAccess Agent
Explanation: GroupWise Agent Engine (**gwenn5.nlm**) that is currently loaded is the incorrect version for the WebAccess Agent.
Possible Cause: Another GroupWise agent loaded an earlier version of gwenn5.nlm.
Action: Unload all GroupWise agents that are running on the server. Start GroupWise WebAccess and restart the other GroupWise agents. Make sure the other GroupWise agents are version 7. If necessary, reinstall the GroupWise WebAccess software to install the correct version of gwenn5.nlm.

WEBACC: Hash value changed

Source: GroupWise WebAccess Agent
Explanation: Possible security violation.
Possible Cause: A user bookmarked a GroupWise WebAccess location then attempted to access it directly from another server.
Action: Have the user log in through the GroupWise WebAccess login screen.

WEBACC: If necessary, the system will attempt a forced shutdown ...

Source: GroupWise WebAccess Agent
Explanation: In one minute, the WebAccess Agent will attempt to shut down even if WebAccess users are still logged in.
Possible Cause: The WebAccess Agent has been shut down, but one or more worker threads are still processing user requests.
Action: None.

WEBACC: Invalid command line syntax

Source: GroupWise WebAccess Agent
Explanation: The specified syntax is invalid.
Possible Cause: The wrong startup switch syntax was used when attempting to start the WebAccess Agent.

Action: See “Using WebAccess Startup Switches” in “WebAccess” in the *GroupWise 7 Administration Guide*.

WEBACC: Invalid log level

Source: GroupWise WebAccess Agent

Explanation: The specified log level is not a valid log level.

Possible Cause: The log level specified by the `/loglevel` startup switch is not valid.

Action: Use one of the valid log levels: normal, verbose, or diagnostic. See “Using WebAccess Startup Switches” in “WebAccess” in the *GroupWise 7 Administration Guide*.

WEBACC: Invalid startup parameter

Source: GroupWise WebAccess Agent

Explanation: The specified startup switch is not a valid switch.

Possible Cause: A startup switch used on the command line or in the startup file is not valid.

Action: Retype the command line or edit the startup file to include valid switches only. See “Using WebAccess Startup Switches” in “WebAccess” in the *GroupWise 7 Administration Guide*.

WEBACC: Invalid startup parameter file

Source: GroupWise WebAccess Agent

Explanation: The specified file is not a valid startup file.

Possible Cause: The file is not a text file or does not contain any startup switches.

Action: Save the file as a text file or enter valid startup switches in the file. See “Using WebAccess Startup Switches” in “WebAccess” in the *GroupWise 7 Administration Guide*.

WEBACC: Invalid startup parameter value

Source: GroupWise WebAccess Agent

Explanation: The value for the specified startup switch is not valid.

Possible Cause: An invalid value was entered with the startup switch on the command line or in the startup file.

Action: Enter a valid value. See “Using WebAccess Startup Switches” in “WebAccess” in the *GroupWise 7 Administration Guide*.

WEBACC: Logging: Disk is full - turning file logging off

Source: GroupWise WebAccess Agent

Explanation: The disk where the log files are stored is full. File logging will be turned off.

Possible Cause: The disk is full.

Action: Delete files to increase available disk space. Allocate more disk space. Specify a different location for the log files. See “Using WebAccess Startup Switches” in “WebAccess” in the *GroupWise 7 Administration Guide*.

WEBACC: Logging: Error creating file - turning file logging off

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not create the log file, so disk logging is being turned off.

Possible Cause: The WebAccess Agent does not have rights to create files in the log file directory.

Action: Provide the WebAccess Agent with rights to create files in the log file directory or specify a different location for the log files. See *“Using WebAccess Startup Switches”* in *“WebAccess”* in the *GroupWise 7 Administration Guide*. Check the disk to make sure that there is sufficient space available to create the file.

WEBACC: Logging: Error writing to file - turning file logging off

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not write information to the log file, so logging is being turned off.

Possible Cause: The WebAccess Agent does not have rights to write to files in the log file directory or the disk is full.

Action: Provide the WebAccess Agent with rights to write to files in the log file directory or specify a different location for the log files. See *“Using WebAccess Startup Switches”* in *“WebAccess”* in the *GroupWise 7 Administration Guide*.

WEBACC: Login failed

Source: GroupWise WebAccess Agent

Explanation: A WebAccess user attempted to log in and failed.

Possible Cause: The user did not enter a valid GroupWise user ID or password.

Action: Make sure the user knows his or her GroupWise user ID. Make sure the user has a password set on his or her mailbox and knows the password.

WEBACC: Login rejected: No valid password specified

Source: GroupWise WebAccess Agent

Explanation: A GroupWise WebAccess user could not log in because he or she did not enter a valid password.

Possible Cause: The user did not enter a password when logging in.

Action: Make sure the user knows his or her mailbox password and enters it when logging in.

WEBACC: Login rejected: No valid userid specified

Source: GroupWise WebAccess Agent

Explanation: A GroupWise WebAccess user could not log in because he or she did not enter a valid GroupWise user ID.

Possible Cause: The user did not enter a GroupWise user ID or full name when logging in.

Action: Make sure the user knows his or her GroupWise user ID and enters it when logging in. Users can also enter their full names as they appear in eDirectory and the GroupWise Address Book.

WEBACC: Login rejected: Password is incorrect

Source: GroupWise WebAccess Agent

Explanation: The password specified during login is incorrect.

Possible Cause: The user entered the wrong password.

Action: Make sure the user knows his or her mailbox password and enters it when logging in. Passwords are case sensitive.

WEBACC: No gateway alias was specified in NW Admin

Source: GroupWise WebAccess Agent

Explanation: The gateway alias type is not defined.

Possible Cause: The gateway alias was not specified in ConsoleOne® during setup.

Action: Specify a gateway alias type. In ConsoleOne, double-click the WebAccess object, enter an alias in the Gateway Alias Type field, then click OK. The alias can be the same name as the gateway.

WEBACC: No gateway directory was specified

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent must know the path to its gateway home directory. This path is specified by the /ph startup switch.

Possible Cause: The /ph startup switch was not used on the command line or in the strtweb.ncf or strtweb.bat file.

Action: Include the startup switch. See “Using WebAccess Startup Switches” in “WebAccess” in the *GroupWise 7 Administration Guide*.

WEBACC: No message is currently open

Source: GroupWise WebAccess Agent

Explanation: This is an internal diagnostic message.

Possible Cause: Unknown.

Action: If the problem persists, contact the [Novell Support \(http://support.novell.com\)](http://support.novell.com).

WEBACC: No NetWare password was specified

Source: GroupWise WebAccess Agent

Explanation: The GroupWise WebAccess Agent requires an account and password that lets it log in to eDirectory or NetWare® servers so that it can access the domain directory and post office directories.

Possible Cause: The /password startup switch was not used on the command line or does not exist in the strtweb.ncf file.

Action: Use the /password startup switch when starting the WebAccess Agent from the command line or edit the strtweb.ncf file to add the switch. See “Using WebAccess Startup Switches” in “WebAccess” in the *GroupWise 7 Administration Guide*.

WEBACC: No NetWare user ID was specified

Source: GroupWise WebAccess Agent

Explanation: The GroupWise WebAccess Agent requires an account and password that lets it log in to eDirectory or NetWare servers so that it can access the domain directory and post office directories.

Possible Cause: The /user startup switch was not used on the command line or does not exist in the strtweb.ncf file.

Action: Use the /user startup switch when starting the WebAccess Agent from the command line or edit the strtweb.ncf file to add the switch. See “Using WebAccess Startup Switches” in “WebAccess” in the *GroupWise 7 Administration Guide*.

WEBACC: No UNC path specified for the post office

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent is attempting direct access to a post office and no UNC path is specified.

Possible Cause: The UNC path is not defined in the post office link information.

Action: In ConsoleOne, specify a UNC path or mapped drive to the post office. See “Modifying Links to Post Offices” in “WebAccess” in the *GroupWise 7 Administration Guide*.

WEBACC: Not able to bind to specified port

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not bind to the TCP/IP port it uses to listen for messages from the GroupWise WebAccess CGI Extension.

Possible Cause: Another program is using the port.

Action: Resolve the port conflict by changing the port used by the other program or the port used by the WebAccess Agent. To change the WebAccess Agent’s port, see in “WebAccess” in the *GroupWise 7 Administration Guide*.

WEBACC: Not able to open configuration file

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not open the comint.cfg file located in its gateway home directory (*domain\wpgate\webac70a*, where *domain* is the domain directory and *webac70a* is the gateway home directory). The WebAccess Agent reads configuration information from this file.

Possible Cause: The file has been deleted or has a problem.

Action: Use ConsoleOne to reenter the configuration information. See “Configuring the WebAccess Agent” in “WebAccess” in the *GroupWise 7 Administration Guide*.

WEBACC: Not enough memory to complete operation

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not perform the operation because of insufficient memory.

Possible Cause: Insufficient memory.

Action: Free up memory or add additional memory.

WEBACC: Request aborted while waiting on locked conversation

Source: GroupWise WebAccess Agent

Explanation: During a conversation (or session), GroupWise WebAccess issues a request whenever the user performs an action in WebAccess. When the WebAccess Agent receives a request, it locks the conversation so that it can process the request. While the conversation is locked, other requests can accumulate. This message indicates a request that was waiting on the locked conversation has timed out.

Possible Cause: The request for the locked conversation took longer than allowed.

Action: Have the GroupWise WebAccess user perform the action again (for example, resend the message).

WEBACC: Request rejected because all threads are busy

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not process a request from a WebAccess user because no threads were available.

Possible Cause: Heavy WebAccess usage for the number of threads allocated to the WebAccess Agent.

Action: If this error occurs often, increase the number of threads. See “[Modifying WebAccess Settings](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

WEBACC: Startup file not found

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not find the startup file specified by the *@filename* startup switch.

Possible Cause: The startup file is not in the same directory as the WebAccess Agent and *filename* does not include the complete path to the file.

Action: Move the startup file to the same directory as the WebAccess Agent or include the full path in the *filename* (for example *@j:\startup\webstart.txt*).

WEBACC: TCP socket accept failed

Source: GroupWise WebAccess Agent

Explanation: The GroupWise WebAccess CGI Extension tried to start a new session with the WebAccess Agent, but the WebAccess Agent could not handle another session.

Possible Cause: Insufficient memory.

Action: Free up memory or add additional memory.

WEBACC: The post office is closed

Source: GroupWise WebAccess Agent

Explanation: While processing a request for a user, the WebAccess Agent could not access the user’s post office.

Possible Cause: Logging in to the post office has been disabled through ConsoleOne.

Action: Enable the post office. See “[Disabling a Post Office](#)” in “[Post Offices](#)” in the *GroupWise 7 Administration Guide*.

WEBACC: The system is busy, please try again later

Source: GroupWise WebAccess Agent

Explanation: A user tried to log in to GroupWise WebAccess, but the WebAccess Agent could not handle another user.

Possible Cause: All worker threads are currently being used.

Action: If the problem persists, increase the number of threads. See “[Modifying WebAccess Settings](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

WEBACC: Unable to establish a connection to the default log path

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent could not access the specified log file directory.

Possible Cause: The WebAccess Agent does not have rights to the directory or does not have access to the file server.

Action: Make sure the WebAccess Agent's user account provides the correct access and rights, or specify a different log file directory using the /log switch. See "Using WebAccess Startup Switches" in "WebAccess" in the *GroupWise 7 Administration Guide*.

WEBACC: Unable to establish a connection to the log path

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent cannot access the log file directory.

Possible Cause: The WebAccess Agent does not have rights to the directory or does not have access to the file server.

Action: Make sure the WebAccess Agent's user account provides the correct access and rights, or specify a different log file directory using the /log switch. See "Using WebAccess Startup Switches" in "WebAccess" in the *GroupWise 7 Administration Guide*.

WEBACC: Unable to find the specified user

Source: GroupWise WebAccess Agent

Explanation: The WebAccess Agent cannot find the user in the GroupWise database.

Possible Cause: When logging in, the user entered an incorrect or invalid user ID.

Action: Have the user enter a valid user ID or full username (as defined in eDirectory or the GroupWise Address Book) when logging in.

Action: Have the user try logging in using the full GroupWise username (*domain.post_office.userID*).

Possible Cause: The WebAccess servlet has encountered a problem with the username.

Action: Check the WebAccess Application log for additional error messages. The location of the log file varies by platform.

NetWare /novell/webaccess/logs
and
Windows:

Linux: /opt/novell/groupwise/webaccess/logs

WEBACC: Unknown keyword:

Source: GroupWise WebAccess Agent

Explanation: When communicating, the WebAccess Agent and WebAccess CGI Extension exchange keywords. This message indicates that the keyword given by the WebAccess CGI Extension is not known by the WebAccess Agent.

Possible Cause: The comint.cfg file used by the WebAccess Agent is out of sync with the commgr.cfg file used by the WebAccess CGI Extension. The WebAccess Agent, WebAccess CGI Extension, HTML templates, and Java* applets are not the same version.

Action: In ConsoleOne, reenter the configuration information so that the comint.cfg file and commgr.cfg file will be resaved. See “[Configuring the WebAccess Agent](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

If the problem persists, reinstall the GroupWise WebAccess software. See “[Installing GroupWise WebAccess](#)” in the “[GroupWise 7 Installation Guide](#)”.

Monitor Agent and Application Error Messages

“GWMON: GroupWise Monitor Agent is not listening” on page 219

“GWMON: No route to GroupWise Monitor Agent” on page 219

“GWMON: Path to domain database (/home) is invalid or blocked” on page 219

“GWMON: Request timed out waiting for response from GroupWise Monitor Agent” on page 220

“GWMON: The URL to connect to the GroupWise Monitor Agent is invalid” on page 220

“GWMON: Unable to communicate with GroupWise Monitor Agent” on page 220

“GWMON: Unable to connect to the MTA at IP_address:port” on page 221

“GWMON: Unable to resolve GroupWise Monitor Agent’s host name to a valid IP address” on page 221

GWMON: GroupWise Monitor Agent is not listening

Source: GroupWise® Monitor Application.

Possible Cause: The Monitor Agent is not running.

Action: Restart the Monitor Agent. See “Starting the Monitor Agent” in “Monitor” in the *GroupWise 7 Administration Guide*.

Possible Cause: The Monitor Agent is listening on a different port than the one the Monitor Application is using to communicate with it.

Action: Check the gwmonitor.cfg file to make sure it provides the correct IP address and port number for the Monitor Agent. Correct the information as needed.

GWMON: No route to GroupWise Monitor Agent

Source: GroupWise Monitor Application.

Possible Cause: Your firewall is preventing the Monitor Application from communicating with the Monitor Agent.

Action: Adjust the configuration of your firewall to accommodate communication between the Monitor Application and the Monitor Agent.

Possible Cause: A router between the Monitor Application and the Monitor Agent is down.

Action: Resolve any network problems that are preventing GroupWise Monitor from functioning.

GWMON: Path to domain database (/home) is invalid or blocked

Source: GroupWise Monitor Agent.

Explanation: The Monitor Agent cannot access the domain database (**wpdomain.db**) in the directory specified by the /home switch.

Possible Cause: The location specified by the /home startup switch does not exist.

Action: Check, and if necessary change, the location specified by the `/home` startup switch when starting the MTA. It must specify the domain directory. See “Using Monitor Agent Switches” in “Monitor” in the *GroupWise 7 Administration Guide*.

Possible Cause: The location specified by the `/home` startup switch is on a server that is currently not available.

Action: Check the status of the server where the specified directory is located. Wait for the server to come back up or contact the administrator of that server.

Possible Cause: The location might be on a server that is not currently mapped.

Action: Make sure the server where the Monitor Agent is running has a drive mapped to the domain directory on the server where the domain is located if it is using a mapped link.

GWMON: Request timed out waiting for response from GroupWise Monitor Agent

Source: GroupWise Monitor Application.

Explanation: The Monitor Application has been able to communicate successfully with the Monitor Agent, but the Monitor Agent has stopped responding.

Possible Cause: The server where the Monitor Agent is running has gone down.

Action: Resolve any network problems that are preventing GroupWise Monitor from functioning.

Possible Cause: The server where the Monitor Agent is running is overburdened or has insufficient system resources available, so that the Monitor Agent cannot respond to the Monitor Application in a timely manner.

Action: Make sure that the server where the Monitor Agent is running meets Monitor system requirements. See “Deciding Where to Install the GroupWise Monitor Components” in “Installing GroupWise Monitor” in the *GroupWise 7 Installation Guide*.

Possible Cause: The Monitor Agent has gone down.

Action: Restart the Monitor Agent. See “Starting the Monitor Agent” in “Monitor” in the *GroupWise 7 Administration Guide*.

GWMON: The URL to connect to the GroupWise Monitor Agent is invalid

Source: GroupWise Monitor Application.

Possible Cause: The Monitor Agent IP address and port number is not correct in the `gwmonitor.cfg` file.

Action: Check the `gwmonitor.cfg` file to make sure it provides the correct IP address and port number for the Monitor Agent. Correct the information as needed.

GWMON: Unable to communicate with GroupWise Monitor Agent

Source: GroupWise Monitor Application.

Possible Cause: The Monitor Agent is not running.

Action: Start the Monitor Agent. See “Starting the Monitor Agent” in “Monitor” in the *GroupWise 7 Administration Guide*.

Possible Cause: The server where the Monitor Agent is running has gone down.

Possible Cause: A router between the Monitor Application and the Monitor Agent is down.

Action: Resolve any network problems that are preventing GroupWise Monitor from functioning.

Possible Cause: Your firewall is preventing the Monitor Application from communicating with the Monitor Agent.

Action: Adjust the configuration of your firewall to accommodate communication between the Monitor Application and the Monitor Agent.

GWMON: Unable to connect to the MTA at IP_address:port

Source: GroupWise Monitor Agent.

Explanation: The Monitor Agent cannot connect to the MTA at the IP address and port you specified when prompted.

Action: Double-check the IP address and port number of the MTA that you want the Monitor Agent to communicate with.


Action: Make sure that the MTA is running with HTTP enabled. See “Using the MTA Web Console” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

GWMON: Unable to resolve GroupWise Monitor Agent’s host name to a valid IP address

Source: GroupWise Monitor Application.

Possible Cause: The Monitor Agent host name is not correct in the gwmonitor.cfg file.

Action: Check the gwmonitor.cfg file to make sure it provides the correct IP address and port number for the Monitor Agent. Correct the information as needed.



Administration Error Messages

The GroupWise® Administrator snap-in to ConsoleOne® is used to create and manage GroupWise objects. GroupWise Check is a standalone version of the Mailbox/Library Maintenance feature found in ConsoleOne.

This part of *Troubleshooting 1: Error Messages* helps you resolve error messages that might occur when you are using the GroupWise Administrator snap-in to ConsoleOne and error codes that might occur when you run GroupWise Check.

- ◆ “GroupWise Administrator Snap-In to ConsoleOne Error Messages” on page 225
- ◆ “GroupWise Check Error Codes” on page 233
- ◆ “GroupWise Time Stamp Utility Error Messages” on page 249

Other sources of assistance include:

- ◆ Novell® Support (<http://support.novell.com>)
- ◆ Novell Support Knowledgebase (http://support.novell.com/search/kb_index.jsp)
- ◆ GroupWise 7 Support Forums (<http://support.novell.com/forums/2gw.html>)
- ◆ Novell GroupWise Support Community (<http://support.novell.com/products/groupwise>)
- ◆ GroupWise Cool Solutions (<http://www.novell.com/coolsolutions/gwmag/index.html>)

GroupWise Administrator Snap-In to ConsoleOne Error Messages

- “0001 Cannot load resource” on page 226
- “0002 Schema not properly defined” on page 226
- “0003 Required DLL has incorrect version” on page 226
- “0004 Required DLL missing” on page 226
- “0005 Cannot read required information from NDS” on page 226
- “0006 GroupWise object missing required information” on page 227
- “0007 Cannot read required information from GroupWise database” on page 227
- “0008 Cannot delete subordinate objects” on page 227
- “0009 Cannot obtain UNC path” on page 227
- “0013 Out of memory” on page 227
- “0019 Cannot map local drive to network resource” on page 227
- “001D Cannot add non-GroupWise account to library membership” on page 227
- “0021 Gateway setup file not found” on page 228
- “0022 Cannot assign non-GroupWise user as administrator” on page 228
- “002D Pending move” on page 228
- “002E Pending delete” on page 228
- “0031 Cannot delete post office that owns GroupWise objects” on page 228
- “0032 Cannot delete domain that owns GroupWise objects” on page 229
- “0033 Cannot delete post office that owns GroupWise objects” on page 229
- “0035 Cannot read GroupWise information for object” on page 229
- “0036 Cannot access object in different GroupWise system” on page 229
- “0038 Owning object (domain/post office) not found in NDS” on page 229
- “0039 Invalid UNC path” on page 230
- “0041 Cannot authenticate” on page 230
- “0042 Cannot authenticate to requested tree” on page 230
- “0045 Domain database not found” on page 230
- “0049 Cannot move user from 6.x post office to 4.x post office” on page 230
- “0053 Parent domain database not found” on page 230
- “0054 Invalid drive specification” on page 230
- “0056 Non-networked drive” on page 231
- “0057 Cannot create another agent of this type in this context” on page 231
- “0059 Cannot create another GroupWise object” on page 231
- “0065 Cannot open domain database” on page 231
- “0069 Outbound MTA platform undefined” on page 231
- “00A2 Cannot set rights on software distribution directory” on page 231
- “0102 Password incorrect” on page 232

0001 Cannot load resource

Source: GroupWise® Administrator; general snap-in.

Explanation: Unable to load resource DLL.

Possible Cause: Invalid NWLANGUAGE environment specification.

Action: Make sure the NetWare® client is set up properly on the workstation where you are running ConsoleOne®.

0002 Schema not properly defined

Source: GroupWise Administrator; general snap-in.

Explanation: Schema error. The GroupWise schema extensions are not present.

Possible Cause: When you install GroupWise, the tree you are currently logged in to is extended. After installation, you run ConsoleOne and change to a tree that has not been extended.

Action: Log in to the tree you want extended, then rerun the installation to extend the schema on the second tree. See “[Setting Up a Basic GroupWise System](#)” in the “*GroupWise 7 Installation Guide*”.

Possible Cause: GroupWise installation did not complete successfully.

Action: Run Install from the root directory of the GroupWise CD. See “[Setting Up a Basic GroupWise System](#)” in the “*GroupWise 7 Installation Guide*”.

0003 Required DLL has incorrect version

Source: GroupWise Administrator; general snap-in.

Explanation: DLL version mismatch.

Possible Cause: An improper update of the GroupWise Administrator snap-in might have been loaded from Novell Support.

Action: Rerun GroupWise Install or acquire the latest GroupWise Administrator snap-in from Novell Support [Novell Support \(http://support.novell.com\)](http://support.novell.com).

0004 Required DLL missing

Source: GroupWise Administrator; general snap-in.

Explanation: One of the GroupWise Administrator snap-in DLL programs is missing.

Possible Cause: You are attempting to run ConsoleOne on a workstation that does not have GroupWise Administrator snap-in installed.

Action: Run ConsoleOne on a workstation where the GroupWise Administrator snap-in has already been installed.

0005 Cannot read required information from NDS

Source: GroupWise Administrator; general snap-in.

Explanation: GroupWise is unable to read necessary information from eDirectory™ (the current product name of Novell Directory Services).

Possible Cause: You have insufficient rights to read this information.

Action: Make sure you have sufficient rights to administer the objects in this GroupWise domain. If you have not been assigned sufficient rights, contact the system administrator.

0006 GroupWise object missing required information

Source: GroupWise Administrator; general snap-in.

Explanation: Invalid object state. The information for the eDirectory object is in an inconsistent state for GroupWise to use.

Action: Fill in the missing information by grafting the objects. For information about grafting, see “GW / eDirectory Association” in “System” in the *GroupWise 7 Administration Guide*.

0007 Cannot read required information from GroupWise database

Source: GroupWise Administrator; general snap-in.

Explanation: Unable to read the required information from the GroupWise database.

Possible Cause: Replication is in progress and has encountered inconsistent data.

Action: Make sure there are no pending operations. See “Pending Operations” in “System” in the *GroupWise 7 Administration Guide*. Then rebuild the database. See “Rebuilding Domain or Post Office Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

0008 Cannot delete subordinate objects

Source: GroupWise Administrator; general snap-in.

Explanation: Error deleting subordinate objects.

Possible Cause: You do not have rights to delete the subordinate objects.

Action: Make sure you have access and delete rights to the objects you are attempting to delete.

0009 Cannot obtain UNC path

Source: GroupWise Administrator; general snap-in.

Explanation: UNC path not available.

Action: Make sure you are logged in to the appropriate network and you have rights to the location.

0013 Out of memory

Source: GroupWise Administrator; database management.

Explanation: Out of memory error.

Action: Free up memory, then try the operation again.

0019 Cannot map local drive to network resource

Source: GroupWise Administrator; connection ID.

Explanation: GroupWise is unable to map a local drive to the network resource.

Action: Make sure the UNC specification is correct, that you have drives available to map, and that you have access to the network resource requested.

001D Cannot add non-GroupWise account to library membership

Source: GroupWise Administrator; document management.

Explanation: You cannot grant library membership to a user that does not have a GroupWise account.

Action: Add the user to GroupWise. See “[Creating GroupWise Accounts](#)” in “[Users](#)” in the *GroupWise 7 Administration Guide*.

0021 Gateway setup file not found

Source: GroupWise Administrator; gateway setup.

Explanation: A file required to run the gateway-specific setup was missing.

Possible Cause: The gateway installation was incomplete.

Action: Reinstall the gateway. For a list of gateways, see [GroupWise Gateways \(http://www.novell.com/documentation/gwgateways\)](http://www.novell.com/documentation/gwgateways).

0022 Cannot assign non-GroupWise user as administrator

Source: GroupWise Administrator; gateway setup.

Explanation: The gateway administrator must be either a GroupWise user or a GroupWise distribution list.

Action: Select a valid GroupWise user or distribution list as the gateway administrator. For a list of gateways, see [GroupWise Gateways \(http://www.novell.com/documentation/gwgateways\)](http://www.novell.com/documentation/gwgateways).

002D Pending move

Source: GroupWise Administrator; association.

Explanation: The record has been moved; however, GroupWise replication is still in progress. The record cannot be modified at this time.

Action: Wait for replication to complete, then retry the record modification. See “[Pending Operations](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*.

002E Pending delete

Source: GroupWise Administrator; association.

Explanation: The record has been moved; however, GroupWise replication is still in progress. The record cannot be deleted at this time.

Action: Wait for the replication to complete, then retry the operation. See “[Pending Operations](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*.

0031 Cannot delete post office that owns GroupWise objects

Source: GroupWise Administrator; delete visitor.

Explanation: You cannot delete this post office until all subordinate objects have been moved or deleted.

Possible Cause: The post office still owns one or more Agent objects.

Action: Delete any Agent objects using ConsoleOne.

Possible Cause: The post office still has users, resources, distribution lists, libraries, or library storage areas assigned to it.

Action: Move or delete each subordinate object in the post office. See “[Deleting a Post Office](#)” in “[Post Offices](#)” *GroupWise 7 Administration Guide*.

0032 Cannot delete domain that owns GroupWise objects

Source: GroupWise Administrator; delete visitor.

Explanation: You cannot delete this domain until all subordinate objects have been moved or deleted.

Possible Cause: The domain still owns one or more Agent objects.

Action: Delete any Agent objects.

Possible Cause: The domain still has post offices assigned to it.

Action: Move or delete the post offices. See “[Deleting a Post Office](#)” in “[Post Offices](#)” and “[Deleting a Domain](#)” in “[Domains](#)” in the *GroupWise 7 Administration Guide*.

0033 Cannot delete post office that owns GroupWise objects

Source: GroupWise Administrator; delete visitor.

Explanation: Cannot delete post office because it still has subordinate GroupWise objects.

Possible Cause: The post office still owns one or more agent objects.

Action: Delete any agent objects from the browser window.

Possible Cause: The post office still has users, resources, distribution lists, libraries, or library storage areas assigned to it.

Action: Move or delete each subordinate object in the post office, then delete the post office. See “[Deleting a Post Office](#)” in “[Post Offices](#)” in the *GroupWise 7 Administration Guide*.

0035 Cannot read GroupWise information for object

Source: GroupWise Administrator; association.

Explanation: Record not read.

Possible Cause: GroupWise replication is still in progress and the data has become inconsistent.

Action: Wait for the replication to complete, then rebuild the database. See “[Rebuilding Domain or Post Office Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

0036 Cannot access object in different GroupWise system

Source: GroupWise Administrator; association.

Possible Cause: You are accessing an object in eDirectory that belongs to a different GroupWise system than the one you are connected to.

Action: Connect to the appropriate GroupWise system. See “[Connecting to a Domain](#)” in “[Domains](#)” in the *GroupWise 7 Administration Guide*.

0038 Owning object (domain/post office) not found in NDS

Source: GroupWise Administrator; association.

Explanation: Object does not exist in eDirectory (the current product name of Novell Directory Services).

Possible Cause: An invalid distinguished name (DN) was entered for the domain or post office that owns this object.

Action: Enter a valid distinguished name.

0039 Invalid UNC path

Source: GroupWise Administrator; UNC path validator.

Explanation: The UNC path entered does not specify a valid network resource.

Action: Enter a correct UNC path.

0041 Cannot authenticate

Source: GroupWise Administrator; eDirectory operation.

Explanation: The NetWare login DLL file was not found. GroupWise was unable to authenticate.

Possible Cause: Your NetWare client installation was incomplete.

Action: Reinstall the NetWare client.

0042 Cannot authenticate to requested tree

Source: GroupWise Administrator; eDirectory operation.

Explanation: GroupWise was unable to authenticate to the requested tree.

Action: Make sure you have proper rights. Contact the system administrator.

0045 Domain database not found

Source: GroupWise Administrator; class definition.

Explanation: You are not currently connected to a GroupWise domain database (**wppdomain.db**). The requested operation cannot be completed.

Action: Connect to an existing GroupWise domain. See “**Connecting to a Domain**” in “**Domains**” in the *GroupWise 7 Administration Guide*.

0049 Cannot move user from 6.x post office to 4.x post office

Source: GroupWise Administrator; 6.x to 4.x move.

Explanation: GroupWise does not support moving users from a GroupWise 6.x or 7 post office to a GroupWise 4.x post office.

Action: You might want to consider migrating your 4.1 system to GroupWise 5.

0053 Parent domain database not found

Source: GroupWise Administrator; visitor base.

Explanation: GroupWise was unable to locate the domain database (**wppdomain.db**) for the requested action. The network resource is unavailable.

Action: Retry the operation.

0054 Invalid drive specification

Source: GroupWise Administrator; visitor base.

Explanation: GroupWise is unable to determine a local path from the drive specification.

Action: Enter a valid path.

0056 Non-networked drive

Source: GroupWise Administrator; visitor base.

Explanation: You are attempting to create a GroupWise domain or post office on a non-networked location that might become unavailable.

Action: You should create domains and post offices where network users will have permanent access to them.

0057 Cannot create another agent of this type in this context

Source: GroupWise Administrator; visitor base.

Explanation: Agents are limited based on context. For example, only one MTA per domain can exist. The maximum number of this agent type already exist in this context.

Action: You cannot create another agent of this type in the selected context.

0059 Cannot create another GroupWise object

Source: GroupWise Administrator; visitor base.

Explanation: You are running a limited evaluation version of GroupWise. This GroupWise system is limited to one domain and two post offices, with a maximum of three users on each post office.

Action: You can upgrade this evaluation software by purchasing and installing the shipping version of GroupWise.

0065 Cannot open domain database

Source: GroupWise Administrator; system-wide operations.

Explanation: The domain database (**wpdomain.db**) from which GroupWise Administrator is reading information has become unavailable. The original database will continue to be used until ConsoleOne is restarted.

Possible Cause: The server where the domain database is located has gone down so the drive mapping is no longer valid.

Action: Check the status of the server.

Possible Cause: The domain database is damaged.

Action: Check and, if necessary, repair the domain database. See **“Maintaining Domain and Post Office Databases”** in **“Databases”** in the *GroupWise 7 Administration Guide*.

0069 Outbound MTA platform undefined

Source: GroupWise Administrator; link tool.

Explanation: Information in the Link Configuration Tool is displayed based on the domain’s MTA platform.

Possible Cause: MTA settings error. The default outbound MTA platform is NetWare®.

Action: Set the outbound MTA platform to the appropriate platform type. See **“Configuring the MTA”** in **“Message Transfer Agent”** in the *GroupWise 7 Administration Guide*.

00A2 Cannot set rights on software distribution directory

Source: GroupWise Administrator; automatic rights.

Explanation: GroupWise Administrator could not automatically set the correct rights to the software distribution directory.

Possible Cause: The software distribution directory is located on a server located in a different tree from the post office.

Action: Create a software distribution directory in the same tree as the post office. See “[Creating a Software Distribution Directory](#)” in “[System](#)” in the *GroupWise 7 Administration Guide*.

0102 Password incorrect

Source: GroupWise Administrator; temporary password.

Explanation: Passwords do not match.

Action: Enter the correct password.

GroupWise Check Error Codes

GWCheck generates two sets of numeric codes: error codes and problem codes. Both sets of codes are in the same numeric range, but error codes are clearly labeled as errors, for example, “Error 9”.

The GWCheck problem codes are not documented because there is nothing you as an administrator need to do about the problems GWCheck is reporting. GWCheck fixes these problems for you.

The numeric codes listed below are GWCheck error codes, and actions to help you resolve the errors are provided.

- “01 Memory initialization error” on page 234
- “02 WPHOST.DB database read error” on page 234
- “03 Record read error” on page 235
- “04 User record has no DS_HOST_NAME” on page 235
- “05 User record has no DS_OBJ_TYPE” on page 235
- “06 User record has no DS_FID” on page 235
- “07 User record has no DS_USER_NETID” on page 235
- “08 User database read error” on page 235
- “09 Message database read error” on page 236
- “10 Message record read error” on page 236
- “11 Unable to start database transaction” on page 236
- “12 Record failed commit” on page 236
- “13 Record failed modify” on page 237
- “14 Record delete failed commit” on page 237
- “15 Record failed delete” on page 237
- “16 User does not exist in post office” on page 238
- “17 Post office does not exist in domain” on page 238
- “18 Message database open error” on page 238
- “19 WPHOST.DB database open error” on page 238
- “20 User record has no DS_DOMAIN_NAME” on page 238
- “21 Unable to decrypt database” on page 239
- “23 Unable to rename file for rebuild backup” on page 239
- “24 Path modify error” on page 239
- “25 Database create error” on page 239
- “26 Database rebuild error” on page 239
- “28 User file already exists or current file inaccessible” on page 240
- “29 User database close error” on page 240
- “30 User database not found” on page 240
- “31 Exclusive access denied to user database” on page 240
- “32 User database open error” on page 241

“33 Error initializing database engine code” on page 241
“34 Unable to get post office information” on page 241
“35 Memory allocation error” on page 241
“36 Message database not found” on page 241
“37 Exclusive access denied to message database” on page 242
“38 Error writing message record as user outbox item” on page 242
“39 Error writing message record as user inbox item” on page 242
“41 All substitute filenames used for rename of database” on page 242
“42 Invalid database; truncated to nn bytes” on page 242
“43 Dictionary file missing; cannot continue” on page 243
“44 Database invalid due to security breach” on page 243
“47 Error in library sync with host” on page 243
“48 Orphaned QuickFinder index file” on page 243
“49 Invalid QuickFinder index file” on page 243
“50 Orphaned blob file” on page 243
“51 Invalid blob file” on page 244
“52 Blob file missing trailer” on page 244
“53 Blob file truncated to 0 bytes” on page 244
“61 Error adding system document type definition” on page 244
“62 Error reading system document type definition” on page 244
“63 Unable to update during check error code” on page 244
“64 Unable to complete verify during check error code” on page 244
“65 Unable to add default system document types” on page 245
“66 Unable to correct document display name” on page 245
“67 Unable to correct element without version object” on page 245
“68 Unable to synchronize document security” on page 245
“69 Unable to correct document without version object” on page 245
“70 Unable to correct version without document” on page 246
“71 Unable to correct version without element” on page 246
“72 Invalid user specified for orphan document reassignment” on page 246
“73 Unable to remove document storage area” on page 246
“74 Unable to move all blobs; storage area cannot be removed” on page 246
“75 Unable to move blob” on page 247
“76 Error accessing document content” on page 247
“77 Error accessing blob for official version distribution list” on page 247
“78 Error accessing blob for current version distribution list” on page 247
“79 Error accessing blob for version distribution list” on page 247

01 Memory initialization error

Source: GroupWise® Check utility (GWCheck).

Explanation: Insufficient memory to run GWCheck.

Action: Run GWCheck where adequate memory is available.

02 WPHOST.DB database read error

Source: GroupWise Check utility (GWCheck).

- Explanation: GWCheck cannot access the post office database (**wphost.db**) for Address Book information.
- Action: In ConsoleOne[®], rebuild the post office database. See “**Rebuilding Domain or Post Office Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.
- Action: For additional information, look up the associated engine error code in “**GroupWise Engine Error Codes**” on page 9.

03 Record read error

- Source: GroupWise Check utility (GWCheck).
- Explanation: GWCheck cannot read records from the post office database (**wphost.db**).
- Action: In ConsoleOne, rebuild the post office database. See “**Rebuilding Domain or Post Office Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.
- Action: For additional information, look up the associated engine error code in “**GroupWise Engine Error Codes**” on page 9.

04 User record has no DS_HOST_NAME

- Source: GroupWise Check utility (GWCheck).
- Explanation: GWCheck encountered an invalid user record in the post office database (**wphost.db**).
- Action: In ConsoleOne, rebuild the post office database. See “**Rebuilding Domain or Post Office Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

05 User record has no DS_OBJ_TYPE

- Source: GroupWise Check utility (GWCheck).
- Explanation: GWCheck encountered an invalid user record in the post office database (**wphost.db**).
- Action: In ConsoleOne, rebuild the post office database. See “**Rebuilding Domain or Post Office Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

06 User record has no DS_FID

- Source: GroupWise Check utility (GWCheck).
- Explanation: GWCheck encountered an invalid user record in the post office database (**wphost.db**).
- Action: In ConsoleOne, rebuild the post office database. See “**Rebuilding Domain or Post Office Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

07 User record has no DS_USER_NETID

- Source: GroupWise Check utility (GWCheck).
- Explanation: GWCheck encountered an invalid user record in the post office database (**wphost.db**).
- Action: In ConsoleOne, rebuild the post office database. See “**Rebuilding Domain or Post Office Databases**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

08 User database read error

- Source: GroupWise Check utility (GWCheck).
- Explanation: GWCheck cannot read records from the specified user database (**userxxx.db**).

Action: Perform a structural analyze/fix on the user database. See “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: For additional information, look up the associated engine error code in “[GroupWise Engine Error Codes](#)” on page 9.

09 Message database read error

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot read records from the specified message database (*msgnnn.db*).

Action: Perform a structural analyze/fix on the message database by supplying the name of the message database in the User/Resource field. See “[Rebuilding Domain or Post Office Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: If the message database cannot be repaired, manually restore it from backup.

Action: For additional information, look up the associated engine error code in “[GroupWise Engine Error Codes](#)” on page 9.

10 Message record read error

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot read a specific record in a message database (*msgnnn.db*).

Action: Perform a structural analyze/fix on the message database by supplying the name of the message database in the User/Resource field. See “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: If the message database cannot be repaired, manually restore it from backup. See “[Restoring GroupWise Databases from Backup](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

11 Unable to start database transaction

Source: GroupWise Check utility (GWCheck).

Explanation: The specified database is locked or otherwise inaccessible.

Action: Retry. There might have been a timing problem with another database user.

Action: See if another program, such as the POA, has the database open with exclusive access and has hung with the database open.

Action: For additional information, look up the associated engine error code in “[GroupWise Engine Error Codes](#)” on page 9.

12 Record failed commit

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot write a modified record back to the database.

Action: Retry. There might have been a timing problem with another database user.

Action: See if another program, such as the POA, has the database open with exclusive access and has hung with the database open.

Action: For additional information, look up the associated engine error code in “[GroupWise Engine Error Codes](#)” on page 9.

13 Record failed modify

- Source: GroupWise Check utility (GWCheck).
- Explanation: GWCheck cannot write a modified record back to the database.
- Possible Cause: The record is unavailable. Another user has the record locked.
- Action: Retry. There might have been a timing problem with another database user.
- Action: See if another program, such as the POA, has the database open with exclusive access and has hung with the database open.
- Possible Cause: The record is damaged.
- Action: Perform a structural analyze/fix on the database. See “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Action: If the database cannot be repaired, manually restore it from backup. See “[Restoring GroupWise Databases from Backup](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Action: For additional information, look up the associated engine error code in “[GroupWise Engine Error Codes](#)” on page 9.

14 Record delete failed commit

- Source: GroupWise Check utility (GWCheck).
- Explanation: GWCheck cannot delete a record from the database.
- Possible Cause: The record is unavailable.
- Action: Retry. There might have been a timing problem with another database user.
- Action: See if another program, such as the POA, has the database open with exclusive access and has hung with the database open.
- Possible Cause: The record is damaged.
- Action: Perform a structural analyze/fix on the database. See “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.
- Action: If the database cannot be repaired, manually restore it from backup.
- Action: For additional information, look up the associated engine error code in “[GroupWise Engine Error Codes](#)” on page 9.

15 Record failed delete

- Source: GroupWise Check utility (GWCheck).
- Explanation: GWCheck cannot delete a record from the database.
- Possible Cause: The record is unavailable.
- Action: Retry. There might have been a timing problem with another database user.
- Action: See if another program, such as the POA, has the database open with exclusive access and has hung with the database open.
- Possible Cause: The record is damaged.
- Action: Perform a structural analyze/fix on the database. See “[Maintaining User/Resource and Message Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: If the database cannot be repaired, restore it from backup. See “Restoring GroupWise Databases from Backup” in “Databases” in the *GroupWise 7 Administration Guide*.

Action: For additional information, look up the associated engine error code in “GroupWise Engine Error Codes” on page 9.

16 User does not exist in post office

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot locate the specified user ID.

Action: Make sure you typed the user ID correctly in the User/Resource field in GWCheck.

Action: If the user ID is typed correctly, make sure you provided the correct information in the Database Path and Post Office Name fields for the post office where the user resides.

17 Post office does not exist in domain

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot locate the specified post office.

Action: Make sure you provided the correct information for the post office in the Database Path and Post Office Name fields.

18 Message database open error

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot open the specified message database (*msgnnn.db*).

Action: Perform a structural analyze/fix on the message database by supplying the name of the message database in the User/Resource field. See “Maintaining User/Resource and Message Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

Action: If the message database cannot be repaired, manually restore it from backup.

Action: For additional information, look up the associated engine error code in “GroupWise Engine Error Codes” on page 9.

19 WPHOST.DB database open error

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot open the post office database (*wphost.db*).

Action: In ConsoleOne, rebuild the post office database. See “Rebuilding Domain or Post Office Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

Action: For additional information, look up the associated engine error code in “GroupWise Engine Error Codes” on page 9.

20 User record has no DS_DOMAIN_NAME

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck encountered an invalid user record in the post office database (*wphost.db*).

Action: In ConsoleOne, rebuild the post office database. See “Rebuilding Domain or Post Office Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

21 Unable to decrypt database

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck encountered an invalid user record in the post office database ([wphost.db](#)).

Action: In ConsoleOne, rebuild the post office database. See [“Rebuilding Domain or Post Office Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

23 Unable to rename file for rebuild backup

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot create a backup copy of the existing database.

Possible Cause: All valid backup database filenames have already been used.

Action: Check for existing backup databases with extensions .dba through .dbz. If all 26 backup extensions have been used, delete old backup databases so valid backup extensions are available.

Possible Cause: Insufficient disk space.

Action: Free up disk space by deleting unneeded files.

Possible Cause: Insufficient rights.

Action: Make sure you have write access to the directory where the database being repaired is located.

24 Path modify error

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot create a needed directory path.

Action: Check rights and available disk space.

Action: For additional information, look up the associated engine error code in [“GroupWise Engine Error Codes”](#) on page 9.

25 Database create error

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot create a new user database ([userxxx.db](#)).

Possible Cause: Insufficient disk space.

Action: Free up disk space by deleting unneeded files.

Possible Cause: Insufficient rights.

Action: Make sure you have write access to the directory where the database being repaired is located.

Action: For additional information, look up the associated engine error code in [“GroupWise Engine Error Codes”](#) on page 9.

26 Database rebuild error

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot rebuild the database.

Possible Cause: Insufficient disk space.

Action: Free up disk space by deleting unneeded files.

Possible Cause: Insufficient rights.

Action: Make sure you have write access to the directory where the database being repaired is located.

Possible Cause: All valid backup database filenames have already been used.

Action: Check for existing backup databases with extensions .dba through .dbz. If all 26 backup extensions have been used, delete old backup databases so valid backup extensions are available.

Action: For additional information, look up the associated engine error code in “[GroupWise Engine Error Codes](#)” on page 9.

28 User file already exists or current file inaccessible

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot create a backup copy of the existing database.

Possible Cause: Insufficient disk space.

Action: Free up disk space by deleting unneeded files.

Possible Cause: Insufficient rights.

Action: Make sure you have write access to the directory where the database being repaired is located.

29 User database close error

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot close the specified user database ([userxxx.db](#)).

Possible Cause: Insufficient rights.

Action: Make sure you have write access to the directory where the repaired database will be written.

Action: For additional information, look up the associated engine error code in “[GroupWise Engine Error Codes](#)” on page 9.

30 User database not found

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot locate the specified user database ([userxxx.db](#)) to check.

Possible Cause: You specified the user incorrectly.

Action: Make sure you typed the user name correctly in the User/Resource field in GWCheck.

Possible Cause: The user database is missing from the post office.

Action: Re-create the user database. See “[Re-creating a User Database](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Action: Restore the user database from backup.

Action: If the user name is typed correctly, make sure you provided the correct information in the Database Path and Post Office Name fields for the post office where the user resides.

31 Exclusive access denied to user database

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot get sufficient access to the specified user database ([userxxx.db](#)).

Possible Cause: Insufficient rights.

Action: Make sure you have write access to the user database.

Action: Retry. There might have been a timing problem with another database user.

Action: See if another program, such as the POA, has the database open with exclusive access and has hung with the database open.

32 User database open error

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot open the specified user database (`userxxx.db`).

Action: Retry. There might have been a timing problem with another database user.

Action: See if another program, such as the POA, has the database open with exclusive access and has hung with the database open.

Action: For additional information, look up the associated engine error code in “GroupWise Engine Error Codes” on page 9.

33 Error initializing database engine code

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot initialize the database engine code.

Possible Cause: Insufficient rights.

Action: Make sure you have write access to the database to repair.

Action: For additional information, look up the associated engine error code in “GroupWise Engine Error Codes” on page 9.

34 Unable to get post office information

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot read information from the post office database (`wphost.db`).

Action: In ConsoleOne, rebuild the post office database. See “Rebuilding Domain or Post Office Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

Action: For additional information, look up the associated engine error code in “GroupWise Engine Error Codes” on page 9.

35 Memory allocation error

Source: GroupWise Check utility (GWCheck).

Explanation: Insufficient memory to run GWCheck.

Action: Run GWCheck where adequate memory is available.

36 Message database not found

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot locate the specified message database (`msgnnn.db`).

Action: Restore the message database from backup.

37 Exclusive access denied to message database

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot get sufficient access to the specified message database (*msgnmn.db*).

Possible Cause: Insufficient rights.

Action: Make sure you have write access to the directory where the message database is located.

Action: Retry. There might have been a timing problem with another database user.

Action: See if another program, such as the POA, has the database open with exclusive access and has hung with the database open.

38 Error writing message record as user outbox item

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot add a message as a received item in a user's mailbox.

Action: Perform a structural analyze/fix on the user's message database by supplying the name of the message database in the User/Resource field. See [“Maintaining User/Resource and Message Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

Action: For additional information, look up the associated engine error code in [“GroupWise Engine Error Codes”](#) on page 9.

39 Error writing message record as user inbox item

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot add a message as a sent item in a user's mailbox.

Action: Perform a structural analyze/fix on the user's message database by supplying the name of the message database in the User/Resource field. See [“Maintaining User/Resource and Message Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

Action: For additional information, look up the associated engine error code in [“GroupWise Engine Error Codes”](#) on page 9.

41 All substitute filenames used for rename of database

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck uses file extensions .dba through .dbz for backup copies of databases. All valid backup database names have already been used.

Action: Delete old backup databases so valid backup extensions are available.

42 Invalid database; truncated to nn bytes

Source: GroupWise Check utility (GWCheck).

Explanation: The database has been modified externally to an illegal size.

Action: Perform a structural rebuild on the user database. See [“Performing a Structural Rebuild of a User Database”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

Action: Perform a structural rebuild on the user's message database by supplying the name of the message database in the User/Resource field. See [“Analyzing and Fixing User and Message Databases”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

Action: Restore the database from backup.

43 Dictionary file missing; cannot continue

Source: GroupWise Check utility (GWCheck).

Explanation: The specified database dictionary (.dc) file is missing from the post office.

Action: Copy the missing *.dc file from the **po** subdirectory of the software distribution directory to the post office directory. See “[Software Distribution Directory](#)” and “[Post Office Directory](#)” in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure*.

44 Database invalid due to security breach

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot open the specified database because it contains an invalid verification record.

Possible Cause: The database has been modified in some unauthorized way.

Possible Cause: The database has been copied from another post office.

Action: Restore the original database from backup.

47 Error in library sync with host

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck synchronizes information in the library database (**dmsb.db**) with information in the post office database (**wphost.db**).

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See “[Analyzing and Fixing Library and Document Information](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

Possible Cause: The post office database is damaged.

Action: In ConsoleOne, rebuild the post office database. See “[Rebuilding Domain or Post Office Databases](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

48 Orphaned QuickFinder index file

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck encountered a QuickFinder™ index file that was not associated with any library.

Action: None. GWCheck deleted the extraneous index file.

49 Invalid QuickFinder index file

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck encountered an invalid QuickFinder index file.

Action: None. GWCheck deleted the invalid index file.

50 Orphaned blob file

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck encountered a BLOB file that was not associated with any library.

Action: None. GWCheck deleted the extraneous BLOB file.

51 Invalid blob file

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck encountered an invalid BLOB file.

Action: None. GWCheck deleted the invalid BLOB file.

52 Blob file missing trailer

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck encountered a BLOB file that did not have a trailer.

Action: None. GWCheck deleted the invalid BLOB file.

53 Blob file truncated to 0 bytes

Source: GroupWise Check utility (GWCheck).

Explanation: The specified BLOB file has been modified externally to an illegal size.

Action: Restore the original BLOB file from backup.

61 Error adding system document type definition

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot add the specified document type definition to the library database (**dmsh.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See [“Analyzing and Fixing Library and Document Information”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

62 Error reading system document type definition

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot read the specified document type definition in the library database (**dmsh.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See [“Analyzing and Fixing Library and Document Information”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

63 Unable to update during check error code

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot write changes to the library database (**dmsh.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See [“Analyzing and Fixing Library and Document Information”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

64 Unable to complete verify during check error code

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot verify the library database (**dmsh.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See “[Analyzing and Fixing Library and Document Information](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

65 Unable to add default system document types

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot add default document types to the library database (**dmsh.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See “[Analyzing and Fixing Library and Document Information](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

66 Unable to correct document display name

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot modify the specified document display name in the library database (**dmsh.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See “[Analyzing and Fixing Library and Document Information](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

67 Unable to correct element without version object

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot correct the specified element because version information was missing in the library database (**dmsh.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See “[Analyzing and Fixing Library and Document Information](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

68 Unable to synchronize document security

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot synchronize security information for the specified document in the library database (**dmsh.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See “[Analyzing and Fixing Library and Document Information](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

69 Unable to correct document without version object

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot correct the specified document because the version information was missing in the library database (**dmsh.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See “[Analyzing and Fixing Library and Document Information](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

70 Unable to correct version without document

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot correct the version information because the specified document was missing in the library database (**dmsb.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See “[Analyzing and Fixing Library and Document Information](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

71 Unable to correct version without element

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot correct the version information for a document because the specified element was missing in the library database (**dmsb.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See “[Analyzing and Fixing Library and Document Information](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

72 Invalid user specified for orphan document reassignment

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot locate the user ID specified in the New Author field in GWCheck.

Action: Make sure you typed the user name correctly in the New Author field.

Action: If the user name is typed correctly, make sure you provided the correct information in the Database Path and Post Office Name fields for the post office where the user resides.

73 Unable to remove document storage area

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot delete the specified document storage area.

Possible Cause: Insufficient rights.

Action: Make sure you have rights to the directory where the document storage area is located.

74 Unable to move all blobs; storage area cannot be removed

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot delete the specified storage area because BLOBs still exist in it.

Possible Cause: Insufficient disk space.

Action: Make sure there is free disk space in the directory where you are trying to move the BLOBs to.

Possible Cause: Insufficient rights.

Action: Make sure you have rights to the directory where the document storage area is located.

75 Unable to move blob

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot move the specified BLOB file.

Possible Cause: Insufficient disk space.

Action: Make sure there is free disk space in the directory where you are trying to move the BLOBs to.

Possible Cause: Insufficient rights.

Action: Make sure you have rights to the directory where the document storage area is located.

76 Error accessing document content

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot read the content of the specified document.

Possible Cause: The library database (**dmsh.db**) is damaged.

Action: Perform a structural analyze/fix on the library. See [“Analyzing and Fixing Library and Document Information”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

77 Error accessing blob for official version distribution list

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot access the specified BLOB file containing the official version distribution list for a document in the library database (**dmsh.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See [“Analyzing and Fixing Library and Document Information”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

78 Error accessing blob for current version distribution list

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot access the specified BLOB file containing the official current distribution list for a document in the library database (**dmsh.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See [“Analyzing and Fixing Library and Document Information”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

79 Error accessing blob for version distribution list

Source: GroupWise Check utility (GWCheck).

Explanation: GWCheck cannot access the specified BLOB file containing the distribution list for a document in the library database (**dmsh.db**) in the post office.

Possible Cause: The library database is damaged.

Action: Perform a structural analyze/fix on the library. See [“Analyzing and Fixing Library and Document Information”](#) in [“Databases”](#) in the *GroupWise 7 Administration Guide*.

GroupWise Time Stamp Utility Error Messages

GWTMSTMP: Error setting time stamp

GWTMSTMP: Invalid user database

GWTMSTMP: Invalid user ID

GWTMSTMP: User login error

GWTMSTMP: Error setting time stamp

- Source: GroupWise® Time Stamp utility.
- Explanation: The Time Stamp utility could not write the date/time stamp information into the user database.
- Possible Cause: The user database is locked by another process.
- Action: Run the Time Stamp utility again.
- Possible Cause: The user database is damaged.
- Action: Run GroupWise Check (GWCheck) to repair the user database. See “**GroupWise Check**” in “**Databases**” in the *GroupWise 7 Administration Guide*.

GWTMSTMP: Invalid user database

- Source: GroupWise Time Stamp utility.
- Explanation: The Time Stamp utility could not process the user database you are running it on.
- Possible Cause: The file you specified using the `/userdb` switch is not a proper user database.
- Action: Make sure you specified a valid `userxxx.db` file.

GWTMSTMP: Invalid user ID

- Source: GroupWise Time Stamp utility.
- Explanation: The Time Stamp utility cannot identify a user database for the user ID you provided when you started it.
- Possible Cause: The GroupWise user ID you specified using the `/@u` switch is not a valid GroupWise user.
- Action: Double-check the GroupWise user ID and provide a valid one.

GWTMSTMP: User login error

- Source: GroupWise Time Stamp utility.
- Explanation: The Time Stamp utility cannot log in to the specified post office as the specified user.
- Possible Cause: The user ID provided with the `/@u` switch does not exist in the post office specified with the `/ph` switch.

Action: Correct either the user information or the post office information that you have provided.

Possible Cause: The user database is damaged.

Action: Run GroupWise Check (GWCheck) to repair the user database. See “GroupWise Check” in “Databases” in the *GroupWise 7 Administration Guide*

IV

Client Error Messages

This part of *Troubleshooting I: Error Messages* helps you resolve GroupWise® Windows client, Remote client, and Cross-Platform client error messages.

- ◆ “Windows Client Error Messages” on page 253
- ◆ “Remote Mode Windows Client Error Messages” on page 255
- ◆ “Cross-Platform Client Error Messages” on page 261

Other sources of assistance include:

- ◆ Novell® Support (<http://support.novell.com>)
- ◆ Novell Support Knowledgebase (http://support.novell.com/search/kb_index.jsp)
- ◆ GroupWise 7 Support Forums (<http://support.novell.com/forums/2gw.html>)
- ◆ Novell GroupWise Support Community (<http://support.novell.com/products/groupwise>)
- ◆ GroupWise Cool Solutions (<http://www.novell.com/cool solutions/gw mag/index.html>)

Windows Client Error Messages

Users might encounter two types of errors while using the GroupWise® Windows client:

- ◆ “Errors the User Can Resolve” on page 253
- ◆ “Errors the Administrator Must Resolve” on page 253

Errors the User Can Resolve

Explanation: When a GroupWise Windows client error can be fixed immediately by the user, the error message includes instructions.

Action: The user resolves the problem independently.

Errors the Administrator Must Resolve

Explanation: When a GroupWise Windows client error cannot be resolved by the user, it is typically accompanied by a GroupWise engine error code. See “GroupWise Engine Error Codes” on page 9.

Action: Look up the error code in “GroupWise Engine Error Codes” on page 9, then resolve the problem for the user.

Remote Mode Windows Client Error Messages

A previous request to retrieve items has not been completed
Cannot access your Master Mailbox
Cannot find the post office
Cannot find the post office in the specified path
Cannot find your remote Mailbox folder
Cannot log in to the gateway. Check the gateway login ID...
Cannot log in to the gateway. Check the gateway login password...
LDAP failure detected
Required information is missing from the connection
Some setup files are missing
The following information necessary to run GroupWise against...
The master GroupWise system is unable to process a request...
The master GroupWise system is unable to process your current...
This item uses a custom view that was not retrieved...
This transmission cannot be completed due to network problems
Unable to create folder
{filename.ext} could not be opened as a modem script file
{filename.ext} failed to open

A previous request to retrieve items has not been completed

- Source:** GroupWise® Windows client; Remote mode.
- Possible Cause:** Because requests sent to the master GroupWise system are processed and then returned to your Remote mailbox, there are times when your Remote mailbox waits for responses from the master system. If this is the case, making a new request will duplicate the response that is returned from the previous request, resulting in wasted transmission time and, possibly, long-distance charges.
- Action:** If you need a new request because of differing date ranges or item filtering, click Yes to confirm that an additional request is required. Otherwise, click No so the outstanding request will be processed completely before another request is issued.

Cannot access your Master Mailbox

- Source:** GroupWise Windows client; Remote mode.
- Possible Cause:** For GroupWise to access your Master Mailbox remotely, GroupWise must give your Master Mailbox password to the master GroupWise system. Otherwise, access is denied without the appropriate password.
- Action:** Run GroupWise before leaving your office, then set a password on your Master Mailbox.

- Action: If you are already away, have someone at your office set a password for you. Then, specify that password in Remote Options.
- Action: The administrator can reset the password for a user in ConsoleOne®. See “[Creating or Changing a Mailbox Password](#)” in “[Users](#)” in the *GroupWise 7 Administration Guide*. Notify the user of the new password.

Cannot find the post office

- Source: GroupWise Windows client; Remote mode.
- Possible Cause: The application is unable to use the provided network connection path. The path might be entered incorrectly or there might be network changes.
- Action: Verify that the specified network connection path is valid and points to a GroupWise master system post office.
- Action: Check the setting of the `/ph` startup switch used to start the GroupWise client.
- Action: In ConsoleOne, right-click the Post Office object, then click Properties. Verify that the `/ph` switch setting matches the path specified on the post office Identification page. On the network, make sure the specified location still exists.

Cannot find the post office in the specified path

- Source: GroupWise Windows client; Remote mode.
- Possible Cause: The path to your post office, as specified in your network connection, doesn't exist.
- Action: If you know the path will be valid at a later time, or if you're currently not logged on to your network, click No to accept the path. If you think the path is valid, click Yes to return to the Network Connection dialog box to edit or browse the path for accuracy. To check the path in ConsoleOne, right-click the Post Office > click Properties > verify the path specified on the post office Identification page. On the network, make sure the specified location still exists.

Cannot find your remote Mailbox folder

- Source: GroupWise Windows client; Remote mode.
- Possible Cause: The folder specified in Hit the Road or with the `/ps` startup switch on the command line doesn't exist.
- Action: Click Yes to let GroupWise create the folder for you, or click No, then modify the command line in Windows to include the existing directory.

Cannot log in to the gateway. Check the gateway login ID...

- Source: GroupWise Windows client; Remote mode.
- Possible Cause: The gateway login ID specified in the modem connection doesn't match the login ID of the gateway the modem is dialing.
- Action: Verify that the gateway login ID in the modem connection definition is correct. In ConsoleOne, double-click the Domain object where the gateway is located > double-click the Gateway object. On the GroupWise client Profiles page, select the profile that is not working > click Edit > verify the login ID displayed in the Remote Profile dialog box > correct it if necessary.

Cannot log in to the gateway. Check the gateway login password...

Source: GroupWise Windows client; Remote mode.

Possible Cause: The password to the gateway specified in the modem connection doesn't match the gateway password the modem is dialing. The password might be entered incorrectly or there might be a password change.

Action: Verify that the gateway password in the modem connection definition is correct. In ConsoleOne, double-click the Domain object where the gateway is located, then double-click the Gateway object. On the GroupWise client Profiles page, select the profile that is not working, then click Edit. Verify the password displayed in the Remote Profile dialog box and correct it if necessary.

LDAP failure detected

Source: GroupWise Windows client; Remote mode.

Explanation: A GroupWise client user is using LDAP to authenticate to GroupWise but GroupWise is unable to authenticate.

Possible Cause: The LDAP server is down.

Action: Contact the administrator of the LDAP server. For more information about using LDAP for authentication, see [“Providing LDAP Authentication for GroupWise Users”](#) in [“Post Office Agent”](#) in the *GroupWise 7 Administration Guide*.

Required information is missing from the connection

Source: GroupWise Windows client; Remote mode.

Possible Cause: The connection definition is incomplete.

Action: Verify the required information:

Phone Number for Modem Connections: To check the phone number in ConsoleOne, double-click the Domain object where the gateway is located, then double-click the Gateway object. On the GroupWise client Profiles page, select the profile that is not working, then click Edit. Verify the phone number displayed in the Remote Profile dialog box.

Gateway Login ID for Modem Connections: To check the gateway login ID in ConsoleOne, double-click the Domain object where the gateway is located, then double-click the Gateway object. On the GroupWise client Profiles page, select the profile that is not working, then click Edit. Verify the login ID displayed in the Remote Profile dialog box.

Gateway Password for Modem Connections: To check the gateway password in ConsoleOne, double-click the Domain object where the gateway is located, then double-click the Gateway object. On the GroupWise client Profiles page, select the profile that is not working, then click Edit. Verify the password displayed in the Remote Profile dialog box.

Path to Post Office for Network Connections: To check the path to the post office in ConsoleOne, right-click the Post Office object, then click Properties. Verify the path displayed in the post office Identification page.

IP Address and Port for TCP/IP Connections: To check the IP address and port in ConsoleOne, double-click the Post Office object to connect to, Right-click the POA object, then click Properties. In the Network Address box, click Edit. Verify the IP address and TCP port displayed in the Edit Network Address dialog box.

Some setup files are missing

Source: GroupWise Windows client; Remote mode.

Possible Cause: Some of the files needed to run the GroupWise client against your Remote mailbox are missing. These files might have been deleted inadvertently.

Action: Reinstall GroupWise on your computer. See “[Installing the GroupWise Windows and Cross-Platform Clients](#)” in the “*GroupWise 7 Installation Guide*”.

The following information necessary to run GroupWise against...

Action: GroupWise Windows client; Remote mode.

Possible Cause: Hit the Road sets up your Remote mailbox with all the needed setup information. If you didn't use Hit the Road, this message appears the first time you run the GroupWise client against your Remote mailbox after a new installation.

Action: Verify the necessary information:

- ◆ Full Name
- ◆ User ID
- ◆ Master Mailbox Password
- ◆ Domain
- ◆ Post Office
- ◆ Connection Definition

To check the first five items for a user in ConsoleOne, double-click the User object, then click GroupWise Account. The user's full name, user ID, domain, and post office are displayed. The user's GroupWise password can be reset if it has been forgotten.

To check the connection definition in ConsoleOne, double-click the Domain object where the gateway is located > double-click the Gateway object. Verify the information displayed on the GroupWise client Profiles page.

The master GroupWise system is unable to process a request...

Source: GroupWise Windows client; Remote mode.

Possible Cause: Transmission errors damaged a response file from the master GroupWise system.

Action: Send another request to the master GroupWise system to receive a new response file.

The master GroupWise system is unable to process your current...

Source: GroupWise Windows client; Remote mode.

Possible Cause: Your master GroupWise system encountered an error while processing your requests. Your master system might have a problem.

Action: Send another request to the master GroupWise system.

Action: Record the conditions under which you encountered the error. For technical services, see [Novell Support \(http://support.novell.com\)](http://support.novell.com).

This item uses a custom view that was not retrieved...

Source: GroupWise Windows client; Remote mode.

Possible Cause: The view file of an item you want to read is too large to download as specified in the Retrieve Options dialog box.

Action: In your Remote mailbox, right-click the item, then click Retrieve Selected Items. Or, click Remote > Send/Retrieve > Advanced, then click the Size Limits tab to increase the maximum size for attachments.

This transmission cannot be completed due to network problems

Source: GroupWise Windows client; Remote mode.

Possible Cause: This is caused by general failures in the network connection.

Action: Make sure your network software is operating correctly. You might also need to exit and restart Windows.

Action: Record the conditions under which you encountered the error. For technical services, see [Novell Technical Support](http://support.novell.com) (<http://support.novell.com>).

Unable to create folder

Source: GroupWise Windows client; Remote mode.

Possible Cause: The folder specified in the Hit the Road Wizard or with the /ps startup switch cannot be created. Either you don't have rights to the specified folder or the path includes more than one folder that does not exist.

Action: Modify the command line in Windows and include a valid path and folder in Hit the Road or with the /ps startup switch.

{filename.ext} could not be opened as a modem script file

Source: GroupWise Windows client; Remote mode.

Possible Cause: The file you specified to open is not in a script file format.

Action: If you want your script file to have the specified filename and overwrite the existing file, open the Modem Connection dialog box, then click Edit Script. Specify the script information, then click Save. Otherwise, select a different script filename

{filename.ext} failed to open

Source: GroupWise Windows client; Remote mode.

Possible Cause: This usually occurs because the script file is in use by another application or access to the file is restricted.

Action: Select a different filename, or open the Modem Connection dialog box > click Edit Script > enter the script information > click Save As.

Cross-Platform Client Error Messages

Users might encounter two general types of errors while using the GroupWise® Cross-Platform client:

- ◆ “Errors the User Can Resolve” on page 253
- ◆ “Errors the Administrator Must Resolve” on page 253

In addition, there are a few error messages specific to the Cross-Platform client:

Can't export to file
Error during updating mailbox
Failed to create directory

Errors the User Can Resolve

Explanation: When a GroupWise Cross-Platform client error can be fixed immediately by the user, the error message includes instructions.

Action: The user resolves the problem independently.

Errors the Administrator Must Resolve

Explanation: When a GroupWise Cross-Platform client error cannot be resolved by the user, it is typically accompanied by a GroupWise engine error code. See “GroupWise Engine Error Codes” on page 9.

Action: Look up the error code in “GroupWise Engine Error Codes” on page 9, then resolve the problem for the user.

Can't export to file

Source: GroupWise Cross-Platform client; Linux or Macintosh*.

Possible Cause: You have tried to save a message or attachment in a location where you do not have sufficient rights to perform the action.

Action: Choose a different directory.

Action: Obtain rights to the desired directory.

Error during updating mailbox

Source: GroupWise Cross-Platform client; Linux or Macintosh.

Possible Cause: The Cross-Platform client cannot update your Caching mailbox because there is a problem with your Caching mailbox.

Action: Use GroupWise Check to repair your Caching mailbox. See “Starting GWCheck on a Linux Workstation” in “Databases” in the *GroupWise 7 Administration Guide*.

Failed to create directory

Source: GroupWise Cross-Platform client; Linux or Macintosh.

Possible Cause: You have tried to create a Caching mailbox or an archive in a location where you do not have sufficient rights to perform the action.

Action: Choose a different directory.

Action: Obtain rights to the desired directory.